


# Product Environmental Profile

## AS-I INTERFACE 4 INPUTS 4 RELAY OUTPUT






## General information

Representative product	AS-I INTERFACE 4 INPUTS 4 RELAY OUTPUT - ASI20MT4I4OR
Description of the range	<p>The IP20 AS-Interface range meets the needs of integration in industrial automation. Its main objective is to allow quick connection of sensors and actuators to the PLC via a single cable providing both the transmission of data and power of sensors. The wiring system AS-Interface replaces the parallel wiring between the PLC and sensors / actuators. This range consists of ten modules belonging to the product family IP20 I/O.</p> <p>The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.</p>
Functional unit	To enable quick connection of sensors and actuators to the PLC via a single cable at 9,8W with an 80% use rate during 10 years.



## Constituent materials

Reference product mass	115,8 g including the product, its packaging and additional elements and accessories
------------------------	--



Plastics	28,5%
Metals	0,0%
Others	71,6%



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



## Additional environmental information

The AS-I INTERFACE 4 INPUTS 4 RELAY OUTPUT presents the following relevant environmental aspects


Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 18,8 g, consisting of cardboard (72%) and paper (28%)
Installation	The product does not require any specific installation operation.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials  This product contains Electronic card (45,1g) that should be separated from the stream of waste so as to optimize end-of-life treatment.  The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website  <a href="http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page">http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</a>  Recyclability potential: <b>12%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



## Environmental impacts

Reference life time	10 years			
Installation elements	The product does not require any specific installation operation.			
Use scenario	The product is in active mode 80% of the time and stand-by mode 20% of the time with a power use of 9,8W for 10 years.			
Geographical representativeness	Europe			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: France	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		AS-I INTERFACE 4 INPUTS 4 RELAY OUTPUT - ASI20MT4I4OR					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	1,34E-03	1,31E-03	0*	0*	2,92E-05	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	1,41E+00	6,35E-03	0*	0*	1,40E+00	0*
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	8,81E-02	3,31E-03	1,57E-05	0*	8,47E-02	3,18E-05
Contribution to global warming	kg CO <sub>2</sub> eq	3,41E+02	4,67E+00	0*	0*	3,36E+02	1,04E-01
Contribution to ozone layer depletion	kg CFC11 eq	2,25E-05	5,94E-07	0*	0*	2,19E-05	3,54E-09
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	7,78E-02	6,72E-04	0*	0*	7,71E-02	0*
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	1,22E+03	1,68E-01	0*	0*	1,22E+03	0*
Total Primary Energy	MJ	6,78E+03	5,81E+01	0*	0*	6,72E+03	0*



Optional indicators		AS-I INTERFACE 4 INPUTS 4 RELAY OUTPUT - ASI20MT4I4OR					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	3,87E+03	4,94E+01	0*	0*	3,82E+03	0*
Contribution to air pollution	m <sup>3</sup>	1,49E+04	3,90E+02	0*	0*	1,45E+04	1,73E+00
Contribution to water pollution	m <sup>3</sup>	1,43E+04	4,39E+02	2,46E+00	0*	1,39E+04	4,21E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	5,64E-03	5,64E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	8,57E+02	2,22E+00	0*	0*	8,55E+02	0*
Total use of non-renewable primary energy resources	MJ	5,92E+03	5,59E+01	0*	0*	5,87E+03	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	8,57E+02	1,95E+00	0*	0*	8,55E+02	0*
Use of renewable primary energy resources used as raw material	MJ	2,68E-01	2,68E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	5,92E+03	5,44E+01	0*	0*	5,87E+03	0*
Use of non renewable primary energy resources used as raw material	MJ	1,54E+00	1,54E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*

Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	5,90E+00	5,48E+00	0*	0*	1,75E-01	2,48E-01
Non hazardous waste disposed	kg	1,26E+03	1,16E+00	0*	0*	1,25E+03	0*
Radioactive waste disposed	kg	8,38E-01	5,77E-04	0*	0*	8,38E-01	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	3,61E-02	5,77E-03	0*	1,87E-02	0*	1,16E-02
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	2,93E-02	0*	0*	0*	0*	2,93E-02
Exported Energy	MJ	5,94E-05	5,53E-06	0*	5,39E-05	0*	0*

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP1311005_V2	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	09/2022		
Validity period	5 years	Information and reference documents	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Independent verification of the declaration and data			
Internal	X	External	
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »			

Schneider Electric Industries SAS

Country Customer Care Center  
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier  
 CS 30323  
 F- 92506 Rueil Malmaison Cedex  
 RCS Nanterre 954 503 439  
 Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

ENVPEP1311005\_V2

© 2019 - Schneider Electric – All rights reserved

09/2022