



TERMINAL LUG DATA ‡			
AMPERES	MAX WIRE	MIN WIRE	TYPE
30	#6 AWG	#12 AWG	AL
30	#6 AWG	#14 AWG	CU
60	#3 AWG	#12 AWG	AL
60	#3 AWG	#14 AWG	CU

DUAL DIMENSIONS: INCHES
MILLIMETERS

CATALOG NUMBER	VOLTAGE RATINGS	AMPERAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS																							
				240VAC						480VAC						600VAC											
				STD			MAX			STD			MAX			STD			MAX			250 VDC	600 VDC				
				1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø	1Ø	2Ø	3Ø						
H221DS	240VAC,250VDC	30	A	1 1/2*	-	3♦	3*	-	7 1/2♦	-	-	-	-	-	-	-	-	-	-	-	5*	-	-	-			
H221NDS	240VAC,250VDC	30																									
H321DS	240VAC,250VDC	30	B	1 1/2*	-	3♦	3*	-	7 1/2♦	-	-	-	-	-	-	-	-	-	-	-	5*	-	-	-			
H321NDS	240VAC,250VDC	30																									
H361DS	600VAC,600VDC	30	B	-	-	-	-	-	-	3*	-	5♦	7 1/2*	-	15♦	-	-	-	-	-	20	5*	-	10*	15*		
H361NDS	600VAC,600VDC	30																									
HU361DS	600VAC,600VDC	30	C	-	-	-	5*	-	10♦	-	-	-	-	-	-	-	-	-	-	-	10*	-	30	-	5*	-	15*
H222DS	240VAC,250VDC	60	A	3*	-	7 1/2♦	10*	-	15♦	-	-	-	-	-	-	-	-	-	-	-	10*	-	-	-			
H222NDS	240VAC,250VDC	60																									
H322DS	240VAC,250VDC	60	B	3*	-	7 1/2♦	10*	-	15♦	-	-	-	-	-	-	-	-	-	-	-	10*	-	-	-			
H322NDS	240VAC,250VDC	60																									

NOTES:
FINISH - TYPE 304 STAINLESS STEEL
UL LISTED - E2875
ALL NEUTRALS - INSULATED
SHORT CIRCUIT CURRENT RATINGS:
10,000 - RMS SYMMETRICAL AMPERES
WHEN USED IN CONJUNCTION WITH CLASS H OR K FUSES
200,000 RMS SYMMETRICAL AMPERES WHEN USED IN CONJUNCTION WITH CLASS R, J, OR T FUSES
* USE BOTH OUTER SWITCHING POLES.
♦ FOR CORNER GROUNDED DELTA, INSTALL NEUTRAL AND USE OUTER SWITCHING POLES FOR UNGROUNDED CONDUCTORS.
‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

HEAVY DUTY SAFETY SWITCHES
VISIBLE BLADES
30 & 60 AMPERE - SERIES F6
ENCLOSURE-NEMA TYPE 4, 4X AND 5 STAINLESS STEEL

SQUARE D
by **Schneider Electric**
DWG# 3178
NO.