

Distance from outside of flange to the circuit breaker mounting surface. 9.12 MIN, 19.25 MAX [232] **[489]** [232] 6.50 [165] 9.53 [242] 15.45 [393]

Catalog Number: 9422-TF2

Ratings: shown with holder for CLASS H, K, or R 200A/250V FUSES

UL File/Guide: E52369 CSA File/Guide: LR44199 Meets Standards: -

Weight: 25.4 lbs Wire Size: #6-250MCM Terminal torque: 375 lb-in

Mounting Hwd.: (4)-5/16-18 screws/(2)-1/4-20 screws

"THE SQUARE D COMPANY HAS PROPRIETARY RIGHTS TO THE INFORMATION CONTAINED HEREON, THIS INFORMATION REMAINS THE PROPERTY OF SQUARE D COMPANY AND MAY BE USED ONLY IN CONFORMANCE WITH INSTRUCTIONS ISSUED BY SQUARE D COMPANY. USER SHOULD VERIFY DRAWINGS ARE TO THE LATEST/CURRENT REVISION PRIOR TO INCORPORATING IN A DESIGN FILE."

THIRD ANGLE PROJECTION DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES 2 PLACE DECIMALS ± .01

TOLERANCES

DISCONNECT WITH HOLDER FOR CLASS H, K, OR R 200A/250V FUSES CLASS 9422 TYPE TF2



DWG# 9422 TF_OUTLINE_002

FEBRUARY 2001

E0102901