

Distance from outside of flange to the circuit breaker mounting surface. 9.12 MIN, 19.25 MAX [232] [489] 6.50 [165] 9.53 [242] 17.95 [456]

Catalog Number: 9422-TF2

shown with holder for CLASS H, K, or R 200A/600V FUSES Ratings:

UL File/Guide: E52369 CSA File/Guide: LR44199 Meets Standards: -Weiaht: 25.4 lbs Wire Size: #6-250MCM

Terminal torque: 375 lb-in **Mounting Hwd.:** (4)-5/16-18 screws/(2)-1/4-20 screws

"THE SQUARE D COMPANY HAS PROPRIETARY RIGHTS TO THE INFORMATION CONTAINED HEREON. THIS INFORMATION REMAINS THE PROPERTY OF SQUARE D COMPANY AND MAY BE USED ONLY IN CONFORMANCE WITH INSTRUCTIONS ISSUED BY SQUARE D COMPANY. USER SHOULD VERIFY DRAWINGS ARE TO THE LATEST/CURRENT REVISION PRIOR TO INCORPORATING IN A DESIGN FILE."

THIRD ANGLE BROJECTION DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED 2 PLACE DECIMALS ± .01 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES

DISCONNECT WITH HOLDER FOR CLASS H, K, OR R 200A/600V FUSES CLASS 9422 TYPE TF2



DWG# 9422 TF\_OUTLINE\_003

FEBRUARY 2001

E0103001