



TERMINAL LUG DATA †

| AMPERES | MAX WIRE | MIN WIRE | TYPE |
|---------|----------|----------|-------|
| 30 | # 6 AWG | # 12 AWG | AL CU |
| 30 | # 6 AWG | # 14 AWG | AL CU |
| 60 | # 3 AWG | # 12 AWG | AL CU |
| 60 | # 3 AWG | # 14 AWG | AL CU |

DUAL DIMENSIONS: INCHES
MILLIMETERS

| CATALOG NUMBER | VOLTAGE RATINGS | AMPERAGE RATINGS | WIRING DIAG | HORSEPOWER RATINGS | | | | | | | | | | | | | | | | | | | | | | |
|----------------|-----------------|------------------|-------------|--------------------|---|---|-----|---|---|--------|---|---|-----|--------|---|--------|---|---|--------|---|---|---------|-----|---------|-----|---|
| | | | | 240VAC | | | | | | 480VAC | | | | | | 600VAC | | | | | | 250 VDC | | 600 VDC | | |
| | | | | STD | | | MAX | | | STD | | | MAX | | | STD | | | MAX | | | STD | MAX | STD | MAX | |
| H361DSWC | 600VAC,250VDC | 30 | A | - | - | - | - | - | - | 3* | - | - | 5 | 7 1/2* | - | 15 | - | - | 7 1/2* | - | - | 20 | 5* | - | - | - |
| HJ361DSWC | 600VAC,250VDC | 30 | B | - | - | - | - | - | - | - | - | - | 5 | 7 1/2* | - | 20 | - | - | 7 1/2* | - | - | 30 | - | 5* | - | - |
| H362DSWC | 600VAC,250VDC | 60 | A | - | - | - | - | - | - | 5* | - | - | 15 | 20* | - | 30 | - | - | 20* | - | - | 50 | 10* | - | - | - |
| HJ362DSWC | 600VAC,250VDC | 60 | B | - | - | - | - | - | - | - | - | - | 15 | 25* | - | 50 | - | - | 25* | - | - | 60 | 10* | - | - | - |

NOTES:
 FINISH - TYPE 304 STAINLESS STEEL
 UL LISTED - E2875
 SHORT CIRCUIT CURRENT RATING
 10,000 RMS SYMMETRICAL AMPERES
 WHEN USED IN CONJUNCTION
 WITH CLASS H OR K FUSES.
 200,000 RMS SYMMETRICAL AMPERES WHEN USED
 IN CONJUNCTION WITH CLASS R, J, OR T FUSES.
 ♦ FOR CORNER GROUNDED DELTA INSTALL NEUTRAL USE AND BOTH OUTER SWITCHING
 * USE OUTER SWITCHING POLES.
 † LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS ONLY.

HEAVY DUTY SAFETY SWITCHES
VISIBLE BLADES
 30 & 60 AMPERE - SERIES F7
 ENCLOSURE - NEMA TYPE 4, 4X, AND 5 STAINLESS STEEL



DMC# 3179
 NO.