



NPXZ.E58760 Manual Motor Controllers for Use in Hazardous Locations

[Page Bottom](#)

Manual Motor Controllers for Use in Hazardous Locations

[See General Information for Manual Motor Controllers for Use in Hazardous Locations](#)**SCHNEIDER ELECTRIC USA, INC.**

E58760

8001 KNIGHTDALE BLVD
KNIGHTDALE, NC 27545-9023 USA



Trademark and/or Tradename:

Across-the-line starters, air break type with or without thermal overload protection.

Class I, Groups B, C, and D; Class II, Groups E, F and G. Class 2510, Types FR1, -2, -8, KR1, -2, -8, with or without suffix H, with or without Series B.

Across-the-line starters, air-break type with thermal overload protection.

Class I, Groups C and D; Class II, Groups E, F and G. Class 2510, Series A, Types MBR, MBT followed by -1*, -2*; Types MCR, MCT followed by -1, -2, -3.

Class 2510, Series A or B, Types MBR, MBT followed by -21*, -22*; Types MCR, MCT followed by -21, -22, -23.

*Suitable for use when protected by fuses or ratings greater than four times the full load current of the motors they are designed to control. Each device is marked with the rating of the maximum fuse with which it may be used.

[Last Updated](#) on 2012-09-06[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".