

ECOFIT™ for your MV Switchboard

WK(A/B/C/D/E/F) / MC - AL - BAL - TG [AEG, Alstom]

Medium voltage distribution

Achieve higher sustainable performance with ECOFIT™ modernization solution!



Benefits

- Extend your switchgear lifetime.
- Digitization, enable access to asset and energy management.
- Reduced environmental impact
- Enhance your process dependability.
- Optimize your maintenance service costs & limits your investments.
- New ECOFIT™ spare parts availability.

Maximize continuity of operation

- Life time extension for existing switchgear.
- Less downtime than with full panel replacement.
- Reduces plants shutdown time from days to hours.

World class manufacturer design

- Original manufacturer tested solution.
- Worldwide support with manufacturer warranty.
- No change of cables and no civil work.
- Safety of people and surrounding equipment.
- Improve reliability and quality with compliance to new standards.


Reduce environmental impact

- Access to energy management with digital products.
- Efficient use of natural resources by replacing only active components.
- Recycling of obsolete equipment (metals, plastics, SF6, etc).

Schneider Electric team with you

- Worldwide support.
- Manufacturer expertise.
- Skilled installation and commissioning experts.


Total Cost of Ownership evolution



WK(A/B/C/D/E/F) / MC - AL - BAL - TG with VAA - Contactor

Original brand: AEG

ECOFIT™ proposal



Main technical characteristics


MC-BAL-AL-TG	
Rated current (Ir)	630-3150A
Short circuit current (Isc)	31.5-50kA
Rated voltage Un (50/60 Hz)	Up to 36kV

VA-VAA- LTRI- FPX- Contactor		VA-VAA- LTRI- FPX- Contactor	
Technology	Vacuum	Switching sequence	0-0.3s-CO-3min-CO
Rated voltage Ur (kV)	3.6-12-24 -36	Closing time (ms)	20
Surge withstand voltage Up (kV)	60-110	Opening time (ms)	20-50
Nominal frequency (Hz)	50-60	Number of switching operations	10000
Rated current Ir (A)	400-4000	Service temperature (°C)	-5/+40
Short circuit current Isc (kA)	10-50		
Short circuit duration Tk (s)	3		

Note: vacuum solutions may require overvoltage protections.

Additional offer

- Remote racking available for higher operator safety
- Improve energy and asset management: replacement of old protection relay with digital and connected relay.



Schneider Electric Industries SAS
35 rue Joseph Monier
92500 Rueil-Malmaison, France
Phone: + 00 (0) 1 41 29 70 00
www.schneider-electric.com

Life Is On

