09 26 2012 12:54 PM Room 1705 Standby

Humidity Outdoor 45% 18°C ∨

\$%) \$\$ (*C ?

SpaceLogic™ Room Controllers

SE8000 Compatibility Matrix

		Schneider Electric SEx83, SE86 & SEZ82 ④																	
	SE8000		1.4		1.5	& 1.6	1	.7	2.0	2.1	2.2	2.3 ④	2.4	2.4.1	2.5	2.5.1	2.6	Description	Part List
	VCM8002 (Wi-Fi)										1.0	1.0	1.1	1.2	1.3	1.4	1.4	Wi-Fi Communication Module	VCM8002V5031
Plug-in Modules	VCM8000 (Zigbee Pro) ③ ⑥	6	9	10	9	10	10	20	20	22	23	24	30	30	31	31	32	Zigbee Pro Communication Module	VCM8000V5045P
	VCM8001 (CO2)				\checkmark	CO2 Sensor Module	VCM8001V5045												
Zigbee Pro Wireless Sensors	Window/Door	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	Window/Door Sensor	SED-WDC-G-5045
	Motion	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	Motion Sensor	SED-WDC-G-5045 SED-WMS-P-5045 and/or SED-MTH-G-5045 SED-CO2-G-5045 and/or SED-MTH-G-5045 and/or SED-TRH-G-5045
	Temperature						\checkmark	Temperature Sensor	SED-CO2-G-5045 and/or SED-MTH-G-5045 and/or SED-TRH-G-5045										
	Humidity						\checkmark	Humidity Sensor	SED-CO2-G-5045 and/or SED-MTH-G-5045 and/or SED-TRH-G-5045										
	CO2						\checkmark	CO2 Sensor	SED-CO2-G-5045										
	Water Leak						\checkmark	Water Leak Sensor	SED-WLS-G-5045										
SEC-TE	Rev 16 or later				√⊘	√⊘	√⑦	√⑦	√⊘	√⑦	√⊘	√⊘	√⊘	√⊘	√⊘	√⊘	√⊘	Smart Terminal Controller	SEC-TEA-24-5045SEC-TEA-230-5045And more Refer to SCE-TESEC-TEA-R-24-5045documentation for more information.SEC-TEA-R-230-5045SEC-TEA-R-230-5045
МРМ	Rev 2.18	√①	√1)		√①	√ ①	√1)											Multi-Purpose Manager	MPM-GW-010-5045 MPM-UN-004-5045 MPM-UN-014-5045 MPM-VA-004-5045 MPM-VA-014-5045 And more Refer to MPM documentation for more information.
	Rev 2.19	√①	√1)	√ <u></u>]	√①	√ <u></u>]	√1)	√ <u></u>]	√ <u></u>]	√①	√①	√ ①	√①	√①	√①	√①	√(<u>1</u>)		
	Rev 2.20	\checkmark	 ✓ 	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	√ <u></u>]	√①	√ ①	√ ①	√①	√①	√(<u>)</u>	√①	√ <u></u>]		
	Rev 2.21	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	√ <u></u>]	√①	√ ①	√①	√ ①	√①	√ ①	√ <u></u>]		
	Rev 2.22	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	√ <u></u>]	√ ①	√ ①	√①	√①	√(<u>)</u>	√①	√ <u></u>]		
Zigbee Pro Wireless USB Adapter ®													\checkmark	~	\checkmark	~	~	Wireless Adapter - Advanced	SXWZBAUSB10001
HRC	Rev 1.4 or later						√②	√2	√②	√②	√2	√2	√2	√2	√②	√2	√②	Hotel Room Controller	HRCPDG42R HRCPBG28R
Facility Expert													√5	√5	√5	√5	√5		
	Rev 1.0 and Rev 2.0	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark										1	
Uploader Tool	Rev 3.x						\checkmark												
	Rev 4.0								\checkmark	✓	\checkmark								
Uploader Tool Config. of Wi-Fi																\checkmark	\checkmark		

 \checkmark = Full objects supported.

① = Partial objects supported (missing new objects).

@ = HRC does not support CO2 and water leak sensors, and is not compatible with SE8650.

③ = Using older VCMs in the range 10-24 with SE8000 Room Controllers up to version 2.3 is not recommended, however will function with reduced features. From SE8000 version 2.4, VCM 30 or newer must be used.

④ = The SEZ8250 requires VCM8000 (Zigbee Pro) revision 24 and later.

⑤ = Facility Expert is compatible with SE8650 RTU, SE8350 and SER8350.

0 = The hardware revision number is found underneath the VCM module. The firmware (starting at version 20) on 051-0131R11 and later is upgradable and downgradable. The firmware on 051-0131R10 and earlier cannot be upgraded.

 \bigcirc = SEC-TE is compatible with SER8350 only.

(8) = The Wireless Adapter - Advanced enables Zigbee 3.0 wireless connectivity for AS-P/AS-B Automation Servers and RP-C/RP-V Room Purpose Controllers.

(9) = Zigbee network high security level support starts at SE8000 firmware revision 2.6 and Zigbee firmware revision 32.

(empty) = Not supported.

UPGRADE OF ZIGBEE FIRMWARE REVISION 24 TO 30

The upgrade from Zigbee firmware revision 24 to 30 will not support the Green Power Sensor (SED-CO2-G-5045 or SED-TRH-G-5045). It will therefore need to be recommissioned.

There is also a new "Security Levels" parameter for the Zigbee network:

•

TOUCHSCREEN ISSUES

A new Printed Circuit Board Assembly (PCBA) is used in the latest version of the Room Controller hardware:

• Firmware 2.5 and older: Does not work with the new hardware, making the touchscreen inoperative.

Firmware 2.6 or newer.

Schneider Flectric

NOTICE

• Low (default value) is fully backwards compatible with Zigbee Home Automation 1.2 devices, and therefore compatible with all of our sensors. Normal or High (needs to be selected by user) is only compatible with Green Power and Zigbee 3.0 network standard (Leedarson sensors). If the Normal or High Security Level is selected with old NYCE or Centralite sensors, they will be removed from the network.

Failure to follow these instructions can result in equipment being disconnected from the network.

NOTICE

• Firmware 2.6 and newer: Works with both the old and new hardware.

Do not downgrade the firmware on the new hardware. If you have issues with your Room Controller touchscreen, upgrade your device to

Failure to follow these instructions can result in equipment malfunction.