



## XC Wireless Switches for cable-less and energy-saving detection



### Wireless and battery-less Limit Switches in miniature format!

The groundbreaking wireless and battery-less limit switch technology from Telemecanique Sensors designed into in the most compact form on the market.

#### Wireless

The revolutionary wireless technology from Telemecanique Sensors simplifies machine communication where cabling is difficult, expensive, or unwanted. It is the perfect way to give mobile machines more freedom of movement. The wireless and battery-less technology also drastically reduces maintenance.

#### Easy to install

The bodies of the wireless and battery-less limit switches from Telemecanique Sensors have been designed to fit in extremely compact areas. They come in a plug-and-play kit and are offered in out-of-the-box compatible packs comprising the transmitter and a receiver.

#### Green and energy saving

The self-powered technology of XC Wireless and battery-less Limit Switches from Telemecanique Sensors eliminates battery replacement, battery recycling, and reduces raw materials. The wireless technology of XC Wireless and battery-less Limit Switches also eliminates cables and other materials necessary to connect power to the switch.

Simply easy!



**Telemecanique**  
Sensors



## Benefits

### Simplified, cost-effective installation & maintenance

- No cables means no cabling cost at installation
- No internal contacts significantly reduces maintenance cost

### Long-distance communication

- 100m (328 ft.) wireless range
- Range can be doubled with a dedicated antenna

### Energy efficient and environmentally friendly

- Self-powered, so there is no battery replacement or recycling costs
- Wireless communication eliminates cables, reducing material usage

## Characteristics

- Uses Zigbee® protocol for best-in-class communication performance
- Up to 100m (328 ft.) distance in open field
- Up to 32 transmitters per receiver (ZBRRC and ZBRRD receivers)
- Top performance with access point receiver through Modbus serial or Modbus/TCP protocol

## Part Numbers

### Transmitters (miniature format)

Part Number	Description
XCMW110	Metal end plunger
XCMW102	Metal roller plunger
XCMW115	Plastic roller lever
XCMW116	Metal roller lever
XCMW145	Adjustable length plastic roller lever

### Packages

Part Number	Description
XCMWD02	XCMW102 transmitter and ZBRRD receiver
XCMWD15	XCMW115 transmitter and ZBRRD receiver

### Receivers

Part Number	Outputs	Number of Transmitters	Optional Antenna
ZBRRC	4xPNP	32	ZBRA1
ZBRRD	2xRelays	32	ZBRA1
ZBRN1	Modbus TCP	60	ZBRA2
ZBRN2	Modbus RS485	60	ZBRA2

For our complete selection of sensor solutions, visit [www.tesensors.com](http://www.tesensors.com)

Schneider Electric Industries SAS  
Head Office  
35, rue Joseph Monier – CS 30323  
F92506 Rueil-Malmaison Cedex  
FRANCE

[www.tesensors.com](http://www.tesensors.com)

Due to the constant evolution of standards and equipment, the specifications indicated in the text and images of this document can only be guaranteed after confirmation by our departments. Print: Schneider Electric Photos: Schneider Electric

©2022 Schneider Electric. All Rights Reserved. Schneider Electric, OsiSense, and Telemecanique are trademarks and the property of Schneider Electric SE, its subsidiaries and affiliated companies. All other trademarks are the property of their respective owners.

January, 2022 9006HO1805 R01/22