

HU-003712-M1

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Ratings and principal characteristics

Trademark (if any)

Customer's Testing Facility (CTF) Stage used Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

Contactors

Schneider Electric Industries SAS 35 rue Joseph Monier 92500 Rueil-Malmaison, France

Schneider Electric Industries SAS 35 rue Joseph Monier 92500 Rueil-Malmaison, France

Schneider Electric Industries S. A. ZAC Le Village 27100 Le Vaudreuil, France

Ui:690V; Uimp:6kV; Ith:60...80A; Utilization category: AC-1, AC-3, AC-4, AC-3e; Ue:AC230...690V; Ie:21...80A; with electronic coils (See appendix of CB Test Certificate for further ratings)

Schneider Electric

N/A

LC1D40A, LC2D40A, LC1D50A, LC2D50A, LC1D65A, LC2D65A, LC1D80A, LC2D80A, LC1DT60A, LC2DT60A, LC1DT80A, LC2DT80A

This Certificate is Modification No.1 to CBTC ref. No. HU-003712, dated 2021-12-08, and is issued due to adding parameter.

IEC 60947-4-1:2018 IEC 60947-5-1:2016

CN2182N3 002

This CB Test Certificate is issued by the National Certification Body



TÜV Rheinland InterCert Kft., MEEI Division H-1143 Budapest, Gizella út 51-57., Hungary Web:www.tuv.com

Abrac 2ho

Date: 2022-07-27

Signature:

Wencai Zhang



HU-003712-M1

Appendix to CB Test Certificate, page 1/2

Type designation:

Possible values:

(1): Product type:

LC1: single contactor LC2: reversing contactor

(2): Size:

D40 (3 poles)

D50 (3 poles)

D65 (3 poles)

D80 (3 poles)

DT60 (4 poles)

DT80 (4 poles)

(3): Indication:

A: Tesys contactor range

(4): Type of connection: (Power / Control)

Blank: "Everlink" Connector / screws

3: "Everlink" Connector / spring connections

6: Ring lugs Connector / Ring lugs Connector

(5): Indicates front cover presence

Blank: Standard treatment (with cover)

5: without removable front cover

(6): Indicates Coil Voltage Code:

See table below

Electronic coils:

Coil code	Us (V)	Frequency
BBE	24	dc
BNE	24-60	50/60Hz and dc
EHE	48-130	50/60Hz and dc
KUE	100-250	50/60Hz and dc

Additional information (if necessary)

Nonau 2tag

Date: 2022-07-27 Signature: Wencai Zhang



HU-003712-M1

Appendix to CE	Test Certificate,	page 2/2
----------------	-------------------	----------

Ratings:

Ratings:								
Type or Reference		Utilization	Ue					
	Ith		230V	400V	440V	500V	690V	
		category	Ie					
LC1D40A,LC2D40A	60A	AC-4	38A	35A	40A	33A	21A	
		AC-3	38A	35A	40A	33A	32A	
		AC-3e	38A	35A	40A	33A	32A	
		AC-1	60A					
		AC-4	51A	41A	50A	33A	21A	
LC1D50A,LC2D50A	80A	AC-3	51A	41A	50A	44A	35A	
LC1D30A,LC2D30A	80A	AC-3e	51A	41A	50A	44A	35A	
		AC-1	80A					
		AC-4	61A	55A	50A	33A	21A	
LC1D65A,LC2D65A	80A	AC-3	61A	55A	65A	53A	39A	
		AC-3e	61A	55A	65A	53A	39A	
		AC-1	80A					
LC1D80A,LC2D80A		AC-4	61A	55A	50A	33A	21A	
	80A	AC-3	80A	80A	66A	53A	39A	
		AC-3e	61A	55A	66A	53A	39A	
		AC-1	80A					
LC1DT60A,LC2DT60A	60A	AC-1	60A					
LC1DT80A,LC2DT80A	80A	AC-1	80A					

Additional information (if necessary)

Abrau 2 tag

Date 2022-07-27 Signature: Wencai Zhang