

C-Bus Professional Series Dimmer



L5104D5 Series

The L5104D5 C-Bus Professional Series Dimmers are C-Bus output units suitable for dimming resistive and low voltage lighting loads in lighting applications.

Housed in an all aluminium heat sink, the dimmers have been designed for fast installation, with features such as keyhole mounting, cable access from both front and rear, ample termination space for mains cabling and removable terminals for the C-Bus and override connections.

All units in the series incorporate the C-Bus 'Learn Mode' feature. Learn mode allows the units to be programmed without the need for a PC connected to the system. Alternatively, the units can be programmed via a PC using the installation software.

The dimmers provide independent dimmable channels, operating from a single-phase mains voltage. They operate with any mains frequency in the range 47 - 53Hz and 57 - 63Hz, and will automatically re-synchronise when this frequency varies.

The L5104D5 C-Bus Professional Series Dimmers feature leading edge control capability, with a load rating of 4 channels x 5 Amps.

The C-Bus Professional Series Dimmers draw 12mA from the C-Bus network when not connected to the mains supply. With mains voltage connected the dimmer sources up to 60mA to the network.

Like all other units that make up a C-Bus system, the C-Bus L5104D5 Professional Series Dimmers are Australian designed, developed and manufactured by Clipsal Integrated Systems Pty Ltd.

clipsal.com/cis

L5104D5 C-Bus Professional Series Dimmer



- Load rating of 4 channels x 5 Amps.
- Incorporates an inbuilt power supply capable of sourcing 60mA to the C-Bus network, when mains voltage is connected.
- Capable of dimming resistive loads, inductive loads and electronic transformers compatible with leading edge dimmers.
- Continuously monitors incoming mains voltage and compensates for any change in the voltage level by adjusting the output drive to the load.
- Continuously tracks the mains frequency and adjusts the dimmer to ensure synchronisation to mains is maintained.
- The C-Bus Installation Software can be used to monitor load current in each individual channel.
- A special algorithm ensures that lights do not flicker due to signal injections on the mains.
- Each channel incorporates thermal overload and over-current protection.
- Incorporates a linear brightness control, which ensures the change in brightness is uniform throughout the control range.
- Incorporates a Soft Turn ON and Soft Turn OFF feature, providing a soft change in brightness.
- Configured via either the C-Bus Installation Software or via the Learn Enabled Features.
- Local ON/OFF toggle buttons allow individual channels to be manually overridden at each unit.
- Remote ON and OFF facility permits all channels to be turned ON or OFF without C-Bus network communication.
- Incorporates C-Bus Network Status, Mains Power Status and Load Status indicators.
- Capable of generating a C-Bus clock signal if enabled.
- A network burden is incorporated and is software selectable.
- Available in Australian and export version.
- Designed to meet Australian and European standards for EMC Compliance and Safety.
- An inbuilt non-volatile memory retains programmed information relating to the current operating status of the unit in the event of a power failure.
- Communication with other C-Bus devices and the supply voltage is obtained via a single C-Bus twisted pair cable.
- Electrical isolation between the safe extra low voltage C-Bus side and the mains voltage output side is provided to maintain safety requirements.
- Dimensions: H = 240mm, W = 220mm, D = 75mm.
- Weight 2200g.

Head Office

12 Park Terrace, Bowden, South Australia 5007
Telephone (08) 8269 0560
International +61 8 8269 0560
Facsimile (08) 8346 0845
International +61 8 8346 0845
E-Mail cis@clipsal.com.au
Internet clipsal.com/cis

International Enquiries

Head Office Export Department

Telephone +61 8 8269 0587
Facsimile +61 8 8340 7350
E-Mail export@clipsal.com.au
Internet clipsal.com

New Zealand

Clipsal Industries (NZ) Ltd
Telephone +64 9 576 303

Malaysia

Clipsal Integrated Systems (M) Sbn Bhd
Telephone +60 3 7665 3555

Singapore

CIS Pte Ltd (Singapore)
Telephone +65 266 1998

Hong Kong

Clipsal Integrated Systems (HK) Limited
Telephone +852 2 487 0261

China

Clipsal China Limited
Telephone +86 755 246 1122

Taiwan

Clipsal (Taiwan) Co Ltd
Telephone +886 2 25583456

Thailand

Clipsal Thailand Ltd
Telephone +66 2 952 5338

South Africa

Clipsal South Africa (Pty) Ltd
Telephone +27 11 314 5200

United Kingdom

Clipsal Ltd (UK)
Telephone +44 1494 521 111

Greece

Clipsal Hellas S.A.
Telephone +30 1 993 9165



Patented