



# Certificate of Compliance

**Certificate:** 70163439

**Master Contract:** 225619

**Project:** 80101557

**Date Issued:** 2021-10-14

**Issued To:** Telemecanique/Schneider Electric Industries SAS  
BP 660  
Zone Industrielle No. 3  
L'Isle d'Espagnac, Charente, 16340  
France

**Attention:** Jean-Pierre Laidet

*The products listed below are eligible to bear the CSA Mark shown*

**Issued by:** Tracy Zhang  
Tracy Zhang



## PRODUCTS

CLASS - C321103 - INDUSTRIAL CONTROL EQUIPMENT Motor Controllers - Auxiliary Devices

CLASS - C321123 - INDUSTRIAL CONTROL EQUIPMENT Motor Controllers-Auxiliary Devices

Auxiliary devices, 22 mm line, flush-mounted:

Push-button or selector switches, and pilot lights, complete unit assembly, Cat. No. XB4F or XB5F, followed by suffixes, may be followed by C0, C1 or CUST.

Push-button, Rotary and Key Operators, Cat. No. ZB4F or ZB5F, followed by A, D, G, H, J or L, followed by 0, 1, 2, 3, 4, 5, 6, 7, 8 or 9, followed by additional digits, may be followed by C0, C1 or CUST.

Illuminated Push-button and Rotary Operators, Cat. No. ZB4F or ZB5F, followed by H, W or K, followed by one, two, three or four alphanumeric digits, may be followed by C0, C1 or CUST.

Pilot Light Heads, Cat. No. ZB4FV0 or ZB5FV0, followed by two numbers, may be followed by C0, C1 or CUST.



**Certificate:** 70163439  
**Project:** 80101557

**Master Contract:** 225619  
**Date Issued:** 2021-10-14

**Ratings:**

Contact blocks Cat. No. ZBE rated A600, Q600; Cat. No. ZBE-1014 and -1024 rated A300, R300; Cat. No. ZBE-1016 and -1026 rated 24-100mA resistive; Cat. No. ZBE-201 and contact block with quick-connect terminals rated A300, Q300.

Contact subunits Cat. No. ZBE 5. rated A300, P300.

Pilot lights, LED type Cat. No. ZBV rated 12V ac/dc, 24V ac/dc, 110...120V ac, 230/240V ac, 24 ... 120V ac/dc.

Transformers, Cat. No. ZB-.V and ZB-.W rated Primary: 110 - 120V, 50/60Hz; 230V, 50Hz or 220 - 240V, 60Hz; 400V, 50Hz; 440 - 480V, 60Hz; 550 - 600V, 60Hz; Secondary: 6V; Cat. No. ZBV rated Primary: 400V, 50/60Hz; 440 - 460V, 50Hz; 550 - 600V, 60Hz; Secondary: 24V, for use with LED pilot light ZBV-B.

Operators and plugs rated for enclosure Type 1, 2, 3, 4, 4X, 12 or 13, with or without legend holders, legend plates, metal or plastic guards, padlockable flaps, the add-on square trim and boots.

**Accessories:**

Legend holders, Cat. No. ZBY or ZBZ, followed by any alphanumeric digits

Caps, Cat. No. ZB4FSZ3 or ZB5FSZ3

Earthing plate, Cat. No. ZB4FBZ100

Spacer, Cat. No. ZB4FBZ010

Liquid spray protection washer, Cat. No. ZB4FBZ007

Nuts, Cat. No. ZB5FAZ901

Anti-rotation plates, Cat. No. ZB5FAZ, followed by any alphanumeric digits

**Note:** These devices are certified as open type for use in other certified equipment where the suitability of the combination is determined by CSA.

**APPLICABLE REQUIREMENTS**

- |   |   |
|---|---|
| CSA-C22.2 No. 14-18 (13 <sup>th</sup> Ed.)                  | - Industrial Control Equipment  |
| CAN/CSA C22.2 No. 60947-1-13 (2 <sup>nd</sup> Ed.)          | - Low-voltage switchgear and controlgear - Part 1: General rules  |
| CAN/CSA C22.2 No. 60947-5-1-14 (1 <sup>st</sup> Ed., R2019) | - Low-voltage switchgear and controlgear - Part 5-1: Control circuit devices and switching elements – Electromechanical control circuit devices |