

Product End-of-Life Instructions

Product Range: Motor Logic Solid State Overload Relay

Marketing Model/Name: The End of Life Instruction (EoLI) covers the entire range:

- *Current rating from 1.5 FLA to 45 FLA*
- *Single or Three Phase*
- *Separate Mount or for Replacement on Type S Starter*

Purpose:

The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.



Size in inches (mm):

2.69in x 3.26in x 3.9in (69mm x 83mm x 99mm)

Weight in lbs (kg):

Between 1.09 lbs (493g) and 1.30 lbs (590g) without battery


Operations recommended for the end of life treatment

There are several steps to process the products at the end of life so as to recover components, materials or energy :
Reuse → Separation for special treatment → Other dismantling → Shredding.

| ⚠ DANGER |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HAZARD OF ELECTRIC SHOCK, EXPLOSION OR ARC FLASH |
| <ul style="list-style-type: none"> • Apply appropriate personal protective equipment (PPE) and follow safe electrical work practices. See NFPA 70E. • This equipment must be removed from service only by qualified electrical personnel. • Turn off all power supplying this equipment before working on or inside equipment. • Always use a properly rated voltage sensing device to confirm power is off. • Replace all devices, doors and covers before turning on power to this equipment. |
| Failure to follow these instructions will result in death or serious injury. |

| ⚠ CAUTION |
|---------------------------------------------------------------------------------------------------------------------------------------------|
| HAZARD OF PERSONAL INJURY |
| The circuit breaker must be tripped to dissipate stored mechanical energy before recycling, crushing or disassembly of the circuit breaker. |
| Failure to follow these instructions can result in personal injury. |

The components of the products that optimize the recycling performances are listed, identified and located hereunder.



| Recommendation | Number on drawing | Components | Weight (g) | Comment |
|-------------------|-------------------|-----------------------|------------|---------|
| Special treatment | | | | |
| | 1 | Printed Circuit Board | 24.43 g | |

Schneider Electric Industries SAS
35, rue Joseph Monier
CS 30323
F- 92506 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 896 313 776 €
www.schneider-electric.com

© 2013 Schneider Electric All Rights Reserved

Schneider Electric and Square D are trademarks owned by Schneider Electric Industries SAS or its affiliated companies. All other trademarks are the property of their respective owners.

The version of the Guide used to create the document: End of Life Instruction Drafting Guide of Schneider Electric version 4.

ENVEOLI1312002EN

Publication date : 12/15/2013