Product Environmental Profile

Renova - double USB charger







🔲 Gen

General information

Representative product

Renova - double USB charger - WDE011760

Description of the product

The function of the socket is to allow users to connect and disconnect the plug of an electrical load or the source of a signal from a network: Electronic: Loudspeaker socket, USB socket.


Functional unit

Make available during 20 years ,2 USB 2.0 port 5 V DC, maximum load current: 2.1 A

Constituent materials

Reference product mass

150 g including the product, its packaging and additional elements and accessories



 Plastics
 16.9%

 Metals
 10.7%

 Others
 72.4%

Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page


(19) Additional environmental information

The Renova - double USB charger presents the following relevent environmental aspects						
Design	Indicate all the eco-design improvements brought to the product at the design phase compared to previous offer range, refer to ecoDesign Way results					
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified					
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive					
	Packaging weight is 83 g, consisting of cardboard (35%),Paper (65%)					
Installation	The product does not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).					
Use	The product does not require special maintenance operations.					
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic card (22.85g) that should be separated from the stream of waste so as to optimize end- of-life treatment. http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page					
	Based on "ECO'DEEE recyclability and recoverability calculation method" Recyclability potential: 16% (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).					

Environmental impacts

Reference life time	20 years						
Product category	USB socket						
Installation elements	The product does not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).						
Use scenario	Load rate: 100 % of the rated current according to the USB standards Load rate: 30% de the RLT						
Geographical representativeness	Europe						
Technological representativeness	The function of the socket is to allow users to connect and disconnect the plug of an electrical load or the source of a signal from a network: Electronic: Loudspeaker socket, USB socket.						
	Manufacturing	Installation	Use	End of life			
Energy model used	Energy model used: Ringsted, Denmark	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27			

Compulsory indicators	Renova - double USB charger - WDE011760						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	7.11E-05	6.29E-05	0*	0*	8.14E-06	0*
Contribution to the soil and water acidification	kg SO ₂ eq	3.95E-01	4.10E-03	8.84E-05	0*	3.91E-01	0*
Contribution to water eutrophication	kg PO ₄ 3- eq	2.60E-02	2.11E-03	2.04E-05	2.25E-04	2.36E-02	5.92E-06
Contribution to global warming	kg CO ₂ eq	9.69E+01	2.97E+00	1.94E-02	1.18E-01	9.37E+01	1.05E-02
Contribution to ozone layer depletion	kg CFC11 eq	6.49E-06	3.79E-07	0*	0*	6.11E-06	0*
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2.20E-02	5.00E-04	6.31E-06	2.86E-05	2.15E-02	2.28E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	3.40E+02	0*	0*	0*	3.40E+02	0*
Total Primary Energy	MJ	1.91E+03	3.72E+01	2.74E-01	0*	1.87E+03	0*



Optional indicators	Renova - double USB charger - WDE011760						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1.10E+03	3.43E+01	2.72E-01	0*	1.06E+03	0*
Contribution to air pollution	m³	4.31E+03	2.69E+02	8.23E-01	5.48E-01	4.03E+03	7.71E-01
Contribution to water pollution	m³	4.20E+03	3.22E+02	3.18E+00	6.76E+00	3.87E+03	9.04E-01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	7.97E-03	7.97E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	2.40E+02	2.22E+00	0*	0*	2.38E+02	0*
Total use of non-renewable primary energy resources	MJ	1.67E+03	3.50E+01	2.73E-01	0*	1.63E+03	0*
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	2.39E+02	7.62E-01	0*	0*	2.38E+02	0*
Use of renewable primary energy resources used as raw material	MJ	1.46E+00	1.46E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.67E+03	3.37E+01	2.73E-01	0*	1.63E+03	0*
Use of non renewable primary energy resources used as raw material	MJ	1.31E+00	1.31E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	2.27E+00	2.09E+00	0*	0*	4.89E-02	1.33E-01
Non hazardous waste disposed	kg	3.51E+02	1.60E+00	0*	8.32E-02	3.49E+02	0*
Radioactive waste disposed	kg	2.34E-01	7.20E-04	0*	0*	2.33E-01	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	2.55E-02	1.37E-02	0*	0*	0*	1.17E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1.20E-03	0*	0*	0*	0*	1.20E-03
Exported Energy	MJ	2.72E-04	3.46E-05	0*	2.38E-04	0*	0*

^{*} represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.7.0.2, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Validity period

5 years

Registration number: SCHN-00335-V01.01-EN Drafting rules PCR-ed3-EN-2015 04 02

Verifier accreditation N° VH25 Supplemented by PSR-0005-ed2-EN-2016 03 29
Information and reference

Date of issue 05/2018 documents www.pep-ecopassport.org

Independent verification of the declaration and data, in compliance with ISO 14025: 2010

Internal External X

The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)

PEP are compliant with XP C08-100-1:2014

The elements of the present PEP cannot be compared with elements from another program.

Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental

declarations »



Country Customer Care Center http://www.schneider-electric.com/contact

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com Published by Schneider Electric

SCHN-00335-V01.01-EN © 2017 - Schneider Electric – All rights reserved

05/2018

PASS