


# Product Environmental Profile

## BIOSOURCED ECO SINGLE MODULE RENOVATION BOX






## General information




<b>Representative product</b>	BIOSOURCED ECO SINGLE MODULE RENOVATION BOX - IMT36132
<b>Description of the product</b>	The main function of the BIOSOURCED ECO BOX is to protect persons against direct contact with live parts and allow grouping monitoring, control and protection devices in a single enclosure.
<b>Functional unit</b>	Protect persons during 20 years against direct contact with live parts and allow grouping monitoring, control and protection devices in a single enclosure having the following dimensions 61 x 72 x 72, while protecting against the penetration of solid objects and liquids (IP30) in accordance with the standard IEC 60529.



## Constituent materials

<b>Reference product mass</b>	82 g	including the product, its packaging.
-------------------------------	------	---------------------------------------



	Plastics	44.2%
	Metals	12.4%
	Others	43.4%



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as mentioned in the Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

## Additional environmental information


The BIOSOURCED ECO SINGLE MODULE RENOVATION BOX presents the following relevant environmental aspects

<b>Manufacturing</b>	Manufactured at a production site complying with the regulations
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 36.9 g, consisting of wood (70.50%), cardboard (28.15%), paper (1.35%) Product distribution optimised by setting up local distribution centres
<b>Installation</b>	The product does not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials is accounted during the installation phase (including transport to disposal).
<b>Use</b>	The product does not require special maintenance operations.
<b>End of life</b>	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials  No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.  Recyclability potential: <b>88%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

## Environmental impacts

<b>Reference life time</b>	20 years			
<b>Product category</b>	Unequipped enclosures and cabinets			
<b>Installation elements</b>	No special components needed			
<b>Use scenario</b>	Non applicable for unequipped enclosures and cabinets			
<b>Geographical representativeness</b>	Sweden			
<b>Technological representativeness</b>	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production.			
<b>Energy model used</b>	<b>Manufacturing</b>	<b>Installation</b>	<b>Use</b>	<b>End of life</b>
	Manufacturing plant: Minera AS, Norway	0	0	0

Compulsory indicators		BIOSOURCED ECO SINGLE MODULE RENOVATION BOX - IMT36132					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	1.47E-05	1.47E-05	0*	0*	0*	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	5.74E-04	4.95E-04	4.83E-05	1.67E-05	0*	1.40E-05
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	5.76E-04	5.53E-04	1.11E-05	7.51E-06	0*	3.57E-06
Contribution to global warming	kg CO <sub>2</sub> eq	2.77E-01	2.33E-01	1.06E-02	2.83E-02	0*	5.83E-03
Contribution to ozone layer depletion	kg CFC11 eq	1.01E-06	1.01E-06	0*	0*	0*	2.92E-10
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	9.90E-05	8.75E-05	3.45E-06	6.56E-06	0*	1.50E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m <sup>3</sup>	2.14E-02	2.14E-02	0*	7.46E-06	0*	5.93E-06
Total Primary Energy	MJ	2.85E+00	2.59E+00	1.50E-01	3.73E-02	0*	6.98E-02



Optional indicators		BIOSOURCED ECO SINGLE MODULE RENOVATION BOX - IMT36132						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Contribution to fossil resources depletion	MJ	1.49E+00	1.25E+00	1.49E-01	3.46E-02	0*	5.60E-02	
Contribution to air pollution	m³	3.56E+01	3.40E+01	4.50E-01	6.75E-01	0*	4.97E-01	
Contribution to water pollution	m³	2.56E+01	2.29E+01	1.74E+00	3.83E-01	0*	5.61E-01	
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Use of secondary material	kg	9.78E-03	9.78E-03	0*	0*	0*	0*	
Total use of renewable primary energy resources	MJ	6.18E-01	6.17E-01	1.99E-04	6.31E-04	0*	7.82E-05	
Total use of non-renewable primary energy resources	MJ	2.23E+00	1.98E+00	1.49E-01	3.66E-02	0*	6.97E-02	
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	3.22E-02	3.13E-02	1.99E-04	6.31E-04	0*	7.82E-05	
Use of renewable primary energy resources used as raw material	MJ	5.86E-01	5.86E-01	0*	0*	0*	0*	
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.14E+00	1.88E+00	1.49E-01	3.66E-02	0*	6.97E-02	
Use of non renewable primary energy resources used as raw material	MJ	9.70E-02	9.70E-02	0*	0*	0*	0*	
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Hazardous waste disposed	kg	1.18E+00	1.12E+00	0*	0*	0*	5.42E-02	
Non hazardous waste disposed	kg	2.16E-01	1.95E-01	3.76E-04	2.09E-02	0*	2.15E-04	
Radioactive waste disposed	kg	5.79E-05	5.66E-05	2.68E-07	7.37E-07	0*	3.31E-07	
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	
Materials for recycling	kg	6.70E-02	6.63E-03	0*	1.83E-02	0*	4.21E-02	
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	
Materials for energy recovery	kg	4.46E-04	0*	0*	0*	0*	4.46E-04	
Exported Energy	MJ	1.79E-02	1.68E-03	0*	1.62E-02	0*	0*	

\* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

“Renobox is using I’m Green™ Polyethylene made from sugarcane ethanol. Being a renewable feedstock, sugarcane captures and fixes CO2 from the atmosphere every growth cycle, which occurs annually. This CO2 is reported as biogenic carbon dioxide emissions in the Life Cycle Inventory used for this current PEP and is reaching 3.11kg of biogenic CO2 stored by kg of I’m Green™ Polyethylene, so 76.2 grams for one Renobox. However, this biogenic CO2 cannot be stored indefinitely in the product cycle and is therefore released during its end of life. As such biogenic carbon is not taken into account in the indicators presented in this PEP.”

*Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.*

<i>Registration number :</i>	SCHN-00612-V01.01-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Verifier accreditation N°</i>	VH-39	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Date of issue</i>	09/2020	<i>Information and reference documents</i>	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
		<i>Validity period</i>	5 years
<i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2010</i>			
Internal	External <input checked="" type="checkbox"/>		
<i>The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)</i>			
<i>PEP are compliant with XP C08-100-1 :2016</i>			
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »</i>			



Schneider Electric Industries SAS  
Country Customer Care Center  
<http://www.schneider-electric.com/contact>  
35, rue Joseph Monier  
CS 30323  
F- 92506 Rueil Malmaison Cedex  
RCS Nanterre 954 503 439  
Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

SCHN-00612-V01.01-EN

© 2019 - Schneider Electric – All rights reserved

09/2020