

Product Environmental Profile

ATV680 LH DRIVE SYSTEMS IP23 315 / 250 kW




General information

Reference product	ATV680 LH DRIVE SYSTEMS IP23 315 / 250 kW - ATV680C31Q4X1
Description of the product	The main function of the Altivar Process product range is the speed control and variation of a synchronous, asynchronous or reluctance electric motor for fluid management and industrial applications.
Functional unit	To adapt the speed and torque of synchronous, asynchronous or reluctance motor to the machine's operating point. Calculation of the environmental impacts is based on 10 years of product service lifetime. The usage profile taken into account is 73% uptime in use phase at 80% loading rate and 27% uptime in stand by phase.

Constituent materials

Reference product mass 755 kg including the product, its packaging and additional elements and accessories



Plastics	2,00%
Metals	80,30%
Others	17,70%

Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website <https://www.se.com/ww/en/work/support/green-premium/>

Additional environmental information

End Of Life	Recyclability potential:	79%	Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).
-------------	--------------------------	-----	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Environmental impacts

Reference service life time	10 years			
Product category	Other equipments - Active product			
Installation elements	No special components needed			
Use scenario	The product is in active phase 73% of the time at 80% loading rate with a power use of 11090W and in stand-by phase 27% of the time with a power use of 76W, for 10 years.			
Technological representativeness	The main function of the Altivar Process product range is the speed control and variation of a synchronous, asynchronous or reluctance electric motor for fluid management and industrial applications.			
Geographical representativeness	Europe			
Energy model used	[A1 - A3]	[A5]	[B6]	[C1 - C4]
	Electricity Mix; Production mix; Low voltage; CN	Electricity Mix; Production mix; Low voltage; UE-27	Electricity Mix; Production mix; Low voltage; UE-27	Electricity Mix; Production mix; Low voltage; UE-27

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

Mandatory Indicators			ATV680 LH DRIVE SYSTEMS IP23 315 / 250 kW - ATV680C31Q4X1					
Impact indicators	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Loads and Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	4,97E+05	3,57E+04	1,69E+02	7,12E+01	4,59E+05	1,52E+03	7,09E-01
Contribution to climate change-fossil	kg CO2 eq	4,97E+05	3,56E+04	1,69E+02	8,98E+01	4,59E+05	1,51E+03	7,09E-01
Contribution to climate change-biogenic	kg CO2 eq	3,45E+02	5,20E+01	0*	0*	3,03E+02	8,82E+00	-6,64E-06
Contribution to climate change-land use and land use change	kg CO2 eq	1,12E-04	1,12E-05	0*	0*	0*	1,01E-04	0,00E+00
Contribution to ozone depletion	kg CFC-11 eq	3,49E-03	1,17E-03	8,88E-05	2,81E-06	2,21E-03	1,34E-05	0,00E+00
Contribution to acidification	mol H+ eq	3,27E+03	3,45E+02	8,75E-01	0*	2,92E+03	7,05E+00	2,84E-03
Contribution to eutrophication, freshwater	kg (PO4) ³⁻ eq	7,16E-01	9,95E-02	0*	5,05E-04	4,00E-01	2,16E-01	2,05E-07
Contribution to eutrophication marine	kg N eq	4,61E+02	1,33E+02	4,06E-01	5,52E-02	3,26E+02	2,02E+00	4,38E-04
Contribution to eutrophication, terrestrial	mol N eq	5,36E+03	1,46E+03	4,43E+00	0*	3,89E+03	1,16E+01	4,78E-03
Contribution to photochemical ozone formation - human health	kg COVNM eq	1,45E+03	3,66E+02	1,28E+00	0*	1,08E+03	4,04E+00	1,37E-03
Contribution to resource use, minerals and metals	kg Sb eq	1,66E+00	1,64E+00	0*	0*	1,31E-02	6,09E-03	4,89E-08
Contribution to resource use, fossils	MJ	9,27E+06	6,11E+05	2,18E+03	0*	8,55E+06	1,04E+05	1,64E+01
Contribution to water use	m3 eq	4,08E+04	3,95E+03	5,36E+00	1,82E+01	1,79E+04	1,89E+04	6,46E-02

Additional indicators for the French regulation are available as well

Inventory flows Indicators		ATV680 LH DRIVE SYSTEMS IP23 315 / 250 kW - ATV680C31Q4X1						
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Loads and Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1,04E+06	3,36E+03	0*	1,94E+02	1,04E+06	2,25E+02	9,72E-05
Contribution to use of renewable primary energy resources used as raw material	MJ	1,22E+03	1,22E+03	0*	0*	0*	0*	0,00E+00
Contribution to total use of renewable primary energy resources	MJ	1,04E+06	4,59E+03	0*	1,94E+02	1,04E+06	2,25E+02	9,72E-05
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	9,26E+06	6,09E+05	2,18E+03	0*	8,55E+06	1,04E+05	9,31E+00
Contribution to use of non renewable primary energy resources used as raw material	MJ	1,49E+03	1,49E+03	0*	0*	0*	0*	7,09E+00
Contribution to total use of non-renewable primary energy resources	MJ	9,27E+06	6,11E+05	2,18E+03	0*	8,55E+06	1,04E+05	1,64E+01
Contribution to use of secondary material	kg	1,95E+01	1,95E+01	0*	0*	0*	0*	0,00E+00
Contribution to use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to net use of freshwater	m³	1,00E+03	9,21E+01	1,25E-01	4,24E-01	4,18E+02	4,93E+02	1,50E-03
Contribution to hazardous waste disposed	kg	3,92E+04	2,74E+04	0*	0*	1,10E+04	8,18E+02	6,51E-03
Contribution to non hazardous waste disposed	kg	7,72E+04	4,58E+03	0*	1,60E+02	7,24E+04	1,52E+01	2,82E-03
Contribution to radioactive waste disposed	kg	1,11E+01	2,50E+00	2,17E-02	1,86E-02	8,56E+00	5,80E-03	0,00E+00
Contribution to components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to materials for recycling	kg	5,85E+02	1,55E-01	0*	3,31E+01	0*	5,52E+02	0,00E+00
Contribution to materials for energy recovery	kg	1,60E-07	1,60E-07	0*	0*	0*	0*	0,00E+00
Contribution to exported energy	MJ	2,54E+01	2,39E+00	0*	2,30E+01	0*	0*	0,00E+00
Contribution to biogenic carbon content of the product	kg de C	0,00E+00	0*	0*	0*	0*	0*	0,00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0,00E+00	0*	0*	0*	0*	0*	0,00E+00

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - <http://www.schneider-electric.com/contact>

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	ENVPEP2402004_V1	Drafting rules	PEP-PCR-ed4-2021 09 06
Date of issue	2024/02/26	Information and reference documents	www.pep-ecopassport.org
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14021 : 2016			
Internal	X	External	
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)			
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021 : 2016 « Environmental labels and declarations. Type II environmental declarations »			

Schneider Electric Industries SAS

*Country Customer Care Center
<http://www.schneider-electric.com/contact>*

*35, rue Joseph Monier
CS 30323
F- 92500 Rueil Malmaison Cedex
RCS Nanterre 954 503 439
Capital social 928 298 512 €*

www.se.com

SCHN-00001-V01.01-EN

Published by Schneider Electric

©2024 - Schneider Electric – All rights reserved

2024/02/26

