
# Product data sheet Characteristics

## DF14AM1

Auxiliary contact block, TeSys DF, 1NC, 5A, disconnector, signalling contact, instantaneous

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 13.50 USD



#### Main

Range	TeSys	
Device short name	DF14	
Product or Component Type	Auxiliary contact block	
Auxiliary contacts operation	Instantaneous	
Pole contact composition	1 NC	
Connections - terminals	Faston connector	

#### Complementary

Range compatibility	TeSys TeSys DF	
[Ui] rated insulation voltage	250 VAC	
[Ue] rated operational voltage	24240 V AC AC-15 24240 V DC DC-13	
[Ith] conventional free air thermal current	5 A	
Minimum switching current	30 MA	
Minimum switching voltage	10 V	
Net Weight	0.06 Lb(US) (0.025 kg)	

#### Environment

Ambient air temperature for operation	-4140 °F (-2060 °C)
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)

## Ordering and shipping details

Category	US10CP121714	:
Discount Schedule	0CP1	
GTIN	3389119407540	-
Returnability	No	:
Country of origin	TN	

### **Packing Units**

r doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 ln (2.0 cm)
Package 1 Width	1.18 ln (3.0 cm)
Package 1 Length	3.15 ln (8.0 cm)
Package 1 Weight	0.60 Oz (17.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	120
Package 2 Height	11.81 ln (30.0 cm)
Package 2 Width	11.81 ln (30.0 cm)
Package 2 Length	15.75 ln (40.0 cm)
Package 2 Weight	5.34 Lb(US) (2.423 kg)

## Offer Sustainability

California proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	

## Contractual warranty

Warranty	18 months

Product Life Status : Commercialised