





600VAC

Note:

- Drawings Not To Scale

Drawings Subject to Change Without Notice
Dimensions are inches next to [Millimeters]

Part No.:

## PKL36100CU63AE1

by Schneider Electric

Schneider Electric United States North American Division Boston One Campus 800 Federal Street Andover, MA 01810, USA Phone:+1 8773425173 Email: CCC@us.schneider-electric.com

## **Technical Information:**

General Application: Provides overload and short circuit protection Panelboards and Switchboards
UL Listed - CSA Certified - IEC Rated For Use With:

**Unit Mount** 

Approvals:
Mounting Type:
Terminal Type: Lugs (ON and OFF ends) #3/0-500 AWG/kcmil(Al/Cu) Wire Size:

Weight: Depth: Height:

Width:

8.07 Inches 16.26 Inches 8.27 Inches

Description:

Number of Poles: Sensor Rating: Voltage Rating: Interrupting Rating: Circuit Breaker Rating:

Electronic Trip Unit:

Trip Function: Installed Rating Plug:

65kA at 240VAC - 50kA at 480/600VAC 100% Rated Micrologic Power Trip Unit (5.0P)

LSI Type A Rating Plug Range: 0.4A to 1A

PowerPact P-frame Electronic Trip Circuit Breaker 3-Pole 1000A

Specification: