



Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable run-time. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 2 Weeks

General

Provided equipment	Installation guide USB cable
Additional specification	Cloud-enabled monitoring
Number of tare power	30 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Cable length	1.83 M
Colour	Black
Depth	43.9 Cm
Height	21.9 Cm
Mounting location	Front
Mounting preference	No preference
Product weight	24.09 Kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Width	17.1 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C14
Input voltage limits	151...302 V adjustable 160...286 V
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	1000 W
Maximum configurable power in W	1000 W
Harmonic distortion	Less than 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Output voltage	220 V 240 V
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	1500 VA
Rated power in VA	1500 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Product certifications	CE EAC RCM VDE
Standards	EN/IEC 62040-1 EN/IEC 62040-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 M
Acoustic level	45 dBA
Heat dissipation	135 Btu/H

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 H
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery charger power	136 W rated
Battery power in VAH	408 VAh runtime
Battery life	3...5 Year(S)
Extended runtime	0

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	27.23 Kg
Package 1 Height	37.6 Cm
Package 1 width	32.8 Cm
Package 1 Length	59.5 Cm
Number of Units in Package 3	12

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Product Life Status : **Commercialised**