

# Product data sheet

## Characteristics

# VLS3P040R1

Disconnect switch, TeSys VLS, body switch, 40A, 20HP at 480VAC, UL508, three phase, 5kA SCCR, size 1, DIN rail mount

Product availability: Stock - Normally stocked in distribution facility

Price\*: 45.31 USD



### Main

Range	TeSys
Product name	TeSys VARIO LS
Device short name	VLS3P
Product or Component Type	Switch body

### Complementary

Device Composition	Handle Switch
Mounting support	Back DIN rail
Fixing mode	By clips back
Performance level	High performance
Poles description	3P
Contacts type and composition	3 NO
Color	Gray
[Ue] rated operational voltage	600 V AC 50/60 Hz UL 508
[Ue] rated operational voltage	690 V AC 50/60 Hz
Maximum Horse Power Rating	10 Hp 200/208 V AC 15 Hp 240 V AC 20 Hp 480 V AC 25 Hp 600 V AC 2 Hp 120 V AC 5 Hp 240 V AC
Rated operational power in W	18.5 KW 400 V AC-23A) 18.5 KW 500 V AC-23A) 22 KW 690 V AC-23A)
[Ie] rated operational current	40 A Ue: 600 V UL 508 40 A AC-21A Ue: 400 V 40 A AC-21A Ue: 500 V 40 A AC-21A Ue: 690 V 40 A AC-22A Ue: 400 V 40 A AC-22A Ue: 500 V 40 A AC-22A Ue: 690 V 40 A AC-23A Ue: 400 V 25 A AC-23A Ue: 500 V 25 A AC-23A Ue: 690 V

[Ith] conventional free air thermal current	40 A (at 131.0000000000 °F (55 °C))
[Ithe] conventional enclosed thermal current	40 A
Making capacity	60 A 690 V AC-21A 120 A 690 V AC-22A 400 A 690 V AC-23A
Breaking capacity	60 A 690 V AC-21A) 120 A 690 V AC-22A) 320 A 690 V AC-23A)
Product compatibility	Fuse RK5 45 A maximum: 5 kA at 600 V AC
Rated conditional short-circuit current	50 KA 400 V 40 A gG
[Icm] rated short-circuit making capacity	1128 A 690 V
[Icw] rated short-time withstand current	800 A 690 V 1 s
[Uimp] rated impulse withstand voltage	8 KV
Suitability for isolation	Yes
Network type	AC
Network Frequency	50/60 Hz
Intermittent duty class	Class 120 - 60 %
Control Type	Rotary handle
Rotary handle mounting style	Direct
Handle colour	Black
Handle front plate colour	Grey
Rotary handle padlocking	1 padlock 0.2 in (4 mm)
Marking	0 - 1
Mechanical durability	100000 Cycles
Electrical durability	100000 Cycles AC-21A
AWG gauge	AWG 18...AWG 6 copper
Connections - terminals	Power circuit screw clamp terminals 0.02 in <sup>2</sup> (10 mm <sup>2</sup> ) solid Power circuit screw clamp terminals 0.02 in <sup>2</sup> (16 mm <sup>2</sup> ) flexible - without cable end
Tightening torque	Power circuit 15.9...17.7 lbf.in (1.8...2 N.m) screw clamp terminals
Height	3.0 In (75 mm)
Width	1.4 In (36 mm)
Depth	3.07 In (78 mm)
Net Weight	0.298 Lb(US) (0.135 kg)

## Environment

Standards	UL 508 CSA C22.2 No 14 IEC 60947-3
Product Certifications	cULus[RETURN]GL
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 2...100 Hz Fc 0.7 g) IEC 60068-2-6 Shocks 11 ms Ea 15 gn) IEC 60068-2-27
Ambient Air Temperature for Operation	-13.0000000000...131.0000000000 °F (-25...55 °C)
Fire resistance	1760.0000000000 °F (960 °C) IEC 60695-2-11
Compatibility code	VLS

## Ordering and shipping details

Category	US10CP121734
Discount Schedule	0CP1
GTIN	3606481156464
Returnability	Yes
Country of origin	IT

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.150 In (8.000 cm)
Package 1 Width	3.346 In (8.500 cm)
Package 1 Length	4.724 In (12.000 cm)
Package 1 Weight	5.926 Oz (168.000 g)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

Product Life Status : **Commercialised**