



**NOTES:**

1. INSTALLATION MUST COMPLY WITH ALL APPLICABLE NATIONAL AND LOCAL CODES.
2. PLEASE REFER TO APC PRODUCT MANUAL FOR DETAILS.
- △3. AC SOURCE MUST BE 220-240VAC (1PH+G) 50/60Hz.
- △4. DASHED LINES BETWEEN UNITS ( - - - ) REPRESENT CABLING PROVIDED BY OTHERS.

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF SCHNEIDER ELECTRIC AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM SCHNEIDER ELECTRIC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.



TITLE: SMART-UPS RT (SURT)  
 3000VA MARINE RACK-MOUNT  
 INPUT: 230V; IEC 320 C20  
 OUTPUT: (8) IEC 320 C13; (2) IEC 320 C19  
 SINGLE-LINE DIAGRAM

PROJECT: STD SUBMITTAL DRAWINGS SHEET 1 OF 1

DWG NO: SURTD3000XLIM-SD REV. 0

DRAWN BY: S CUNHA 22-JUN-11 PROJ

ENGINEER: B McKENNA 22-JUN-11 ANGLE

APPROVED BY: B McKENNA 22-JUN-11 N/A