



CH "DIN".



CH "48 x 48".

Function

Electromechanical counter that counts the operating hours of a machine or piece of electrical equipment. Giving a precise indication of operating time, the counter is used to decide when to carry out preventive maintenance.

Common technical data

- Electromechanical display.
- Maximum display: 99999.99 hours.
- Display accuracy: 0.01 %.
- Without reset.
- Storage temperature: -25 °C to +85 °C.
- Connection: tunnel terminals for 2.5 mm² cable.

Specific technical data

CH "DIN"

- Consumption: 0.15 VA.
- Operating temperature: -10 °C to +70 °C.
- Mounting on DIN rail.


CH "48 x 48"

- Consumption:
 - 15607: 0.25 VA
 - 15608: 0.15 VA
 - 15609: 0.02 VA to 12 V and 0.3 VA to 36 V.
- Operating temperature: -20 °C to + 70 °C.
- Degree of protection: IP65 on front face.
- Mounting on front face of monitoring switchboards.


Catalogue numbers

Type	Voltage (V)	Width in mod. of 9 mm	Cat. no.
CH "DIN"	230 V AC ± 10%/50 Hz	4	15440
CH "48 x 48"	24 V AC ± 10%/50 Hz		15607
	230 V AC ± 10%/50 Hz		15608
	12 to 36 V DC		15609

Connection



CH "DIN".



CH "48 x 48".