



# ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: **4900-045-07**

Valid from: 2021 02 13  
until: 2023 02 13

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: **Schneider Electric Industries SAS**  
35, rue Joseph Monier  
92500 Rueil-Malmaison  
France

Product: **Switches for household and similar fixed installations**

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s): **TGM-VA EE 38663**

**Österreichischer Verband für Elektrotechnik**  
Head of Testing and Certification

Digitally signed by W. Martin  
Email=w.martin@ove.at

Dipl.-Ing. W. Martin

Wien, 2021 01 19



## OVE Testing and Certification

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under [www.bmdw.gv.at/akkreditierung](http://www.bmdw.gv.at/akkreditierung).



**Manufacturer:**

Schneider Electric Industries SAS  
35, rue Joseph Monier  
92500 Rueil-Malmaison  
France

**Factory location(s):**

Merten GmbH  
Fritz Kotz Straße 8  
51674 Wiehl-Bornig  
Germany

**Tested and certified according to:**

OVE EN 60669-1:2019-04-01

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

**Product: Switches for household and similar fixed installations**

**Type designation:**

*Rating:*

**Trademark:**

**Serie 314,  
System M, System Design,  
Anti vandalism, Aquadesign (IP44)**  
Rated voltage: AC 250 V  
Rated current: 6 A, 10 A, 10 AX  
IP20, IP21 or IP44  
screwless terminals

MERTEN/SCHNEIDER ELECTRIC

**314 (1)**  
Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 1  
one-way, 1-pole

MERTEN/SCHNEIDER ELECTRIC

**314 (1)**  
Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 1  
one-way, 1-pole  
illuminated (with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**OVE Testing and Certification**

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under [www.bmdw.gv.at/akkreditierung](http://www.bmdw.gv.at/akkreditierung).

**314 (1)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 1  
one-way, 1-pole  
with separate signalling contact

MERTEN/SCHNEIDER ELECTRIC

**314 (1K)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 1  
one-way, 1-pole  
control-switch (with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**314 (2)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 2  
one-way, 2-pole

MERTEN/SCHNEIDER ELECTRIC

**314 (2K)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 2  
one-way, 2-pole  
control-switch (with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**314 (4)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 4  
1-pole  
shutter-switch

MERTEN/SCHNEIDER ELECTRIC

**314 (4)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 4  
1-pole, with separate contact  
shutter-switch

MERTEN/SCHNEIDER ELECTRIC

**314 (5)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 5  
two-circuit

MERTEN/SCHNEIDER ELECTRIC

**314 (5)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 5  
two-circuit  
illuminated (with LED lighting module 3942 / 3902 / 3922)

MERTEN/SCHNEIDER ELECTRIC

**OVE Testing and Certification**

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under [www.bmdw.gv.at/akkreditierung](http://www.bmdw.gv.at/akkreditierung).

**314 (5)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 5

two-circuit, with N-Terminal

MERTEN/SCHNEIDER ELECTRIC

**314 (5K)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 5

two-circuit control switch, with N-Terminal

(with LED lighting module 3942 / 3902 / 3922)

MERTEN/SCHNEIDER ELECTRIC

**314 (6)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 6

two-way

MERTEN/SCHNEIDER ELECTRIC

**314 (6)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 6

two-way, illuminated (with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**314 (6K)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 6

two-way control switch

(with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**314 (6+6)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 6+6

two-way

MERTEN/SCHNEIDER ELECTRIC

**314 (6 + 6T)**

Rated voltage: AC 250 V

Rated current: 10 AX + 10 A

PatternNo. 6 + 6T

two-way + two-way push-button

MERTEN/SCHNEIDER ELECTRIC

**314 (1 + 6)**

Rated voltage: AC 250 V

Rated current: 10 AX

PatternNo. 1 + 6T

one-way + two-way fan switch

MERTEN/SCHNEIDER ELECTRIC

**OVE Testing and Certification**

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under [www.bmdw.gv.at/akkreditierung](http://www.bmdw.gv.at/akkreditierung).

**314 (7)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 7  
intermediate switch

MERTEN/SCHNEIDER ELECTRIC

**314 (7)**

Rated voltage: AC 250 V  
Rated current: 10 AX  
PatternNo. 7  
intermediate switch, illuminated (with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T  
1-pole, push-button (make contact)

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T  
1-pole, push-button (make contact)  
illuminated(with LED lighting module 3901 / 3921)

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T  
1-pole, push-button (make contact)  
with separate signalling contact

MERTEN/SCHNEIDER ELECTRIC

**314 (1TÖ)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T  
1-pole, push-button (break contact)

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS+1TS)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T+1T  
2x1-pole, push-button (make contact)

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS+1TS)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T+1T  
2x1-pole, push-button (make contact)  
illuminated (with LED lighting module 3942 / 3902 / 3922)

MERTEN/SCHNEIDER ELECTRIC

**OVE Testing and Certification**

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under [www.bmdw.gv.at/akkreditierung](http://www.bmdw.gv.at/akkreditierung).

**314 (1TS+1TS)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 1T+1T  
2x1-pole, push-button (make and break contact)

MERTEN/SCHNEIDER ELECTRIC

**314 (4T)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 4T  
1-pole, push-button

MERTEN/SCHNEIDER ELECTRIC

**314 (6T)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 6T  
two-way, 1-pole,  
push-button with N-terminal

MERTEN/SCHNEIDER ELECTRIC

**314 (6T+6T)**

Rated voltage: AC 250 V  
Rated current: 10 A  
PatternNo. 6T+6T  
two-way, push-button

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS)**

Rated voltage: AC 250 V  
Rated current: 6 A  
PatternNo. 1T  
Hotel-card switch, 1-pole, push-button (make contact)  
with separate signalling contact

MERTEN/SCHNEIDER ELECTRIC

**314 (1TS)**

Rated voltage: AC 250 V  
Rated current: 6 A  
PatternNo. 1T  
Hotel-card switch, 1-pole, push-button (make contact)  
with separate signalling contact  
illuminated (with LED lighting module 3901/ 3921)

MERTEN/SCHNEIDER ELECTRIC

**3901 /3921**

Lighting module for switch/push button

MERTEN/SCHNEIDER ELECTRIC

**3942 / 3902 / 3922**

Lighting module for double switch/push button

MERTEN/SCHNEIDER ELECTRIC

**Rockers and frames of System M (Thermo+Duro), System Design (Thermo+Duro), System Design (Thermo+metal+glass/stone), Anti vandalism and Aquadesign (IP44), System M-Exxact (Thermo).**

---

**OVE Testing and Certification**

Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under [www.bmdw.gv.at/akkreditierung](http://www.bmdw.gv.at/akkreditierung).