

Certificate of Suitability

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and notifies the certificate holder to affix the Certificate number and Regulatory Compliance Mark (RCM) mark on the product of the same type provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the Certificate number and/or RCM mark on the product, the Responsible Supplier makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein.

CERTIFICATION AND CERTIFICATE HOLDER DETAILS						
Company Nam	e Schneider Electric	c (Australia) Pty Ltd	Other Name			
Address	33-37 Port Wakefie	ld Road Gepps Cross SA 5	094 Australia			
Client ID	102093	Global-Mark Fi	le Number: 102093-336	System 1 Approval		
Certification and Authorized Mark Number	GMA-514128		Revision Number 00			
Certification Standard(s)	IEC 60947-4-1:2018	(Ed 4.0) Low-voltage swit	chgear and controlgear - Pai	rt 4-1: Contactors and motor-starters –		
	Electromechanical contactors and motor-starters					
Type of Certification	Electrical Safety Pr	oduct Scheme Global-1	Mark Electrical Product Safe	ty Certification Scheme		

CERTIFICATE DATES
Certificate Issue Date
Certificate Last Update Date
Certification Expiry Date
6/12/2027

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia



Certificate of Suitability

CERTIFIED ELECTRICAL	EQUIPMENT			
Declared Article	Product Description	Trade Name	Model Number	Rating
Non declared	High power Contactor	Schneider Electric	LC1G6304EHEA	Coil voltage: 48-130V AC/DC,Utilisation category=AC-1/AC-5a/AC- 5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC- 1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G6304EHEN	Coil voltage: 48-130V AC/DC,Utilisation category=AC-1/AC-5a/AC- 5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC- 1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G6304KUEN	Coil voltage: 100-250V AC/DC,Utilisation category=AC-1/AC-5a/AC- 5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC- 1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G6304LSEA	Coil voltage: 200-500V AC/DC,Utilisation category=AC-1/AC-5a/AC- 5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC- 1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G630EHEA	Coil voltage: 48-130V AC/DC, Utilisation category=AC-1/AC-3/AC- 3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC- 5, Rated operational current (AC-1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G630EHEN	Coil voltage: 48-130V AC/DC, Utilisation category=AC-1/AC-3/AC- 3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC- 5, Rated operational current (AC-1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G630KUEN	Coil voltage: 100-250V AC/DC,Utilisation category=AC-1/AC-3/AC- 3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC- 5, Rated operational current (AC-1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G630LSEA	Coil voltage: 200-500V AC/DC,Utilisation category=AC-1/AC-3/AC- 3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC- 5, Rated operational current (AC-1)=1050 A
Non declared	High power Contactor	Schneider Electric	LC1G8004EHEA	Coil voltage: 48-130V AC/DC, Utilisation category=AC-1/AC-5a/AC- 5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC- 1)=1050 A

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia



Certificate of Suitability

Non declared	High power Contactor	Schneider Electric	LC1G8004EHEN	Coil voltage: 48-130V AC/DC, Utilisation category=AC-1/AC-5a/AC- 5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC-			
				1)=1050 A			
Non declared	High power Contactor	Schneider Electric	LC1G8004KUEN	Coil voltage: 100-250V AC/DC, Utilisation category=AC-1/AC-5a/AC-			
				5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC- 1)=1050 A			
Non declared	High power Contactor	Schneider Electric	LC1G8004LSEA	Coil voltage: 200-500V AC/DC, Utilisation category=AC-1/AC-5a/AC-			
				5b/AC-6a/AC-6b/DC-1/DC-3/DC-5, Rated operational current (AC-			
				1)=1050 A			
Non declared	High power Contactor	Schneider Electric	LC1G800EHEA	Coil voltage: 48-130V AC/DC, Utilisation category=AC-1/AC-3/AC-			
				3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC-			
				5, Rated operational current (AC-1)=1050 A			
Non declared	High power Contactor	Schneider Electric	LC1G800EHEN	Coil voltage: 48-130V AC/DC, Utilisation category=AC-1/AC-3/AC-			
				3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC-			
				5, Rated operational current (AC-1)=1050 A			
Non declared	High power Contactor	Schneider Electric	LC1G800KUEN	Coil voltage: 100-250V AC/DC, Utilisation category=AC-1/AC-3/AC-			
				3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC-			
			(5, Rated operational current (AC-1)=1050 A			
Non declared	High power Contactor	Schneider Electric	LC1G800LSEA	Coil voltage: 200-500V AC/DC,Utilisation category=AC-1/AC-3/AC-			
				3e/AC-4/AC-5a/AC-5b/AC-6a/AC-6b/AC-8b/AC-8a/DC-1/DC-3/DC-			
				5, Rated operational current (AC-1)=1050 A			

Relevant Trademark (s)									
							1		
COMMENTS OR CONDITIONS ON THE CERTIFICATION									
Nil									
End of document	0					and the second			

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.



Certification Manager



Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia