

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-2134791-1  
**Report Reference** E352710-20140217  
**Date** 17-Sep-2021

**Issued to:** Schneider Electric Industries S A, DBA Telemecanique  
8001 Knightdale Blvd Knightdale, NC  
United States 27545

**This is to certify that  
representative samples of**

NISD - Emergency Stop Devices  
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 60947-1, 5th Ed., Issue Date: 2013-07-31, Revision  
Date: 2019-05-06, UL 60947-5-1, 3rd Ed., Issue Date:  
2014-03-28

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-2134791-1  
**Report Reference** E352710-20140217  
**Date** 17-Sep-2021

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

<b>Model</b>	<b>Category Description</b>
XB4B, followed by S or T, followed by 8 or 9, may be followed by 4, followed by 4 and followed by 2, 4, 41, 5 or 6 may be followed by additional digits.	Complete device, Emergency stop pushbutton with contact blocks
XB5A, followed by S or T, followed by 8 or 9, may be followed by 4, followed by 4 and followed by 2, 4, 41, 5 or 6 may be followed by additional digits.	Complete device, Emergency stop pushbutton with contact blocks



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>.