



UL iQ for Surge Protective Devices



Surge Protective Devices

E314042

Guide Information

Schneider Electric USA, Inc.

Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

Model(s): SDSB80111

Permanently Connected

| <u>SPD</u> <u>Type</u> | <u>Volts</u> <u>(V)</u> | <u>AC/DC</u> <u>DC PV</u> | <u>Phase</u> | <u>Amps</u> <u>(A)</u> | <u>Ambient</u> <u>Min(°C)</u> | <u>Ambient</u> <u>Max(°C)</u> | <u>Mode</u> | <u>VPR</u> <u>(Vpk)</u> | <u>MCOV</u> <u>(V)</u> | <u>In</u> <u>(kA)</u> | <u>SCCR</u> <u>(kA)</u> |
|---------------------------|----------------------------|------------------------------|--------------|---------------------------|----------------------------------|----------------------------------|-------------|----------------------------|---------------------------|--------------------------|----------------------------|
| 2 | 240/120 | AC | 1S | n/a | -35 | 85 | L-L | 1200 | 300 | 10 | 25 |
| | | | | | | | L-N | 800 | 150 | | |
| | | | | | | | L-G | 800 | 150 | | |
| | | | | | | | N-G | 1800 | 300 | | |

Evaluated to: UL 1449 4th Ed. Rev: 2018-08-01 and CSA C22.2 No. 269.2-13, 2013-06

Note - All models may be followed by additional suffixes.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2009-12-10

Last Revised: 2019-01-25

© 2019 UL LLC

