

Product End-of-Life Instructions

Product Range: Compact NSX 400-630 (400-630 A)

Marketing Model/Name:

The End of Life instruction (EOLI) covers the entire range:

- Compact NSX 400-630, 3 or 4-pole, fixed or draw-out circuit breaker with a rating of 400 A to 630 A
- Fitted with:
 - Micrologic control unit

Purpose:

The product family must be disposed according to the legislation of the country. This document is intended for use by end of life recyclers or treatment facilities. It provides the basic information to assure an appropriate end of life treatment for the components and materials of the product.

Note :

This product family is not in the scope of EU directive 2002/96/EC, Waste Electrical and Electronic Equipment (WEEE).



Size in mm (3P fixed type):

H x W x D in mm: Ex: 140 x 255 x 110

Weight in kg:

Between 6.05 kg and 8.13 kg without battery

Operations recommended for the end of life treatment

There are several steps to process the products at the end of life so as to recover components, materials or energy :
 Reuse → Separation for special treatment → Other dismantling → Shredding.

The components of the products that optimize the recycling performances are listed, identified and located hereunder.



Number on drawing	Components	Comment	
Components listed for special treatment which improves the recycling performances			
1	Printed circuit board	32 g	Electric board & Electronic Components
Components listed for operating hazards			
2	Spring	Ejections	

Schneider Electric SA
 43-45, boulevard Franklin Roosevelt
 F-92500 Rueil-Malmaison Cedex (France)
 Tel.: +33 (0) 1 41 29 70 00
 www.schneider-electric.com

The version of the Guide used to create the document: End of Life Instruction Drafting Guide of Schneider Electric version V3

ENVEOLI121004EN

Publication date : 11/10/2012