

Emergency lighting EXIWAY-PLUS  
IP42 L/450/1NC

# Product Environmental Profile



**Schneider**  
Electric

# Product Environmental Profile - PEP

## Product overview

The main function of the Emergency lighting EXIWAY product range is to provide emergency lighting in compliance with European standards.

This subrange consists of 10 commercial references (Exyway Plus IP42): OVA38888, OVA38889, OVA38866, OVA38872, OVA38880, OVA38881, OVA38879, OVA38873, OVA38867, OVA38878.

The representative product used for the analysis is EMERGENCY LIGHTING EXIWAYPLUS IP42 L/450/1NC OVA38888.

The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with the similar technology.

The extrapolation rules are described in the following chapters.


The environmental analysis was performed in conformity with ISO14040.

This analysis takes the stages of the life cycle of the product into account.

## Constituent materials

The mass of the product range is from 1050 G and 1240 G no including packaging. It is 1240 G for the EMERGENCY LIGHTING EXIWAYPLUS IP42 L/450/1NC OVA38888.

The constituent materials are distributed as follows:



## Substance assessment

Products of this range are designed in conformity with the requirements of the ROHS directive (European Directive 2002/95/EC of 27 January 2003) and do not contain, or in the authorised proportions, lead, mercury, cadmium, chromium hexavalent, flame retardant (polybromobiphenyles PBB, polybromodiphenylthethers PBDE) as mentioned in the Directive.

## Manufacturing

Emergency lighting EXIWAY is manufactured at a production site which complies with the regulations governing industrial sites.

## Distribution

The weight and volume of the packaging have been reduced, in compliance with the European Union's packaging directive.

The Emergency lighting EXIWAY OVA38888 packaging weight is 89,4 g. It consists of:

MATERIAL	WEIGHT
Cardboard (Kraft)	80 g
Paper (Recycled, With Deinking)	9.4 g
<b>Total</b>	<b>89.4</b>

The product distribution flows have been optimised by setting up local distribution centres close to the market areas.

# Product Environmental Profile - PEP

## Utilisation

The products of the Emergency lighting EXIWAY range do not generate environmental pollution requiring special precautionary measures (noise, emissions, and so on) in using phase

The dissipated power depends on the conditions under which the product is implemented and used.

The electrical power consumed by this Emergency lighting EXIWAY sub range spreads of between 1.6 W and 1.9 W. It is 2.1 W 1% in active mode and 1.9 W 98% in stand by mode for the referenced EMERGENCY LIGHTING EXIWAYPLUS IP42 L/450/1NC OVA38888.

During the products lifetime the battery should be substituted to preserve the declared performance.

## End of life

At end of life, the products in the Emergency lighting EXIWAY range have been optimized to decrease the amount of waste and valorise the components and materials of the product in the usual end of life treatment process.

The design and information have been achieved so as components are able to enter the usual end of life treatment processes as appropriate: depollution if recommended, reuse and/or dismantling if recommended so as to increase the recycling performances and shredding for separating the rest of materials.

The potential of recyclability of the products has been evaluated using the "Codde" recyclability and recoverability calculation method" (version V1, 20 Sep. 2008) and published by ADEME (French Agency for Environment and Energy Management).

According this method, the potential recyclability ratio is: 78%.

The recommendations to optimize the recycling performance are detailed in the product "End of Life Instructions" of this product range.

## Environmental impacts

The environmental impacts were analysed for the Manufacturing (M) phases, the Distribution (D) and the Utilisation (U) phases.

This product range is included in the category Energy consuming product (assumed lifetime service is 10 years and using scenario: 1.9 W and 98% uptime).

The EIME (Environmental Impact and Management Explorer) software, version 4.0, and its database, version 10.0 were used for the life cycle assessment (LCA).

The calculation has been done on EMERGENCY LIGHTING EXIWAYPLUS IP42 L/450/1NC OVA38888.

The electrical power model used is ITALIAN model.

Presentation of the product environmental impacts:

Indicator	Unit	For 1 EMERGENCY LIGHTING EXIWAYPLUS IP42 L/450/1NC OVA38888			
		S=M+D+U	M	D	U
Raw Material Depletion	Y-1	7,3257E-13	5,8085E-13	1,2831E-17	1,517E-13
Energy Depletion	MJ	2,1077E3	2,86E2	8,153	1,8136E3
Water Depletion	dm3	3,7434E2	2,5047E2	2,216	1,2165E2
Global Warming	g ~CO2	1,3679E5	1,5364E4	4,6772E2	1,2095E5
Ozone Depletion	g ~CFC-11	3,9157E-2	2,114E-3	2,8799E-4	3,6755E-2
Air Toxicity	m3	4,2284E7	6,6757E6	9,0805E4	3,5518E7
Photochemical Ozone Creation	g ~C2H4	67,669	5,149	3,6755E-1	62,152
Air Acidification	g ~H+	35,089	5,637	6,2897E-2	29,389
Water Toxicity	dm3	2,3913E4	7,3522E3	96,072	1,6465E4
Water Eutrophication	g ~PO4	7,983	5,719	3,5824E-2	2,229
Hazardous Waste Production	kg	7,4673E-1	2,4887E-1	4,9065E-4	4,9737E-1

The life cycle analysis shows that the U phase (M, D or U phase) is the life cycle phase which has the greatest impact on the majority of environmental indicators.

Extrapolation rules for product range:

Depending on the analysis of environmental impacts, the parameters of other products in this sub range may be proportionally extrapolated multiplying the values of the use (U) phase by the ratio of the power consumption values.

The product benefits from design optimisation which allows reducing its impact on environment.

# Product Environmental Profile - PEP

## System approach

As the product of the range are designed in accordance with the ROHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction within an assembly or an installation submitted to this Directive.

Please note that the environmental impacts of the product depend on the use and installation conditions of the product. Impacts values given above are only valid within the context specified and cannot be directly used to draw up the environmental assessment of the installation.

## Glossary

Raw Material Depletion (RMD)	This indicator quantifies the consumption of raw materials during the life cycle of the product. It is expressed as the fraction of natural resources that disappear each year, with respect to all the annual reserves of this material.
Energy Depletion (ED)	This indicator gives the quantity of energy consumed, whether if be from fossil, hydroelectric, nuclear or other sources. This indicator takes into account the energy from the material produced during combustion. It is expressed in MJ.
Water Depletion (WD)	This indicator calculates the volume of water consumed, including drinking water and water from industrial sources. It is expressed in m <sup>3</sup> .
Global Warming Potential (GWP)	The global warming of the planet is the result of the increase in the greenhouse effect due to the sunlight reflected by the earth's surface being absorbed by certain gases known as "greenhouse-effect" gases. This effect is quantified in gram equivalent CO <sub>2</sub> .
Ozone Depletion (OD)	This indicator defines the contribution to the phenomenon of the disappearance of the stratospheric ozone layer due to the emission of certain specific gases. This effect is expressed in gram equivalent of CFC-11.
Photochemical Ozone Creation (POC)	This indicator quantifies the contribution to the smog phenomenon (the photochemical oxidation of certain gases which generates ozone) and is expressed in gram equivalent of ethylene (C <sub>2</sub> H <sub>4</sub> ).
Air Acidification (AA)	The acid substances present in the atmosphere are carried by the rain. A high level of acidity in rain can cause damage to forests. The contribution of acidification is calculated using the acidification potentials of the substances concerned and is expressed in mole equivalent of H <sup>+</sup> .
Hazardous Waste Production (HWP)	This indicator gives the quantity of waste, produced along the life cycle of the product (manufacturing, distribution, use, including production of energy), that requires special treatments. It is expressed in kg.



We are committed to safeguarding our planet by "Combining innovation and continuous improvement to meet the new environmental challenges".

**Schneider Electric Industries SAS**  
35 rue Joseph Monier  
92500 Rueil-Malmaison  
France  
[www.schneider-electric.com](http://www.schneider-electric.com)

This document is based on ISO14020 which relates to the general principles of environmental declarations and the ISO14025 relating to type III environmental declarations.  
The version of the Guide used to create the document: Product Environmental Profiles Drafting Guide version V12

Produced and published by: Schneider Electric