

Product Environmental Profile

Wiser Energy™ QO™ Load Center






General information

Representative product	Wiser Energy™ QO™ Load Center - QO142M200PCMR
Description of the product	The Wiser Energy™ QO™ load center monitors the power consumption of up to 18 circuit breakers, as well as residential solar generation. These capabilities allow instantaneous and historical insight into how the residential electrical energy is performing and how to achieve different types of goals.
Functional unit	To measure power consumption of 18 circuits during 10 years, to protect persons against direct contact with live parts, and allow grouping of protection devices in a single enclosure or a cabinet having the following dimensions 39 in x 14 in x 3.74 in, while protecting against mechanical impacts and the penetration of solid objects and liquids (NEMA Type 1).



Constituent materials

Reference product mass	18543 g including the product, its packaging and additional elements and accessories
------------------------	--



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information


The Wiser Energy™ QO™ Load Center presents the following relevant environmental aspects	
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized. Packaging weight is 1336,8 g, consisting of cardboard (1120g), PET Polyethylene Terephthalate (5.4g) and paper (206g) Product distribution optimised by setting up local distribution centers.
Installation	The Wiser Energy™ QO™ Load Center does not require any installation operations.
Use	The product does not require special maintenance operations.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic cards (208g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 94% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).



Environmental impacts

Reference life time	10 years			
Product category	Active products			
Installation elements	No special components needed			
Use scenario	The product is in active mode 100% of the time with a power use of 29.2W for 10 years.			
Geographical representativeness	USA			
Technological representativeness	The Wiser Energy™ QO™ load center monitors the power consumption of up to 18 circuit breakers, as well as residential solar generation. These capabilities allow instantaneous and historical insight into how the residential electrical energy is performing and how to achieve different types of goals.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: USA	Electricity mix; AC; consumption mix, at consumer; 120V; US	Electricity mix; AC; consumption mix, at consumer; 120V; US	Electricity mix; AC; consumption mix, at consumer; 120V; US

Compulsory indicators		Wiser Energy™ QO™ Load Center - QO142M200PCMR					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	9,23E-02	9,22E-02	0*	0*	1,74E-05	0*
Contribution to the soil and water acidification	kg SO ₂ eq	3,91E+01	3,74E+01	2,14E-02	0*	1,70E+00	4,76E-03
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	3,95E+00	3,49E+00	4,91E-03	0*	4,47E-01	1,17E-03
Contribution to global warming	kg CO ₂ eq	9,01E+03	7,23E+03	4,74E+00	0*	1,77E+03	1,80E+00
Contribution to ozone layer depletion	kg CFC11 eq	1,22E-03	1,19E-03	0*	0*	3,21E-05	0*
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2,31E+00	2,04E+00	1,52E-03	0*	2,72E-01	5,11E-04
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	4,32E+01	4,01E+01	0*	0*	3,13E+00	0*
Total Primary Energy	MJ	1,23E+05	9,94E+04	6,71E+01	0*	2,38E+04	2,39E+01



Optional indicators		Wiser Energy™ QO™ Load Center - QO142M200PCMR					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	1,05E+05	7,73E+04	6,66E+01	0*	2,80E+04	2,18E+01
Contribution to air pollution	m³	4,78E+05	3,28E+05	1,96E+02	0*	1,50E+05	1,69E+02
Contribution to water pollution	m³	5,79E+05	4,90E+05	7,80E+02	0*	8,73E+04	1,87E+02
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	7,12E+00	7,12E+00	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	8,45E+03	7,02E+03	0*	0*	1,43E+03	0*
Total use of non-renewable primary energy resources	MJ	1,15E+05	9,24E+04	6,70E+01	0*	2,24E+04	2,39E+01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	8,44E+03	7,01E+03	0*	0*	1,43E+03	0*
Use of renewable primary energy resources used as raw material	MJ	7,81E+00	7,81E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1,15E+05	9,23E+04	6,70E+01	0*	2,24E+04	2,39E+01
Use of non renewable primary energy resources used as raw material	MJ	4,93E+01	4,93E+01	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	2,25E+04	2,25E+04	0*	0*	4,74E+01	1,76E+01
Non hazardous waste disposed	kg	1,80E+04	1,77E+04	0*	0*	2,71E+02	0*
Radioactive waste disposed	kg	1,41E+01	1,41E+01	0*	0*	2,79E-02	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	1,90E+01	2,37E+00	0*	1,32E+00	0*	1,53E+01
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	8,86E-02	2,05E-03	0*	0*	0*	8,65E-02
Exported Energy	MJ	0,00E+00	0*	0*	0*	0*	0*



* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.5, database version 2016-11.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration N°	SCHN-00262-V01.01-EN	Drafting rules	PCR-ed3-EN-2015 04 02
Verifier accreditation N°	VH08	Information and reference documents	www.pep-ecopassport.org
Date of issue	10/2017		
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010			
Internal		External X	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »			





Schneider Electric USA, Inc

Country Customer Care Center

<http://www2.schneider-electric.com/sites/corporate/en/support/operations/local-operations/local-operations.page>

1-888-SquareD (1-888-778-2733)

800 Federal Street

Andover, MA 01810

www.schneider-electric.com

Published by Schneider Electric

SCHN-00262-V01.01-EN

© 2016 - Schneider Electric – All rights reserved

10/2017