

Product Environmental Profile

Tian Lang Enclosure 48 modules White 3 rows






General information

Representative product	Tian Lang Enclosure 48 modules White 3 rows - TLA48B
Description of the product	Tian Lang Enclosure 48 modules White 3 rows is to provide fixed installation space for electrical products and protect users from directly touching live components.
Functional unit	Protect persons during 20 years against direct contact with live parts and allow grouping monitoring, control and protection devices in a single enclosure or a cabinet having the following dimensions 120 x 542 x 402, while protecting against mechanical impacts (IK05) and the penetration of solid objects and liquids (IP40).



Constituent materials

Reference product mass	7313.43 g including the product, its packaging and additional elements and accessories
------------------------	--



Plastics	35.0%
Metals	52.0%
Others	13.0%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 2 January 2013, amended in March 2015, 2015/863/EU and in November 2017, 2017/2102/EU) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers – PBDE), Bis (2-ethylhexyl)phthalate - DEHP, Benzyl butyl phthalate– BBP, Dibutyl phthalate - DBP, Diisobutyl phthalate - DIBP) as

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



Additional environmental information

The Tian Lang Enclosure 48 modules White 3 rows presents the following relevant environmental aspects


Manufacturing	Manufactured at a production site complying with the regulations
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 1036.5 g, consisting of cardboard(93.0%),PE(4.7%),paper(1.2%),PC(1.1%)
Installation	Ref TLA48B does not require any installation operations.
Use	The product does not require special maintenance operations.
End of life	<p>End of life optimized to decrease the amount of waste and allow recovery of the product components and materials</p> <p>No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.</p> <p>Recyclability potential: 72% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).</p>



Environmental impacts

Reference life time	20 years			
Product category	Unequipped enclosures and cabinets			
Installation elements	The product does not require special installation procedure and requires little to no energy to install. The disposal of the packaging materials are accounted for during the installation phase (including transport to disposal).			
Use scenario	The product is in active mode 100% of the time with a power use of 0W, for 20 years			
Geographical representativeness	China			
Technological representativeness	Tian Lang Enclosure 48 modules White 3 rows is to provide fixed installation space for electrical products and protect users from directly touching live components.			
Energy model used	Manufacturing	Installation	Use	End of life
	Energy model used: China	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN

Compulsory indicators		Tian Lang Enclosure 48 modules White 3 rows - TLA48B					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	4.86E-03	4.86E-03	0*	0*	0*	0*
Contribution to the soil and water acidification	kg SO ₂ eq	9.89E-02	9.24E-02	4.31E-03	2.44E-04	0*	1.91E-03
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	1.84E-02	1.69E-02	9.92E-04	7.68E-05	0*	4.93E-04
Contribution to global warming	kg CO ₂ eq	4.99E+01	4.81E+01	9.44E-01	5.89E-02	0*	8.27E-01
Contribution to ozone layer depletion	kg CFC11 eq	3.72E-06	3.68E-06	1.91E-09	0*	0*	4.14E-08
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	1.27E-02	1.22E-02	3.07E-04	1.83E-05	0*	2.02E-04
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	1.14E+01	1.14E+01	0*	0*	0*	0*
Total Primary Energy	MJ	8.12E+02	7.88E+02	1.33E+01	7.59E-01	0*	9.43E+00



Optional indicators		Tian Lang Enclosure 48 modules White 3 rows - TLA48B					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	4.76E+02	4.54E+02	1.33E+01	7.47E-01	0*	7.57E+00
Contribution to air pollution	m³	1.10E+04	1.09E+04	4.01E+01	2.76E+00	0*	6.74E+01
Contribution to water pollution	m³	9.88E+03	9.64E+03	1.55E+02	8.74E+00	0*	7.69E+01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	9.05E-01	9.05E-01	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1.24E+01	1.24E+01	1.78E-02	2.51E-03	0*	1.05E-02
Total use of non-renewable primary energy resources	MJ	7.99E+02	7.76E+02	1.33E+01	7.56E-01	0*	9.42E+00
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	9.34E+00	9.31E+00	1.78E-02	2.51E-03	0*	1.05E-02
Use of renewable primary energy resources used as raw material	MJ	3.09E+00	3.09E+00	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	6.95E+02	6.71E+02	1.33E+01	7.56E-01	0*	9.42E+00
Use of non renewable primary energy resources used as raw material	MJ	1.04E+02	1.04E+02	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	3.91E+02	3.83E+02	0*	0*	0*	8.30E+00
Non hazardous waste disposed	kg	3.27E+01	3.26E+01	3.35E-02	5.54E-02	0*	2.90E-02
Radioactive waste disposed	kg	1.39E-02	1.39E-02	2.39E-05	3.08E-06	0*	4.51E-05
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	6.38E+00	7.39E-01	0*	9.88E-01	0*	4.65E+00
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	7.33E-02	0*	0*	0*	0*	7.33E-02
Exported Energy	MJ	3.09E-03	2.90E-04	0*	2.80E-03	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.9.4, database version 2020-12 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number	ENVPEP2303001_V1	Drafting rules	PCR-ed3-EN-2015 04 02
Date of issue	03/2023	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Validity period	5 years	Information and reference documents	www.pep-ecopassport.org
Independent verification of the declaration and data			
Internal	X	External	
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14021:2016 « Environmental labels and declarations - Self-declared environmental claims (Type II environmental labelling) »			

Schneider Electric Industries SAS

Country Customer Care Center

<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

ENVPEP2303001_V1

© 2019 - Schneider Electric – All rights reserved

03/2023