Product Environmental Profile

200A VisiPacT[™] F-Series Heavy Duty Safety Switch








General information							
Reference product	200A VisiPacT™ F-Series Heavy Duty Safety Switch - VHU364AWKGL						
Description of the product	The main purpose of the F-series safety switch is to isolate power and provide an effective way to interrupt power in an emergency. Two primary applications for safety switches are as a lockout on sight disconnect and as a circuit isolation device.						
Functional unit	Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 600 V and rated current 200 A. This function is provided for 20 years. The product qualifies for the standards UL50E Type 12, UL98 & NEMA KS1.						

<u>8</u> **Constituent materials** 24327 g including the product, its packaging and additional elements and accessories Copper - 4.5% Aluminium - 1.3% Stainless steel - 0.8% Zamak - 0.3% Cardboard - 1.3% Steel - 82.3% Various - 1.1% _ Paper - <0.1% PBT Polybutylene Terephtalate - 5.9% UP Polyester - 1.7% PC Polycarbonate - 0.5% PA Polyamide - 0.2% PET Polyethilene Terephtalate - 0.1% EPS Expandable Polystyrene - <0.1% Metals 89.2% Plastics 8.4%

Substance assessment

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website https://www.se.com/ww/en/work/support/green-premium/

2.4%



Others

\mathcal{O} Environmental impacts

Reference service life time	20 years					
Product category	Disconnectors - Low voltage					
Installation elements	No special installation components need during installation phase					
Use scenario	Load rate: 50% Use time rate (closed unit): 30% of RLT					
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production.					
Geographical representativeness	United States, Canada, Mexico.					
	[A1 - A3]	[A5]	[B6]	[C1 - C4]		
Energy model used		Electricity Mix; Production mix; Low voltage; US	Electricity Mix; Production mix; Low voltage; US	Electricity Mix; Production mix; Low voltage; US		
	Electricity Mix; Production mix; Low voltage; US	Electricity Mix; Production mix; Low voltage; CA	Electricity Mix; Production mix; Low voltage; CA	Electricity Mix; Production mix; Low voltage; CA		
		Electricity Mix; Production mix; Low voltage; MX	Electricity Mix; Production mix; Low voltage; MX	Electricity Mix; Production mix; Low voltage; MX		

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - http://www.schneider-electric.com/contact

Mandatory Indicators			200A VisiPa	acT™ F-Series I	Heavy Duty Safet	y Switch - VHU3	64AWKGL	
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	2.59E+02	1.36E+02	7.01E+00	3.62E-01	5.95E+01	5.59E+01	-1.45E+02
Contribution to climate change-fossil	kg CO2 eq	2.58E+02	1.36E+02	7.01E+00	3.62E-01	5.95E+01	5.57E+01	-1.43E+02
Contribution to climate change-biogenic	kg CO2 eq	1.05E+00	7.64E-01	0*	1.62E-04	6.48E-02	2.23E-01	-1.50E+00
Contribution to climate change-land use and land use change	e kg CO2 eq	3.71E-06	0*	0*	0*	0*	3.71E-06	0.00E+00
Contribution to ozone depletion	kg CFC-11 eq	2.89E-05	2.22E-05	6.19E-06	0*	2.48E-07	2.94E-07	-2.20E-05
Contribution to acidification	mol H+ eq	1.30E+00	7.43E-01	3.05E-02	2.61E-04	3.11E-01	2.13E-01	-1.35E+00
Contribution to eutrophication, freshwater	kg (PO4)³⁻eq	8.23E-03	2.16E-04	0*	6.21E-06	9.46E-05	7.92E-03	-2.67E-04
Contribution to eutrophication marine	kg N eq	1.89E-01	1.00E-01	1.40E-02	1.40E-04	3.71E-02	3.76E-02	-8.61E-02
Contribution to eutrophication, terrestrial	mol N eq	2.10E+00	1.10E+00	1.52E-01	1.05E-03	4.38E-01	4.18E-01	-9.97E-01
Contribution to photochemical ozone formation - human health	kg COVNM eq	7.28E-01	4.10E-01	4.98E-02	3.56E-04	1.23E-01	1.45E-01	-3.73E-01
Contribution to resource use, minerals and metals	kg Sb eq	1.14E-02	1.12E-02	0*	0*	2.59E-06	2.25E-04	-4.04E-02
Contribution to resource use, fossils	MJ	1.05E+04	5.21E+03	8.52E+01	0*	1.27E+03	3.97E+03	-3.05E+03
Contribution to water use	m3 eq	7.52E+01	4.65E+01	3.56E-01	0*	2.11E+00	2.62E+01	-7.66E+01

Additional indicators for the French regulation are available as well

Inventory flows Indicators			200A VisiPacT™ F-Series Heavy Duty Safety Switch - VHU364AWKGL					
			Manufact.	Distribution	Installation	Use	End of Life	Benefits
Inventory flows	Unit	Total	[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	2.16E+02	1.86E+01	0*	0*	1.92E+02	5.37E+00	-4.77E+01
Contribution to use of renewable primary energy resources used as raw material	MJ	6.15E+00	6.15E+00	0*	0*	0*	0*	-3.60E-02
Contribution to total use of renewable primary energy resources	MJ	2.22E+02	2.47E+01	0*	0*	1.92E+02	5.37E+00	-4.77E+01
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw materia	I MJ	1.05E+04	5.15E+03	8.52E+01	0*	1.27E+03	3.97E+03	-3.05E+03
Contribution to use of non renewable primary energy resources used as raw material	MJ	5.81E+01	5.81E+01	0*	0*	0*	0*	0.00E+00
Contribution to total use of non-renewable primary energy resources	MJ	1.05E+04	5.21E+03	8.52E+01	0*	1.27E+03	3.97E+03	-3.05E+03
Contribution to use of secondary material	kg	4.99E-02	4.99E-02	0*	0*	0*	0*	0.00E+00
Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to net use of freshwater	m³	1.75E+00	1.08E+00	8.28E-03	0*	4.91E-02	6.11E-01	-1.78E+00
Contribution to hazardous waste disposed	kg	7.46E+02	7.21E+02	0*	0*	1.13E+00	2.38E+01	-3.25E+03
Contribution to non hazardous waste disposed	kg	4.85E+01	3.91E+01	7.14E-03	3.52E-01	8.73E+00	3.26E-01	-1.30E+02
Contribution to radioactive waste disposed	kg	2.21E-02	1.89E-02	1.39E-03	1.32E-05	1.70E-03	1.67E-04	-7.15E-02
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to materials for recycling	kg	2.09E+01	8.00E-01	0*	0*	0*	2.01E+01	0.00E+00
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to exported energy	MJ	1.74E-01	0*	0*	1.74E-01	0*	0*	0.00E+00
Contribution to biogenic carbon content of the product	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00
Contribution to biogenic carbon content of the associated packaging	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00

 * represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - http://www.schneider-electric.com/contact

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number :	SCHN-00958-V01.01-EN	Drafting rules	PEP-PCR-ed4-2021 09 06				
Verifier accreditation N°	VH18	Supplemented by	PSR-0005-ed2-2016 03 29				
Date of issue	11/2023	Information and reference documents	www.pep-ecopassport.org				
		Validity period	5 years				
Independent verification of the declaration and data, in compliance with ISO 14025 : 2010							
Internal External X							
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (DDemain)							
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019							
The elements of the present PEP cannot be compared with elements from another program.							
Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »							

Schneider Electric Industries SAS Country Customer Care Center http://www.schneider-electric.com/contact 35, rue Joseph Monier CS 30323 F- 92500 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.se.com

SCHN-00958-V01.01-EN

Published by Schneider Electric ©2023 - Schneider Electric – All rights reserved

11/2023