Product Environmental Profile


TeSys Vario enclosed emergency switch disconnector, 63A





General information

Reference product	VCF4GE
Description of the product	TeSys Vario rotary switch disconnectors act as machine circuit load breakers and can be used for the manual stopping and starting of motors
Functional unit	Turn off all or part of an installation by separating the installation or part of the installation of all electrical energy or earth, for safety reasons with a rated voltage 690V AC and rated current 63A ensuring isolation characterized by rated voltage 8KV. This function is provided for 20 years.



Substance assessment

E

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website https://www.se.com/ww/en/work/support/green-premium/

W Additional environmental information

20%

End Of Life

Recyclability potential:

Recyclability rate has been calculated based on REEECY'LAB tool developed by Ecosystem, for components/materials not covered by the tool, data from the "ECO'DEEE recyclability and recoverability calculation method" was taken. If no data was found a conservative assumption was used (0% recyclability).

\mathcal{O} Environmental impacts

Reference service life time	20 years						
Product category	Disconnectors - Low voltage						
Installation elements	Ref VCF4GE does not require any installation operations.						
Use scenario	Load rate: 50% Use time rate (closed unit): 30% of RLT						
Technological representativeness	The Modules of Technologies such as material production, manufacturing process and transport technology used in this PEP analysis (LCA-EIME in this case) are Similar and representative of the actual type of technologies used to make the product in production						
Geographical representativeness	France						
	[A1 - A3]	[A5]	[B6]	[C1 - C4]			
Energy model used	Electricity Mix; Production mix; Low voltage; CZ	Electricity Mix; Production mix; Low voltage; FR	Electricity Mix; Production mix; Low voltage; FR	Electricity Mix; Production mix; Low voltage; FR			

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report and on demand in a digital format - Country Customer Care Center - http://www.schneider-electric.com/contact

Mandatory Indicators	TeSys Vario enclosed emergency switch disconnector, 63A - VCF4GE							
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life	Loads and Benefits
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]
Contribution to climate change	kg CO2 eq	8.84E+01	5.59E+00	1.35E-01	2.64E-01	7.98E+01	2.63E+00	-1.02E+00
Contribution to climate change-fossil	kg CO2 eq	8.81E+01	5.50E+00	1.35E-01	2.52E-01	7.96E+01	2.63E+00	-1.01E+00
Contribution to climate change-biogenic	kg CO2 eq	3.14E-01	9.50E-02	0*	1.17E-02	2.06E-01	1.83E-03	-1.41E-02
Contribution to climate change-land use and land use change	kg CO2 eq	3.05E-08	0*	0*	0*	0*	3.05E-08	0.00E+00
Contribution to ozone depletion	kg CFC-11 eq	1.53E-06	3.27E-07	2.07E-10	1.75E-08	1.17E-06	8.51E-09	-1.53E-07
Contribution to acidification	mol H+ eq	4.92E-01	2.57E-02	8.71E-04	1.05E-03	4.62E-01	2.45E-03	-6.86E-03
Contribution to eutrophication, freshwater	kg (PO4)³ [—] eq	3.90E-03	3.89E-05	0*	1.91E-06	3.79E-03	6.52E-05	-4.60E-06
Contribution to eutrophication marine	kg N eq	6.86E-02	3.90E-03	4.09E-04	2.77E-04	6.36E-02	4.91E-04	-7.95E-04
Contribution to eutrophication, terrestrial	mol N eq	9.66E-01	4.01E-02	4.49E-03	2.09E-03	9.14E-01	6.01E-03	-7.92E-03
Contribution to photochemical ozone formation - human health	kg COVNM eq	2.06E-01	1.41E-02	1.13E-03	5.59E-04	1.88E-01	1.74E-03	-2.61E-03
Contribution to resource use, minerals and metals	kg Sb eq	2.54E-04	2.14E-04	0*	0*	3.78E-05	1.85E-06	-1.82E-04
Contribution to resource use, fossils	MJ	1.55E+04	1.02E+02	1.89E+00	2.75E+00	1.53E+04	3.48E+01	-1.65E+01
Contribution to water use	m3 eq	7.43E+00	1.13E+00	0*	1.13E-01	5.78E+00	4.08E-01	-5.48E-01

Additional indicators for the French regulation are available as well

Inventory flows Indicators				TeSys Vario enclosed emergency switch disconnector, 63A - VCF4GE					
Inventory flows	Unit	Total	Manufact.	Distribution	Installation	Use	End of Life	Loads and Benefits	
			[A1 - A3]	[A4]	[A5]	[B1 - B7]	[C1 - C4]	[D]	
Contribution to use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.42E+03	6.90E-01	0*	1.97E-01	1.42E+03	0*	1.42E+00	
Contribution to use of renewable primary energy resources used as raw material	MJ	2.88E+00	2.88E+00	0*	0*	0*	0*	-2.61E+00	
Contribution to total use of renewable primary energy resources	MJ	1.42E+03	3.57E+00	0*	1.97E-01	1.42E+03	0*	-1.19E+00	
Contribution to use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	1.54E+04	8.10E+01	1.89E+00	2.75E+00	1.53E+04	3.48E+01	-1.65E+01	
Contribution to use of non renewable primary energy resources used as raw material	MJ	2.14E+01	2.14E+01	0*	0*	0*	0*	0.00E+00	
Contribution to total use of non-renewable primary energy resources	MJ	1.55E+04	1.02E+02	1.89E+00	2.75E+00	1.53E+04	3.48E+01	-1.65E+01	
Contribution to use of secondary material	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to net use of freshwater	m³	1.73E-01	2.64E-02	0*	2.62E-03	1.35E-01	9.51E-03	-1.28E-02	
Contribution to hazardous waste disposed	kg	1.89E+01	1.69E+01	0*	3.12E-03	1.19E+00	8.51E-01	-1.44E+01	
Contribution to non hazardous waste disposed	kg	1.83E+01	9.05E+00	4.74E-03	8.58E-01	7.67E+00	7.11E-01	-4.22E+00	
Contribution to radioactive waste disposed	kg	6.60E-03	3.23E-03	3.38E-06	1.15E-04	3.22E-03	2.85E-05	-3.93E-04	
Contribution to components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to materials for recycling	kg	3.12E-01	0*	0*	1.45E-01	0*	1.67E-01	0.00E+00	
Contribution to materials for energy recovery	kg	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to exported energy	MJ	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to biogenic carbon content of the product	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	
Contribution to biogenic carbon content of the associated packaging	kg de C	0.00E+00	0*	0*	0*	0*	0*	0.00E+00	

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version v5.9.4, database version 2022-01 in compliance with ISO14044.

Detailed results, including all the optional indicators mentioned in PCRed4, and the split of the Use Phase (B1 to B7), are available in the LCA report

and on demand in a digital format - Country Customer Care Center - http://www.schneider-electric.com/contact

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration nui	nber :	ENVPEP2211019_V2	Drafting rules	PEP-PCR-ed4-2021 09 06			
Verifier accredit	tion N°		Supplemented by	PSR-0005-ed2-2016 03 29			
Date of issue		12023/12/7	Information and reference documents	www.pep-ecopassport.org			
			Validity period	5 years			
Independent verification of the declaration and data, in compliance with ISO 14021 : 2016							
Internal	nternal X External						
The PCR review was conducted by a panel of experts chaired by Julie ORGELET (Ddemain)							
PEP are compliant with XP C08-100-1 :2016 or EN 50693:2019							
The elements of the present PEP cannot be compared with elements from another program.							
Document in compliance with ISO 14021 : 2016 « Environmental labels and declarations. Type II environmental declarations »							

Schneider Electric Industries SAS Country Customer Care Center http://www.se.com/contact 35, rue Joseph Monier CS 30323 F- 92500 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 928 298 512 €

WWW.Se.com ENVPEP2211019_V2 Published by Schneider Electric ©2023 - Schneider Electric – All rights reserved

2023/12/7