



Commercial status

This Product is Obsolete :

⚠ This Product is Obsolete

Main

Range	Compact
Range of product	NSJ400...600 NS400...630 NS100...250 NR100...250 NS400...630 DC NR400...630 NS100...250 DC NB400...600 NSF150...250 NS125E
Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	Compact NSF Compact NS Compact NR Compact NB Compact NSJ
Voltage release type	Shunt trip release
[Uc] control circuit voltage	125 V DC

Complementary

Control signal type	Impulse Maintained
Impulse duration	>= 20 ms
Threshold tripping voltage	0.7...1.1 x Un
Response time	50 ms
Auxiliary connection terminal	Screw terminal 0...1.5 mm ²

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative

Ordering and shipping details

Category	01103 - H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES
Discount Schedule	DE2
GTIN	00785901110040
Nbr. of units in pkg.	1
Package weight(Lbs)	0.80000000000000004
Returnability	N

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status : End of commercialisation