Product data sheet
Characteristics

9036DG2R
Float switch, Pumptrol, open tank, NEMA 1, pedestal mounted, 2 NO DPST DB contacts

Green Premium

Product availability: Non-Stock - Not normally stocked in distribution facility
Important message: We have updated the process to order Telemecanique Sensors products. For more information, please contact your Telemecanique Sensors representative at (US.salesorders@tesensors.com).You can find all product information on the Telemecanique Sensors website: https://tesensors.com/us/en

Commercial status
This Product is Obsolete : SEP 01, 2023

⚠ This Product is Obsolete

Main

Range of Product	Pumptrol
Product or Component Type	Float switch
Device Application	Open tank general purpose
Device short name	9036D
Product Specific Application	Liquid level control
Electrical circuit type	Power circuit
Quantity per Set	Set of 1
Type of Packing	Individual

Complementary

Product destination	For open tank or sump
Device mounting	Pedestal
Cable entry number	3 knock-outs for 1/2" conduit UL 508
Contacts type and composition	2 NO, snap action, DPST-DB, Form XX
Controlled fluid	Fresh water specific gravity of 0.85 in or higher Sea water specific gravity of 0.85 in or higher Hydraulic oil specific gravity of 0.85 in or higher Corrosive fluid specific gravity of 0.85 in or higher
Motor power kW	1.5 KW 2 hp)115 V AC, 1 phase 2.2 KW 3 hp)115 V AC, 3 phase 2.2 KW 3 hp)230 V AC, 1 phase 3.7 KW 5 hp)230 V AC, 3 phase 0.75 KW 1 hp)460 V AC, 3 phase 0.75 KW 1 hp)475 V AC, 3 phase 0.18 KW 0.25 hp)32 V DC 0.37 KW 0.5 hp)115 V DC 0.37 KW 0.5 hp)230 V DC
Electrical connection	Screw-clamp terminals 10 AWG
Contact operation	Contacts open on liquid rise

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Float movement	Variable adjustable
Float position	Any
Float rod angle	Vertical
Force down to trip	8 Ozf
Force up to trip	9 Ozf
Short-circuit protection	20 A cartridge fuse gG
Local signalling	Without
Enclosure Material	Polypropylene or equivalent
Operating position	Vertical position only
Electrical durability	100 Cycles 60 cyc/mn
Mechanical durability	300 Cycles
Terminal block type	4 terminals
Maximum operating rate	60 Cyc/Mn
[Ui] rated insulation voltage	575 V UL 508
Net Weight	1.19 Lb(US) (0.54 kg)
Terminals description ISO n°1	Line-load-load-line
Factory modification	Without
Kit composition	Float switch Rod and float are to be choosen in accessories

Environment

Standards	CE UL 508
Ambient Air Temperature for Operation	-22…200 °F (-30…93 °C)
Ambient Air Temperature for Storage	-22…200 °F (-30…93 °C)
NEMA degree of protection	NEMA 1 UL 50
Product Certifications	UL Listed[RETURN]CSA

Ordering and shipping details

Category	US1CP7G21591
Discount Schedule	CP7G
GTIN	785901576433
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.50 In (11.43 cm)
Package 1 Width	3.40 In (8.636 cm)
Package 1 Length	7.00 In (17.78 cm)
Package 1 Weight	17.92 Oz (508.0 g)
Unit Type of Package 2	PAL
Number of Units in Package 2	336
Package 2 Height	40.00 In (101.6 cm)
Package 2 Width	40.00 In (101.6 cm)
Package 2 Length	48.00 In (121.92 cm)
Package 2 Weight	400.00 Lb(US) (181.437 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months

Product Life Status : End of commercialisation