



Main

| | |
|---------------------------|---|
| Range of product | ProDis |
| Range | Prodis |
| Product name | DT40 |
| Product or component type | Miniature circuit-breaker |
| Device short name | DT40 |
| Device application | Distribution |
| Poles description | 3P |
| Number of protected poles | 3 |
| [In] rated current | 32 A |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | D |
| Breaking capacity | 4500 A Icn at 400 V AC 50 Hz conforming to EN/IEC 60898-1 6 KA Icu at 400...415 V AC 50 Hz conforming to IEC 60947-2 |
| Suitability for isolation | Yes |
| Quality labels | NF |

Complementary

| | |
|--|--|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 400 V AC 50 Hz between phases |
| Magnetic tripping limit | 10...14 x In |
| [Ics] rated service breaking capacity | 4500 A 100 % x Icn at 400 V AC 50 Hz conforming to EN/IEC 60898-1 4.5 KA 75 % x Icu at 400 V AC 50 Hz conforming to IEC 60947-2 |
| Limitation class | 3 conforming to EN/IEC 60898-1 |
| [Ui] rated insulation voltage | 440 V AC 50 Hz |
| [Uimp] rated impulse withstand voltage | 4 KV conforming to IEC 60947-2 |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | ON/OFF indication |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| 9 mm pitches | 6 |
| Height | 81 Mm |
| Width | 54 Mm |
| Depth | 78 Mm |
| Net weight | 310 G |

| | |
|-----------------------------|--|
| Colour | White |
| Mechanical durability | 20000 Cycles |
| Electrical durability | 10000 Cycles |
| Locking options description | Padlocking device |
| Connections - terminals | Tunnel type terminals downstream0.33...10 mm ² flexible Tunnel type terminals downstream0.75...16 mm ² rigid Tunnel type terminals upstream0.33...10 mm ² flexible Tunnel type terminals upstream0.75...16 mm ² rigid |
| Wire stripping length | 13 Mm |
| Tightening torque | 2 N.M |
| Earth-leakage protection | Separate block |

Environment

| | |
|---------------------------------------|----------------------------------|
| Standards | EN/IEC 60898-1 EN/IEC 60947-2 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Pollution degree | 3 conforming to IEC 60947-2 |
| Tropicalisation | 2 conforming to IEC 60068-1 |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -40...70 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**