

### Main

Range of product	Altivar Process ATV600
Product or component type	Variable speed drive
Product specific application	Process and utilities
Device short name	ATV6A0
Variant	Modular version
Product destination	Asynchronous motors Synchronous motors
Mounting mode	Cabinet mount
Kit composition	Mechanical mounting kits Set of fuses Power connection 1 control unit 1 power module 160 kW
EMC filter	Integrated with <= 300 m conforming to EN/IEC 61800-3 category C3
IP degree of protection	IP00 (for IP21 or IP54 cabinet integration) conforming to IEC 60529 IP00 (for IP21 or IP54 cabinet integration) conforming to IEC 61800-5-1
Type of cooling	Forced convection
Supply frequency	50...60 Hz - 5...5 %
Network number of phases	3 phases
[Us] rated supply voltage	480 V - 15...10 %
Prospective line Isc	50 kA
Asynchronous motor control profile	Optimized torque mode Variable torque standard Constant torque standard
Synchronous motor control profile	Permanent magnet motor
Speed drive output frequency	0.1...500 Hz
Nominal switching frequency	2.5 kHz
Switching frequency	2...8 kHz adjustable 2.5...8 kHz with derating factor
Safety function	STO (safe torque off) SIL 3
Discrete input logic	16 preset speeds
Communication port protocol	Modbus TCP Ethernet Modbus serial
Option card	Slot A: communication module Profibus DP V1 Slot A: communication module DeviceNet Slot A: communication module Profinet Slot A: communication module CANopen daisy chain RJ45 Slot A/slot B: output relay extension module Slot A: communication module CANopen SUB-D 9 Slot A: communication module Modbus TCP/EtherNet/IP Slot A/slot B: digital and analog I/O extension module Slot A: communication module CANopen screw terminals

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Complementary

Output voltage	$\leq$ power supply voltage
Permissible temporary current boost	1.1 x I <sub>n</sub> during 60 s during normal duty) 1.5 x I <sub>n</sub> during 60 s during heavy duty)
Motor slip compensation	Can be suppressed Automatic whatever the load Not available in permanent magnet motor law Adjustable
Acceleration and deceleration ramps	S, U or customized Linear adjustable separately from 0.01...9999 s
Braking to standstill	By DC injection
Protection type	Safe torque off: drive Overspeed: drive Motor phase break: motor Break on the control circuit: drive Thermal protection: motor Overcurrent between output phases and earth: drive Overheating: drive Short-circuit protection: drive Thermal protection: drive Overload of output voltage: drive Overvoltages on the DC bus: drive Line supply undervoltage: drive Motor phase break: drive Line supply overvoltage: drive Line supply phase loss: drive Safe torque off: motor
Frequency resolution	Analog input: 0.012/50 Hz Display unit: 0.1 Hz
Electrical connection	Motor: M10 x 2 bars Line side: screw terminal Control: removable screw terminals 0.5...1.5 mm <sup>2</sup> /AWG 20...AWG 16
Connector type	RJ45 (on the remote graphic terminal)For Ethernet/Modbus TCP RJ45 (on the remote graphic terminal)For Modbus serial
Physical interface	2-wire RS 485For Modbus serial
Transmission frame	RTUFor Modbus serial
Transmission rate	4.8, 9.6, 19.2, 38.4 kbit/sFor Modbus serial 10/100 Mbit/sFor Ethernet IP/Modbus TCP
Exchange mode	Half duplex, full duplex, autonegotiation Ethernet/Modbus TCP
Data format	8 bits, configurable odd, even or no parityFor Modbus serial
Type of polarization	No impedanceFor Modbus serial
Number of addresses	For Modbus serial
Method of access	Slave Modbus TCP
Supply	External supply for digital inputs: 24 V DC (19...30 V) $\leq$ 1.25 mA overload and short-circuit protection Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V D-C +/- 5 % $\leq$ 10 mA overload and short-circuit protection Internal supply for digital inputs and STO: 24 V DC (21...27 V) $\leq$ 200 mA overload and short-circuit protection
Local signalling	Local diagnostic: 3 LEDs Embedded communication status: 3 LEDs (dual colour) Communication module status: 4 LEDs (dual colour)
Analogue input number	3
Analogue input type	AI1, AI2, AI3 software-configurable voltage: 0...10 V DC 30 kOhm 12 bits AI1, AI2, AI3 software-configurable current: 0...20 mA/4...20 mA 250 Ohm 12 bits
Discrete input number	8
Discrete input type	DI1...DI6 programmable 24 V DC ( $\leq$ 30 V) 3.5 kOhm DI5, DI6 programmable as pulse input: 0...30 kHz 24 V DC ( $\leq$ 30 V) STOA, STOB safe torque off 24 V DC ( $\leq$ 30 V) > 2.2 kOhm
Input compatibility	DI1...DI6: discrete input level 1 PLC conforming to EN/IEC 61131-2 DI5, DI6: discrete input level 1 PLC conforming to IEC 65A-68 STOA, STOB: discrete input level 1 PLC conforming to EN/IEC 61131-2
Discrete input logic	Positive logic (source) (DI1...DI6) < 5 V (state 0) > 11 V (state 1) Negative logic (sink) (DI1...DI6) > 16 V (state 0) < 10 V (state 1) Positive logic (source) (DI5, DI6) < 0.6 V (state 0) > 2.5 V (state 1) Positive logic (source) (STOA, STOB) < 5 V (state 0) > 11 V (state 1)

Analogue output type	Software-configurable voltage AO1, AO2: 0...10 V DC impedance 470 Ohm 10 bits Software-configurable current AO1, AO2: 0...20 mA 10 bits
Analogue output number	2
Sampling duration	2 ms +/- 0.5 ms (DI1...DI4) - discrete input 5 ms +/- 1 ms (DI5, DI6) - discrete input 5 ms +/- 0.1 ms (AI1, AI2, AI3) - analog input 10 ms +/- 1 ms (AO1) - analog output
Accuracy	+/- 0.6 % AI1, AI2, AI3 for a temperature variation 60 °C analog input +/- 1 % AO1, AO2 for a temperature variation 60 °C analog output
Linearity error	AI1, AI2, AI3: +/- 0.15 % of maximum value For analog input AO1, AO2: +/- 0.2 % For analog output
Relay output number	3
Relay output type	Configurable relay logic R1: fault relay NO/NC electrical durability 100000 cycles Configurable relay logic R2: sequence relay NO electrical durability 100000 cycles Configurable relay logic R3: sequence relay NO electrical durability 100000 cycles
Refresh time	Relay output (R1, R2, R3): 5 ms (+/- 0.5 ms)
Maximum switching current	Relay output R1, R2, R3 on resistive load 1: 3 A at 250 V AC Relay output R1, R2, R3 on resistive load 1: 3 A at 30 V DC Relay output R1, R2, R3 on inductive load 0.4 and L/R = 7 ms: 2 A at 250 V AC Relay output R1, R2, R3 on inductive load 0.4 and L/R = 7 ms: 2 A at 30 V DC
Minimum switching current	Relay output R1, R2, R3: 5 mA at 24 V DC
Isolation	Between power and control terminals
Number of power modules	1

## Environment

Insulation resistance	> 1 mOhm 500 V DC for 1 minute to earth
Noise level	69 dB conforming to 86/188/EEC
Power dissipation in W	Forced convection: 2980 W 2.5 kHz
THDI	<= 48 % full load conforming to IEC 61000-3-12
Electromagnetic compatibility	Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3 Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6
Pollution degree	2 conforming to EN/IEC 61800-5-1
Vibration resistance	1.5 mm peak to peak (f= 2...13 Hz) conforming to IEC 60068-2-6 0.5 gn (f= 13...200 Hz) conforming to IEC 60068-2-6
Shock resistance	7 gn For 11 ms conforming to IEC 60068-2-27
Relative humidity	5...95 % without condensation conforming to IEC 60068-2-3
Ambient air temperature for operation	40...50 °C (with derating factor) -10...40 °C (without derating)
Ambient air temperature for storage	-40...70 °C
Operating altitude	1000...4800 m with current derating 1 % per 100 m <= 1000 m without derating
Environmental characteristic	Chemical pollution resistance class 3C3 conforming to EN/IEC 60721-3-3 Dust pollution resistance class 3S3 conforming to EN/IEC 60721-3-3
Standards	IEC 13849-1 EN/IEC 61800-5-1 IEC 61508 EN/IEC 61800-3 IEC 60721-3 IEC 61000-3-12
Product certifications	REACH TÜV
Marking	CE

Product Life Status : **Commercialised**