Product data sheet
Characteristics

HOM2024L125TCI
Load center interior, Homeline, 1 phase, 20 spaces, 24 circuits, 125A convertible main lugs, NEMA1, gnd bar

Commercial status
This Product is Obsolete : JAN 23, 2021

⚠ This Product is Obsolete

Main

Product or Component Type	Load Center Interior
Range of Product	Homeline
Load center type	Convertible Mains (lugs)
Line Rated Current	125 A
Number of spaces	20
Short-circuit current	10 KA
Number of circuits	24
Number of tandem circuit breakers	4
Phase	1 phase
[Ue] rated operational voltage	120/240 V AC

Complementary

AWG gauge	AWG 6...AWG 2/0 copper
Device Composition	Grounding bar (factory installed)
Wiring configuration	3-wire
Material	Tin plated aluminium: busbar

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL listed file E-6294

Ordering and shipping details

Category	00185-MISC. HOM LOAD CENTERS
Discount Schedule	DE3C
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	10.00 Lb(US) (4.536 kg)

Contractual warranty

Warranty	Lifetime

Product Life Status : End of commerc. - Block

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.