



## Main

Range	TeSys
Product name	TeSys B
Product or component type	Contactor
Device short name	LC1BL
Contactor application	Motor-heating-lighting
Utilisation category	AC-1 AC-3
Control circuit type	DC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO
[Ie] rated operational current	800 A (at <40 °C) AC AC-1 for power circuit 750 A (at <55 °C) AC AC-3 for power circuit
Motor power kW	220 kW at 220...230 V AC 50/60 Hz 400 kW at 380...400 V AC 50/60 Hz 425 kW at 415 V AC 50/60 Hz 450 kW at 440 V AC 50/60 Hz 500 kW at 500 V AC 50/60 Hz 530 kW at 1000 V AC 50/60 Hz 560 kW at 660...690 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 3 NC
[Uc] control circuit voltage	220 V DC

## Complementary

Control circuit voltage limits	Drop-out: 0.3...0.5 Uc Operational: 0.85...1.1 Uc
[Ui] rated insulation voltage	1000 V - for power circuit conforming to IEC 60158-1 1000 V - for power circuit conforming to IEC 60947-4 1500 V - for power circuit conforming to VDE 0110 group C
Mounting mode	Fixed
Mounting support	Notched mounting rails Bar support bracket
Tightening torque	Power circuit: 21 N.m - on bars
[Ue] rated operational voltage	Power circuit: ≤ 1000 V AC 50/60 Hz
[Ith] conventional free air thermal current	800 A (at 40 °C) for power circuit
Rms rated making capacity	10000 A at 1000 V AC for power circuit conforming to IEC 60158-1 10000 A at 1000 V AC for power circuit conforming to IEC 60947-4

Rated breaking capacity	10000 A at 440 V for power circuit conforming to IEC 60158-1 10000 A at 440 V for power circuit conforming to IEC 60947-4 4000 A at 1000 V for power circuit conforming to IEC 60158-1 4000 A at 1000 V for power circuit conforming to IEC 60947-4 8000 A at 660...690 V for power circuit conforming to IEC 60158-1 8000 A at 660...690 V for power circuit conforming to IEC 60947-4 9000 A at 500 V for power circuit conforming to IEC 60158-1 9000 A at 500 V for power circuit conforming to IEC 60947-4
Associated fuse rating	1000 A gI at <= 440 V for power circuit 800 A aM at <= 440 V for power circuit 800 A gI at <= 440 V for power circuit
Average impedance	0.18 MOhm - Ith 800 A 50 Hz for power circuit
Power dissipation per pole	115 W AC-1 - Ith 800 A 88 W AC-3 - Ith 800 A
Inrush power in W	1100 W
Hold-in power consumption in W	31 W
Operating time	100...150 ms closing 20...40 ms opening
Mechanical durability	1200000 Cycles
Maximum operating rate	120 Cyc/H 55 °C
Height	486 Mm
Width	570 Mm
Depth	475 Mm
Net weight	58 Kg

## Environment

Standards	IEC 60158-1 IEC 60947-4 BS 5424 NF C 63-110 VDE 0660
Product certifications	RINA BV CSA
Protective treatment	TC TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**