

# Product data sheet

## Characteristics

# LV839264

## MN undervoltage release - 380/480 V AC/DC - for MTZ drawout

### Main

Device short name	MN
Product or component type	Voltage release
Device application	Safety
Range compatibility	Masterpact MTZ2 circuit-breaker Masterpact MTZ3 circuit-breaker Masterpact MTZ1 circuit-breaker
Voltage release type	Undervoltage release

### Complementary

Control type	Communicating Standard
Signalling function	Coil powered Error MN open
[Uc] control circuit voltage	380/480 V DC 380/480 V AC 50/60 Hz
Threshold tripping voltage	0.35...0.7 Un - during on opening time 0.85 Un - during on closing time
Supply holding power	4.5 VA 4.5 W
Mounting mode	Drawout
Response time	40 ms +/- 5 % for Masterpact MTZ1 90 ms +/- 5 % for Masterpact MTZ2 90 ms +/- 5 % for Masterpact MTZ3

Product Life Status : **Commercialised**

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.