



## Main

Range	Unica
Device application	Control
Product or component type	Switch
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Switch function	2-way
Switch application	Roller blind
Rated current	10 A at 250 V AC 50/60 Hz
Actuator	Push-button
Number of modules	2 modules
Fixing mode	Long claws
Cover plate colour tint	Aluminium

## Complementary

Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[I <sub>u</sub> ] rated interrupted current	2.5 A for motor
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screwless terminals
Cable cross section	2.5 Mm <sup>2</sup> flexible cable 2.5 Mm <sup>2</sup> rigid cable
Minimum load breaking capacity	200 operations 1.25 I <sub>n</sub> and 1.1 I <sub>u</sub> , cos phi = 0.3
Electrical durability	40000 Cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V
Material	ABS (acrylonitrile butadiene-styrene): mechanism cover Zamak: fixing frame
Standards	LV directive EMC directive EN 60669-1
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
Embedding depth	22 Mm
Depth	34 Mm
Width	70.9 Mm

Height	70.9 Mm
Net weight	0.0771 Kg

### Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Bleach Liquid soap UV resistant Oil Ammonia Petrol Window-cleaning fluid Alcohol Acetone
Environmental health and issues	Halogen free

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**