Product data sheet
Characteristics

MGU50.207.30Z
Unica Top/Class - pushbutton switch - 10 A, 250 VAC - 2 m - aluminium

⚠ End of Commercialisation

Commercial status
End of Commercialisation : JUN 15, 2023

Main

Range	Unica
Device application	Control
Product or component type	Shutter control
Aesthetic name	Unica Top - Unica Class
Device presentation	Mechanism
Rated current	10 A
[Ue] rated operational voltage	250 V
Network type	AC
Network frequency	50/60 Hz
Fixing mode	Long claws
Colour tint	Aluminium

Complementary

Device mounting	Flush
Number of modules	2 modules
Technology type	Electromechanical
Actuator	Push-button
Number of rocker	2
Switch function	1-pole 2-way
Switch application	Roller blind
Contacts type and composition	1 C/O
Mechanical interlocking	Interlock between up/down
[Iu] rated interrupted current	2.5 A for motor
Opening distance	> 3 mm
Marking	Down UP
Connections - terminals	Screwless terminals
Cable cross section	2.5 Mm² flexible cable 2.5 Mm² rigid cable
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Electrical durability	40000 Cycles, cos phi = 0.6
Insulation resistance	> 5 MOhm at 500 V
Dielectric strength	2000 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Material	ABS (acrylonitrile butadiene-styrene): mechanism cover Zamak: fixing frame
Standards	LV directive EMC directive EN 60669-1
Ambient air temperature for operation	25…35 °C
Ambient air temperature for storage	0…50 °C
Embedding depth	22 Mm
Depth	34 Mm
Width	70.9 Mm
Height	70.9 Mm
Net weight	0.0771 Kg

Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Bleach Liquid soap UV resistant Oil Petrol Window-cleaning fluid Alcohol Acetone

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4 Cm
Package 1 Width	7.5 Cm
Package 1 Length	7.5 Cm
Package 1 Weight	77 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	8.5 Cm
Package 2 Width	20 Cm
Package 2 Length	22.5 Cm
Package 2 Weight	869 G
Unit Type of Package 3	S03
Number of Units in Package 3	50
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	4.746 Kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months

Product Life Status : End of commerc. - Block