Product data sheet
Characteristics

NU543118
New Unica - 3 RCA connectors (video & Audio) - with fixig frame - 2 module - whi

Commercial status
End of Commercialisation : APR 15, 2024

⚠ End of Commercialisation

Main

Range	New Unica
Product or component type	Audio/Video socket
Connector type	RCA
Electrical circuit type	Audio/Video
Device presentation	Mechanism with fixing frame
Colour tint	White (RAL 9003)
Type of packing	Flow-pack

Complementary

Socket number	3
Fixing mode	Screws or claws
Number of modules	2 modules
Surface finish	Glossy
Quantity per set	Set of 10
Connections - terminals	Screw terminals
Clamping connection capacity	<= 1.5 mm² for flexible cable(s) <= 1.5 mm² for rigid cable(s)
Wire stripping length	8 Mm
Material	Thermoplastic ABS-UV stabilised: centre plate PC (polycarbonate) GF10 FR: casing Zamak: fixing frame
Height	74.5 Mm
Width	74.5 Mm
Depth	28 Mm
Embedding depth	19 Mm
Net weight	0.07 Kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient air temperature for storage	-5…50 °C
Ambient air temperature for operation	5…45 °C
IP degree of protection	IP2XC
IK degree of protection	IK02

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.5 Cm
Package 1 Width	7.5 Cm
Package 1 Length	2.8 Cm
Package 1 Weight	71 G
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	1134 G
Unit Type of Package 3	P06
Number of Units in Package 3	160
Package 3 Height	77 Cm
Package 3 Width	80 Cm
Package 3 Length	60 Cm
Package 3 Weight	26644 G

Offer Sustainability

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product Life Status : End of commercialisation