Product data sheet
Characteristics

SSP06EMA20
Surge protection device, Surgelogic, 200kA, 240 VAC delta, 3 phase, 3 wire, NEMA 1

Commercial status
This Product is Obsolete : MAY 11, 2021

⚠ This Product is Obsolete

Main

Product or Component Type	Surge protection device
Range of Product	Surgelogic
Device short name	EMA

Complementary

[Ue] rated operational voltage	240 V delta AC
[Uc] maximum continuous operating voltage	300 V
Short-circuit protection	200 KA
Surge current	200 KA
Nominal Discharge Current	20 KA
Phase	3 phase
Wiring configuration	3-wire
Connections - terminals	Lugs AWG 10...AWG 2 copper 35.40 lbf.in (4 N.m)
Local signalling	Status LED green per phase normal operation Status LED red per phase fault
Provided equipment	Alarm enable/disable switch Surge counter Dry contacts
Cable length	19.02 In (483 mm)
Device mounting	Surface
Height	11.10 In (282 mm)
Width	9.98 In (253.5 mm)
Depth	5.31 In (135 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient Air Temperature for Operation	149 °F (65 °C)
NEMA Degree of Protection	NEMA 1
Enclosure material	Gray painted sheet steel
Standards	CSA C22.2 No 8 UL 1449:ed. 4 UL 1283:ed. 5

Ordering and shipping details

Category	08464-SURGE PROTECTION EMA
Discount Schedule	DE1B
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	20.50 Lb(US) (9.299 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Product Life Status : End of commerc. - Block