



### Main

Range of product	Harmony XB4
Product or component type	Contact block
Device short name	ZBE
Sale per indivisible quantity	1
Contacts type and composition	1 NC
Contact operation	Standard
Contact block type	Single
Contacts usage	Gas protected contact
Connections - terminals	Screw clamp terminals, 2 x 1.5 mm <sup>2</sup> without cable end Screw clamp terminals, 1 x 2.5 mm <sup>2</sup> with cable end

### Complementary

CAD overall width	38 Mm
CAD overall height	10 Mm
CAD overall depth	42.4 Mm
Net weight	0.019 Kg
Marking	Ex db eb IIC Gb
Positive opening	With
Operating travel	1.688 Mm (engagement point) 3.271 Mm (changing state point) 4.424 Mm (total travel)
Operating force	2.873 N
Mechanical durability	1000000 Cycles
Tightening torque	0.8...1.2 N.M conforming to EN 60947-1
[I <sub>th</sub> ] conventional free air thermal current	10 A conforming to EN/IEC 60947-5-1
[U <sub>i</sub> ] rated insulation voltage	415 V
[I <sub>e</sub> ] rated operational current	1.9 A at 380 V, AC, A600 conforming to EN/IEC 60947-5-1 3 A at 240 V, AC, A600 conforming to EN/IEC 60947-5-1 6 A at 120 V, AC, A600 conforming to EN/IEC 60947-5-1 0.27 A at 250 V, DC, Q300 conforming to EN/IEC 60947-5-1 0.55 A at 125 V, DC, Q300 conforming to EN/IEC 60947-5-1 2.87 A at 24 V, DC, Q300 conforming to EN/IEC 60947-5-1
Mounting of block	Front mounting
Condition of use	Standard
Compatibility code	ZBE

## Environment

Protective treatment	TH
Ambient air temperature for storage	-50...70 °C
Ambient air temperature for operation	-50...75 °C
Standards	UL 60079-31 UL 60079-0 UL 60079-1 ANSI/ISA 12.12.01 EN/IEC 60079-0 EN/IEC 60079-31 CSA C22.2 No 213 EN/IEC 60079-1 EN/IEC 60079-7
Product certifications	CULus
Environmental characteristic	Hazardous location class I division 2

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Product Life Status : **Commercialised**