

# Product Environmental Profile

## Ethernet Drive Control Unit






## General information

<b>Representative product</b>	Ethernet Drive Control Unit -LXM32iETH
<b>Description of the range</b>	<p>The main purpose of the drive control unit of the Lexium 32i is to drive and control the integrated synchronous electric motor and make the link with the command coming from the fieldbus, the inputs/outputs or the Safe Torque Off.</p> <p>Available for three fieldbusses the drive control unit of the Lexium 32i can communicate with CANopen/CANmotion, EtherCAT and PROFINET.</p> <p>The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.</p>
<b>Functional unit</b>	To drive and control the integrated synchronous electric motor for 10 years 100% of the time



## Constituent materials

**Reference product mass** 644,5 g including the product, its packaging and additional elements and accessories



## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>



## Additional environmental information

**The Ethernet Drive Control Unit presents the following relevant environmental aspects**


<b>Manufacturing</b>	Manufactured at a Schneider Electric production site ISO14001 certified
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 143,4 g, consisting of cardboard (72,9%), polyurethane (PU) foam (21,8%) and paper (5,3%)
<b>Use</b>	The product does not require special maintenance operations.
<b>End of life</b>	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials  This product contains electronic card (79,70 g) that should be separated from the stream of waste so as to optimize end-of-life treatment.  The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website  <a href="http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page">http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</a>  Recyclability potential: <b>72%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

## Environmental impacts

<b>Reference life time</b>	10 years			
<b>Product category</b>	Active products			
<b>Installation elements</b>	No special components needed			
<b>Use scenario</b>	The product is in active mode 100% of the time with a power use of 5,5W for 10 years.			
<b>Geographical representativeness</b>	Europe			
<b>Technological representativeness</b>	LXM32iCAN, LXM32iECT, LXM32iETH			
<b>Energy model used</b>	<b>Manufacturing</b>	<b>Installation</b>	<b>Use</b>	<b>End of life</b>
	Energy model used: Indonesia	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity Mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		Ethernet Drive Control Unit - LXM32iETH					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	6,82E-03	6,81E-03	0*	0*	1,30E-05	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	2,20E+00	4,34E-02	3,80E-04	0*	2,15E+00	0*
Contribution to water eutrophication	kg PO <sub>4</sub> <sup>3-</sup> eq	8,68E-02	6,00E-03	8,74E-05	1,13E-05	8,06E-02	6,41E-05
Contribution to global warming	kg CO <sub>2</sub> eq	2,98E+02	1,32E+01	8,32E-02	0*	2,84E+02	1,60E-01
Contribution to ozone layer depletion	kg CFC11 eq	7,10E-05	1,86E-06	0*	0*	6,91E-05	0*
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	1,05E-01	3,16E-03	2,71E-05	0*	1,02E-01	1,74E-05
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m <sup>3</sup>	8,52E-01	1,10E-01	0*	0*	7,42E-01	1,04E-04
Total Primary Energy	MJ	5,96E+03	1,99E+02	1,18E+00	0*	5,76E+03	9,39E-01





Optional indicators		Ethernet Drive Control Unit - LXM32iETH					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	3,09E+03	1,54E+02	1,17E+00	0*	2,93E+03	7,79E-01
Contribution to air pollution	m³	1,35E+04	1,28E+03	3,54E+00	1,54E+00	1,22E+04	6,02E+00
Contribution to water pollution	m³	1,36E+04	1,62E+03	1,37E+01	1,75E+00	1,19E+04	9,26E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	3,39E-01	3,39E-01	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	4,18E+02	5,99E+00	0*	0*	4,12E+02	0*
Total use of non-renewable primary energy resources	MJ	5,55E+03	1,93E+02	1,17E+00	0*	5,35E+03	9,38E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	4,18E+02	5,99E+00	0*	0*	4,12E+02	0*
Use of renewable primary energy resources used as raw material	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	5,54E+03	1,90E+02	1,17E+00	0*	5,35E+03	9,38E-01
Use of non renewable primary energy resources used as raw material	MJ	2,79E+00	2,79E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0,00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1,23E+01	1,13E+01	0*	2,87E-01	0*	7,21E-01
Non hazardous waste disposed	kg	1,07E+03	8,78E+00	0*	0*	1,06E+03	0*
Radioactive waste disposed	kg	8,73E-01	5,90E-03	0*	0*	8,67E-01	0*
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	4,14E-01	5,12E-02	0*	9,00E-05	0*	3,63E-01
Components for reuse	kg	0,00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	3,69E-02	3,59E-04	0*	1,56E-03	0*	3,49E-02
Exported Energy	MJ	0,00E+00	0*	0*	0*	0*	0*

\* represents less than 0.01% of the total life cycle of the reference flow


Life cycle assessment performed with EIME version EIME v5.5, database version 2015-04.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

Depending on the impact analysis, the environmental indicators (without mineral resources depletion) of other products in this family may be proportional extrapolated by energy consumption values". For mineral resources depletion, impact may be proportional extrapolated by mass of the product.

*Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.*

<i>Registration N°</i>	SCHN-00126-V01.01-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Verifier accreditation N°</i>	VH08	<i>Information and reference documents</i>	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
<i>Date of issue</i>	10/2016	<i>Validity period</i>	5 years
<i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2010</i>			
<i>Internal</i>	<i>External X</i>		
<i>The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)</i>			
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »</i>			

Schneider Electric Industries SAS

Schneider Electric Country Customer Care Center

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)

Published by Schneider Electric

SCHN-00126-V01.01-EN

© 2016 - Schneider Electric – All rights reserved

10/2016