Product Environmental Profile

1 GANG DOUBLE POLE SW MODULE BLUE LED









Functional unit


General information

Representative product 1 GANG DOUBLE POLE SW MODULE BLUE LED - U201SPM/DP B00

Description of the product Establish and cut off the supply of an electrical circuit.

Establish, support and interrupt for 20 years rated currents in normal conditions of circuit characterized by the 20A, including any conditions specified for overload in operation characterized by the 23A, for the operating 250V and a current for shortcircuit 5KA for a specified time.

Constituent materials



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page


(I) Additional environmental information

The 1 GANG DOUBLE POLE SW MODULE BLUE LED presents the following relevent environmental aspects							
Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified						
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive						
	Packaging weight is 17 g, consisting of cardboard (85.3%), PE film (8.8%), paper (5.9%)						
Installation	Reference U201SPM/DP B00 does not require any installation operations. Packaging waste is considered in installation.						
Use	The product does not require special maintenance operations.						
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials						
	No special end-of-life treatment required. According to countries' practices this product can enter the usual end-of-life treatment process.						
	Based on "ECO'DEEE recyclability and recoverability calculation method" Recyclability potential: 46% (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).						

Environmental impacts

Reference life time	20 years						
Product category	Switches						
Installation elements	No special installation components need during installation phase, but transport of packaging to disposal, and disposal of packaging accounted for during installation.						
Use scenario	Load rate: 50% of In Use time rate: 30% of RLT						
Geographical representativeness	China						
Technological representativeness	Establish and cut off the supply of an electrical circuit.						
	Manufacturing	Installation	Use	End of life			
Energy model used	Energy model used: Malaysia	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN	Electricity mix; AC; consumption mix, at consumer; 220V; CN			

Compulsory indicators		1 GANG DOUBLE POLE SW MODULE BLUE LED - U201SPM/DP B00					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	1.41E-04	1.41E-04	0*	0*	6.71E-08	0*
Contribution to the soil and water acidification	kg SO ₂ eq	1.97E-02	3.00E-03	7.13E-05	4.08E-06	1.66E-02	3.21E-05
Contribution to water eutrophication	kg PO ₄ ³- eq	4.92E-03	5.20E-04	1.64E-05	1.43E-06	4.37E-03	9.20E-06
Contribution to global warming	kg CO ₂ eq	1.67E+01	1.39E+00	1.56E-02	0*	1.53E+01	1.81E-02
Contribution to ozone layer depletion	kg CFC11 eq	2.64E-07	1.42E-07	3.16E-11	0*	1.22E-07	7.79E-10
Contribution to photochemical oxidation	$kg C_2H_4 eq$	2.26E-03	2.94E-04	5.09E-06	3.06E-07	1.96E-03	3.32E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	2.67E-02	9.60E-03	0*	0*	1.71E-02	1.50E-05
Total Primary Energy	MJ	2.69E+02	1.85E+01	2.21E-01	0*	2.50E+02	1.55E-01



Optional indicators	1 GANG DOUBLE POLE SW MODULE BLUE LED - U201SPM/DP B00						
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	2.56E+02	1.62E+01	2.19E-01	0*	2.39E+02	1.42E-01
Contribution to air pollution	m³	1.87E+03	2.85E+02	6.64E-01	0*	1.59E+03	1.12E+00
Contribution to water pollution	m³	1.09E+03	3.28E+02	2.57E+00	1.45E-01	7.60E+02	1.39E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	2.88E-03	2.88E-03	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1.36E+01	8.08E-01	0*	0*	1.28E+01	0*
Total use of non-renewable primary energy resources	MJ	2.55E+02	1.77E+01	2.20E-01	0*	2.37E+02	1.55E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.33E+01	5.03E-01	0*	0*	1.28E+01	0*
Use of renewable primary energy resources used as raw material	MJ	3.05E-01	3.05E-01	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.54E+02	1.62E+01	2.20E-01	0*	2.37E+02	1.55E-01
Use of non renewable primary energy resources used as raw material	MJ	1.55E+00	1.55E+00	0*	0*	0*	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	6.46E+00	5.80E+00	0*	0*	4.93E-01	1.62E-01
Non hazardous waste disposed	kg	3.41E+00	6.36E-01	5.55E-04	1.31E-03	2.77E+00	4.73E-04
Radioactive waste disposed	kg	5.09E-04	4.16E-04	3.95E-07	6.38E-08	9.14E-05	7.64E-07
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	7.57E-02	1.14E-02	0*	1.59E-02	0*	4.85E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	2.67E-03	0*	0*	0*	0*	2.67E-03
Exported Energy	MJ	4.90E-05	4.61E-06	0*	4.44E-05	0*	0*

^{*} represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.7.0.2, database version 2016-11 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number: SCHN-00358-V01.01-EN

Verifier accreditation N° VH08

Date of issue

06/2018

Drafting rules

PCR-ed3-EN-2015 04 02

Supplemented by
PSR-0005-ed2-EN-2016 03 29

Information and reference documents
Validity period

5 years

Independent verification of the declaration and data, in compliance with ISO 14025: 2010

Internal External X

The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)

PEP are compliant with XP C08-100-1 :2014

The elements of the present PEP cannot be compared with elements from another program.

Document in compliance with ISO 14025: 2010 « Environmental labels and declarations. Type III environmental

declarations »



Schneider Electric Industries SAS
Country Customer Care Center
http://www.schneider-electric.com/contact
35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex RCS Nanterre 954 503 439 Capital social 896 313 776 €

www.schneider-electric.com Published by Schneider Electric

SCHN-00358-V01.01-EN © 2017 - Schneider Electric – All rights reserved

06/2018