



### Main

For System M.

With integrated bus coupling unit.

Push-button with 8 operating buttons, operating and status display and labelling field. The operating display can also be used as an orientation light.

The functions of each of the keys can be triggered using an IR remote control.

The push-button is pre-programmed for operation with a Merten IR remote control Distance. Many other IR remote controls (e.g. existing TV or CD player remote controls) can be taught into the push-buttons.

### Complementary

The device is connected to the bus line with a bus connecting terminal.

#### KNX software functions:

Switching, toggling, dimming (single/dual-surface), blind (single/dual-surface), pulse edges trigger 1-, 2-, 4- or 8-bit telegrams (distinction between short and long operation), pulse edges with 2-byte telegrams (distinction between short and long operation), 8-bit linear regulator, scene retrieval, scene saving, disable functions.

**Accessories:** Labelling sheets for multi-function push-button with IR receiver, art. no. MTN618419/20.

**Transmitter:** IR remote control Distance, art. no. MTN570222.

Contents: With protective hood for plaster. With bus connecting terminal.

Material : Thermoplastic classy matt

Colour: anthracite

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.