

Easergy MiCOM P746

Numerical Busbar Protection Relay

P746/EN MC/L72

Software Version	C3
Hardware Suffix	M
IEC61850	Edition 1

Model Implementation Conformance Statement (MICS)

Note

The technical manual for this device gives instructions for its installation, commissioning, and operation. However, the manual cannot cover all conceivable circumstances or include detailed information on all topics. In the event of questions or specific problems, do not take any action without proper authorization. Contact the appropriate Schneider Electric technical sales office and request the necessary information.

Any agreements, commitments, and legal relationships and any obligations on the part of Schneider Electric including settlements of warranties, result solely from the applicable purchase contract, which is not affected by the contents of the technical manual.

This device **MUST NOT** be modified. If any modification is made without the express permission of Schneider Electric, it will invalidate the warranty, and may render the product unsafe.

Easergy MiCOM and the Schneider Electric logo and any alternative version thereof are trademarks and service marks of Schneider Electric.

All trade names or trademarks mentioned herein whether registered or not, are the property of their owners.

This manual is provided for informational use only and is subject to change without notice.

© 2016, Schneider Electric. All rights reserved.

MODEL IMPLEMENTATION
CONFORMANCE STATEMENT
(MICS)

Date (month/year):	10/2016
Products covered by this chapter:	This chapter covers the specific versions of the MiCOM products listed below. This includes only the following combinations of Software Version and Hardware Suffix.
Hardware suffix:	M
Software version:	C3
IEC61850 Edition:	1
Connection diagrams:	This includes a list of the Connection Diagrams for the Products covered by this document. 10P746xx (xx = 00 to 21)

CONTENTS

		Page-
1	Introduction	7
2	Objective	8
3	Logical Device Definitions	9
3.1	IEC61850 Logical Device Data Model	9
4	Logical Node definitions	16
4.1	Logical Node: GGIO_ALM_32	17
4.2	Logical Node: GGIO_ALM_96	18
4.3	Logical Node: GGIO_IND_10	20
4.4	Logical Node: GGIO_IND_18	20
4.5	Logical Node: GGIO_IND_32	21
4.6	Logical Node: GGIO_IND_32_CTRL	22
4.7	Logical Node: GGIO_IND_40	23
4.8	Logical Node: GGIO_IND_64	24
4.9	Logical Node: LLN0_PROT	26
4.10	Logical Node: LLN0_STANDARD	26
4.11	Logical Node: LLN0_SYSTEM	26
4.12	Logical Node: LPHD_STANDARD	27
4.13	Logical Node: MDIF_BBP	27
4.14	Logical Node: MDIF_CZ	27
4.15	Logical Node: MMXU_A_21	27
4.16	Logical Node: MMXU_A_7	28
4.17	Logical Node: MMXU_DERIVED_A_7	29
4.18	Logical Node: MMXU_FOURIER_7	29
4.19	Logical Node: MSQI_SEQ_7	29
4.20	Logical Node: PDIF_NEU	30
4.21	Logical Node: PTOC_NEU	30
4.22	Logical Node: PTRC_NO_SEG	30
4.23	Logical Node: RBRF_STANDARD	30
4.24	Logical Node: RDRE_BASIC	31
4.25	Logical Node: RFLO_PRIV_P747	31
5	Common Data Class Definitions	34
5.1	Common Data Class: ACD_NO_SEG	34
5.2	Common Data Class: ACT_NO_SEG	34
5.3	Common Data Class: CMV_MAG	35
5.4	Common Data Class: CMV_MAG_ANG_FLOAT	35
5.5	Common Data Class: CMV_MAG_FLOAT	36

5.6	Common Data Class: DPL_STANDARD	36
5.7	Common Data Class: INC_MOD	36
5.8	Common Data Class: INC_MOD_D_PRIV	37
5.9	Common Data Class: INS_BASIC	37
5.10	Common Data Class: INS_BEH	37
5.11	Common Data Class: INS_BEH_D_PRIV	38
5.12	Common Data Class: INS_D	38
5.13	Common Data Class: INS_D_NS	38
5.14	Common Data Class: INS_HEALTH	38
5.15	Common Data Class: LPL_LLNO	39
5.16	Common Data Class: LPL_LN	39
5.17	Common Data Class: MV_FLOAT_D	39
5.18	Common Data Class: MV_FLOAT_FAULT	40
5.19	Common Data Class: MV_FLOAT_ND	40
5.20	Common Data Class: SEQ_MAG	41
5.21	Common Data Class: SEQ_MAG_ND	41
5.22	Common Data Class: SPC_CONTROL	41
5.23	Common Data Class: SPS_D	42
5.24	Common Data Class: SPS_WD	42
5.25	Common Data Class: SPS_WD_NS	43
5.26	Common Data Class: WYE_SEG_ANG_NS	43
5.27	Common Data Class: WYE_SEG_ANONYMOUS	43
5.28	Common Data Class: WYE_SEG_D	43
5.29	Common Data Class: WYE_SEG_FAULT	44
<hr/>		
6	Common Data Attribute Type Definitions	45
6.1	Component: AnalogueValue_Float	45
6.2	Component: Originator	45
6.3	Component: RangeConfig_Deadband	45
6.4	Component: Unit	45
6.5	Component: Unit_Multiplier	46
6.6	Component: Vector_Magnitude_Float	46
6.7	Component: Vector_MagnitudeAngle_Float	46
<hr/>		
7	Enumerated Type Definitions	47
7.1	Enumerated Type: AddCause	47
7.2	Enumerated Type: Beh	47
7.3	Enumerated Type: Bypass	47
7.4	Enumerated Type: ctlModel	48
7.5	Enumerated Type: dir	48
7.6	Enumerated Type: Health	48
7.7	Enumerated Type: Mod	48
7.8	Enumerated Type: multiplier	48
7.9	Enumerated Type: orCategory	49

7.10	Enumerated Type: seqT	49
7.11	Enumerated Type: SIUnit	49
8	MMS Data-Type Conversions	52

Notes:

1 INTRODUCTION

This specification is the Model Implementation Conformance Statement (MICS) and presents the top-level IEC61850 data model that has been implemented. The definitions of all used Logical Nodes and their associated Common Data Classes, components and associated enumerated values are also included for completeness.

The reader is expected to be conversant with the terminology presented within the IEC61850 part 7 series of specifications.

2 OBJECTIVE

This document is applicable for P746 with the firmware C3A. The MICS is conformant to the devices associated ICD (Substation Configuration Language) file: P746_____C3A.ICD, version V2.1, according to part 6 and part 7 of the IEC61850 standards.

The layouts of the presented tables within this document are conformant to the part 6 and 7 series of the IEC61850 standard specifications with the following exceptions:

- The "Trigger Options" field is not presented
- The "M/O" field is not present as the definitions are as deployed within the model
- An additional column "X" is used to signify MiCOM custom attributes

3 LOGICAL DEVICE DEFINITIONS

The MiCOM relay implements an IEC61850 server that can contain one or more Logical Devices. Each Logical Device contains a data model built from instances of specific Logical Nodes and must consist of at least an instance of the LPHD Logical Node (which is responsible for providing physical device information) and an instance of the LLN0 Logical Node (for addressing common issues across the Logical Device).

The IEC61850 data model is contained within the Logical Devices detailed in the table below. All MiCOM devices will name the supported Logical Devices consistently to ensure that data model variables with the same purpose will have the same name within each MiCOM server.

Logical Device	Comment/Usage
Measurements	P747 Measurements
Protection	P747 Protection
Records	P747 Records
System	P747 System

3.1 IEC61850 Logical Device Data Model

The IEC61850 Logical Device top-level data model consists of instances of Logical Nodes. The data model name for a Logical Node instance is constructed from an optional prefix (known as the wrapper), the Logical Node name, and an instance ID (or suffix).

The presented data model is in an alphabetically sorted order, rather than a logical order, because this is the natural order of the data when presented by a native MMS browser. (Higher level browsers can of course impart any ordering that they desire).

LD	LN Instance	LN Type	Description
Measurements			
	LLN0	LLN0_STANDARD	Measurements Logical Device
	LPHD1	LPHD_STANDARD	Physical Device Information
	PriBbpMDIF1	MDIF_BBP	Primary Busbar Differential measurements for base values - zone 1
	PriBbpMDIF2	MDIF_BBP	Primary Busbar differential measurements for bias values - zone 1
	PriBbpMDIF3	MDIF_BBP	Primary Busbar Differential measurements for base values - zone 2
	PriBbpMDIF4	MDIF_BBP	Primary Busbar Differential measurements for bias values - zone 2
	PriBbpMDIF5	MDIF_BBP	Primary Busbar Differential measurements for base values - zone 3
	PriBbpMDIF6	MDIF_BBP	Primary Busbar Differential measurements for bias values - zone 3
	PriBbpMDIF7	MDIF_BBP	Primary Busbar Differential measurements for base values - zone 4

LD	LN Instance	LN Type	Description
	PriBbpMDIF8	MDIF_BBP	Primary Busbar Differential measurements for bias values - zone 4
	PriCznMDIF1	MDIF_CZ	Primary Check zone differential measurements for base values-fundamentals
	PriCznMDIF2	MDIF_CZ	Primary Check zone differential measurements for bias values-fundamentals
	PriDvdMMXU1	MMXU_A_7	Primary Derived one-box measurements for P747
	PriFouMMXU1	MMXU_FOURIER_7	Primary Fourier based measurements for P747
	PriMsiMMXU1	MMXU_DERIVED_A_7	Primary measured values for One-box measurements For P747
	PriMsiMMXU2	MMXU_A_21	Primary measured values for Three-box measurements For P747
	PriSeqMSQI1	MSQI_SEQ_7	Primary one-box sequence measurements for P747
	SecBbpMDIF1	MDIF_BBP	Secondary Busbar Differential measurements for base values - zone 1
	SecBbpMDIF2	MDIF_BBP	Secondary Busbar differential measurements for bias values - zone 1
	SecBbpMDIF3	MDIF_BBP	Secondary Busbar differential measurements for base values - zone 2
	SecBbpMDIF4	MDIF_BBP	Secondary Busbar differential measurements for bias values - zone 2
	SecBbpMDIF5	MDIF_BBP	Secondary Busbar Differential measurements for base values - zone 3
	SecBbpMDIF6	MDIF_BBP	Secondary Busbar Differential measurements for bias values - zone 3
	SecBbpMDIF7	MDIF_BBP	Secondary Busbar Differential measurements for base values - zone 4
	SecBbpMDIF8	MDIF_BBP	Secondary Busbar Differential measurements for bias values - zone 4
	SecCznMDIF1	MDIF_CZ	Secondary Check zone differential measurements for base value - fundamentals
	SecCznMDIF2	MDIF_CZ	Secondary Check zone differential measurements for bias value - fundamentals

LD	LN Instance	LN Type	Description
	SecDvdMMXU1	MMXU_A_7	Secondary Derived one-box measurements for P747
	SecFouMMXU1	MMXU_FOURIER_7	Secondary Fourier based measurements For P747
	SecMsiMMXU1	MMXU_DERIVED_A_7	Secondary measured values for One-box measurements for P747
	SecMsiMMXU2	MMXU_A_21	Secondary measured values for Three-box measurements for P747
	SecSeqMSQI1	MSQI_SEQ_7	Secondary one-box sequence measurements for P747
Protection			
	BbpT01PDIF1	PDIF_NEU	Busbar Differential - T1
	BbpT02PDIF1	PDIF_NEU	Busbar Differential - T2
	BbpT03PDIF1	PDIF_NEU	Busbar Differential - T3
	BbpT04PDIF1	PDIF_NEU	Busbar Differential - T4
	BbpT05PDIF1	PDIF_NEU	Busbar Differential - T5
	BbpT06PDIF1	PDIF_NEU	Busbar Differential - T6
	BbpT07PDIF1	PDIF_NEU	Busbar Differential - T7
	BbpT08PDIF1	PDIF_NEU	Busbar Differential - T8
	BbpT09PDIF1	PDIF_NEU	Busbar Differential - T9
	BbpT10PDIF1	PDIF_NEU	Busbar Differential - T10
	BbpT11PDIF1	PDIF_NEU	Busbar Differential - T11
	BbpT12PDIF1	PDIF_NEU	Busbar Differential - T12
	BbpT13PDIF1	PDIF_NEU	Busbar Differential - T13
	BbpT14PDIF1	PDIF_NEU	Busbar Differential - T14
	BbpT15PDIF1	PDIF_NEU	Busbar Differential - T15
	BbpT16PDIF1	PDIF_NEU	Busbar Differential - T16
	BbpT17PDIF1	PDIF_NEU	Busbar Differential - T17
	BbpT18PDIF1	PDIF_NEU	Busbar Differential - T18
	BbpT19PDIF1	PDIF_NEU	Busbar Differential - T19
	BbpT20PDIF1	PDIF_NEU	Busbar Differential - T20
	BbpT21PDIF1	PDIF_NEU	Busbar Differential - T21
	BbpZonPDIF1	PDIF_NEU	Dead zone differential protections - zone 1
	BbpZonPDIF2	PDIF_NEU	Dead zone differential protections - zone 2
	BbpZonPDIF3	PDIF_NEU	Dead zone differential protections - zone 3
	BbpZonPDIF4	PDIF_NEU	Dead zone differential protections - zone 4
	CbfT01RBRF1	RBRF_STANDARD	CB Fail - T1
	CbfT02RBRF1	RBRF_STANDARD	CB Fail - T2
	CbfT03RBRF1	RBRF_STANDARD	CB Fail - T3
	CbfT04RBRF1	RBRF_STANDARD	CB Fail - T4

LD	LN Instance	LN Type	Description
	CbfT05RBRF1	RBRF_STANDARD	CB Fail - T5
	CbfT06RBRF1	RBRF_STANDARD	CB Fail - T6
	CbfT07RBRF1	RBRF_STANDARD	CB Fail - T7
	CbfT08RBRF1	RBRF_STANDARD	CB Fail - T8
	CbfT09RBRF1	RBRF_STANDARD	CB Fail - T9
	CbfT10RBRF1	RBRF_STANDARD	CB Fail - T10
	CbfT11RBRF1	RBRF_STANDARD	CB Fail - T11
	CbfT12RBRF1	RBRF_STANDARD	CB Fail - T12
	CbfT13RBRF1	RBRF_STANDARD	CB Fail - T13
	CbfT14RBRF1	RBRF_STANDARD	CB Fail - T14
	CbfT15RBRF1	RBRF_STANDARD	CB Fail - T15
	CbfT16RBRF1	RBRF_STANDARD	CB Fail - T16
	CbfT17RBRF1	RBRF_STANDARD	CB Fail - T17
	CbfT18RBRF1	RBRF_STANDARD	CB Fail - T18
	CbfT19RBRF1	RBRF_STANDARD	CB Fail - T19
	CbfT20RBRF1	RBRF_STANDARD	CB Fail - T20
	CbfT21RBRF1	RBRF_STANDARD	CB Fail - T21
	CznPDIF1	PDIF_NEU	Check zone differential protection
	DznT01PTOC1	PTOC_NEU	Deadzone Overcurrent - T1 - Stage 1
	DznT02PTOC1	PTOC_NEU	Deadzone Overcurrent - T2 - Stage 1
	DznT03PTOC1	PTOC_NEU	Deadzone Overcurrent - T3 - Stage 1
	DznT04PTOC1	PTOC_NEU	Deadzone Overcurrent - T4 - Stage 1
	DznT05PTOC1	PTOC_NEU	Deadzone Overcurrent - T5 - Stage 1
	DznT06PTOC1	PTOC_NEU	Deadzone Overcurrent - T6 - Stage 1
	DznT07PTOC1	PTOC_NEU	Deadzone Overcurrent - T7 - Stage 1
	DznT08PTOC1	PTOC_NEU	Deadzone Overcurrent - T8 - Stage 1
	DznT09PTOC1	PTOC_NEU	Deadzone Overcurrent - T9 - Stage 1
	DznT10PTOC1	PTOC_NEU	Deadzone Overcurrent - T10 - Stage 1
	DznT11PTOC1	PTOC_NEU	Deadzone Overcurrent - T11 - Stage 1
	DznT12PTOC1	PTOC_NEU	Deadzone Overcurrent - T12 - Stage 1
	DznT13PTOC1	PTOC_NEU	Deadzone Overcurrent - T13 - Stage 1
	DznT14PTOC1	PTOC_NEU	Deadzone Overcurrent - T14 - Stage 1
	DznT15PTOC1	PTOC_NEU	Deadzone Overcurrent - T15 - Stage 1

LD	LN Instance	LN Type	Description
	DznT16PTOC1	PTOC_NEU	Deadzone Overcurrent - T16 - Stage 1
	DznT17PTOC1	PTOC_NEU	Deadzone Overcurrent - T17 - Stage 1
	DznT18PTOC1	PTOC_NEU	Deadzone Overcurrent - T18 - Stage 1
	DznT19PTOC1	PTOC_NEU	Deadzone Overcurrent - T19 - Stage 1
	DznT20PTOC1	PTOC_NEU	Deadzone Overcurrent - T20 - Stage 1
	DznT21PTOC1	PTOC_NEU	Deadzone Overcurrent - T21 - Stage 1
	EfdT01PTOC1	PTOC_NEU	Earth Fault Protection - T1 - Stage 1
	EfdT01PTOC2	PTOC_NEU	Earth Fault Protection - T1 - Stage 2
	EfdT02PTOC1	PTOC_NEU	Earth Fault Protection - T2 - Stage 1
	EfdT02PTOC2	PTOC_NEU	Earth Fault Protection - T2 - Stage 2
	EfdT03PTOC1	PTOC_NEU	Earth Fault Protection - T3 - Stage 1
	EfdT03PTOC2	PTOC_NEU	Earth Fault Protection - T3 - Stage 2
	EfdT04PTOC1	PTOC_NEU	Earth Fault Protection - T4 - Stage 1
	EfdT04PTOC2	PTOC_NEU	Earth Fault Protection - T4 - Stage 2
	EfdT05PTOC1	PTOC_NEU	Earth Fault Protection - T5 - Stage 1
	EfdT05PTOC2	PTOC_NEU	Earth Fault Protection - T5 - Stage 2
	EfdT06PTOC1	PTOC_NEU	Earth Fault Protection - T6 - Stage 1
	EfdT06PTOC2	PTOC_NEU	Earth Fault Protection - T6 - Stage 2
	EfdT07PTOC1	PTOC_NEU	Earth Fault Protection - T7 - Stage 1
	EfdT07PTOC2	PTOC_NEU	Earth Fault Protection - T7 - Stage 2
	LLN0	LLN0_PROT	Protection LLN0
	LPHD1	LPHD_STANDARD	Physical Device Information
	OcpT01PTOC1	PTOC_NEU	Overcurrent Protection - T1 - Stage 1
	OcpT01PTOC2	PTOC_NEU	Overcurrent Protection - T1 - Stage 2
	OcpT02PTOC1	PTOC_NEU	Overcurrent Protection - T2 - Stage 1
	OcpT02PTOC2	PTOC_NEU	Overcurrent Protection - T2 - Stage 2
	OcpT03PTOC1	PTOC_NEU	Overcurrent Protection - T3 - Stage 1

LD	LN Instance	LN Type	Description
	OcpT03PTOC2	PTOC_NEU	Overcurrent Protection - T3 - Stage 2
	OcpT04PTOC1	PTOC_NEU	Overcurrent Protection - T4 - Stage 1
	OcpT04PTOC2	PTOC_NEU	Overcurrent Protection - T4 - Stage 2
	OcpT05PTOC1	PTOC_NEU	Overcurrent Protection - T5 - Stage 1
	OcpT05PTOC2	PTOC_NEU	Overcurrent Protection - T5 - Stage 2
	OcpT06PTOC1	PTOC_NEU	Overcurrent Protection - T6 - Stage 1
	OcpT06PTOC2	PTOC_NEU	Overcurrent Protection - T6 - Stage 2
	OcpT07PTOC1	PTOC_NEU	Overcurrent Protection - T7 - Stage 1
	OcpT07PTOC2	PTOC_NEU	Overcurrent Protection - T7 - Stage 2
	OcpT08PTOC1	PTOC_NEU	Overcurrent Protection - T8 - Stage 1
	OcpT08PTOC2	PTOC_NEU	Overcurrent Protection - T8 - Stage 2
	OcpT09PTOC1	PTOC_NEU	Overcurrent Protection - T9 - Stage 1
	OcpT09PTOC2	PTOC_NEU	Overcurrent Protection - T9 - Stage 2
	OcpT10PTOC1	PTOC_NEU	Overcurrent Protection - T10 - Stage 1
	OcpT10PTOC2	PTOC_NEU	Overcurrent Protection - T10 - Stage 2
	OcpT11PTOC1	PTOC_NEU	Overcurrent Protection - T11 - Stage 1
	OcpT11PTOC2	PTOC_NEU	Overcurrent Protection - T11 - Stage 2
	OcpT12PTOC1	PTOC_NEU	Overcurrent Protection - T12 - Stage 1
	OcpT12PTOC2	PTOC_NEU	Overcurrent Protection - T12 - Stage 2
	OcpT13PTOC1	PTOC_NEU	Overcurrent Protection - T13 - Stage 1
	OcpT13PTOC2	PTOC_NEU	Overcurrent Protection - T13 - Stage 2
	OcpT14PTOC1	PTOC_NEU	Overcurrent Protection - T14 - Stage 1
	OcpT14PTOC2	PTOC_NEU	Overcurrent Protection - T14 - Stage 2
	OcpT15PTOC1	PTOC_NEU	Overcurrent Protection - T15 - Stage 1
	OcpT15PTOC2	PTOC_NEU	Overcurrent Protection - T15 - Stage 2
	OcpT16PTOC1	PTOC_NEU	Overcurrent Protection - T16 - Stage 1

LD	LN Instance	LN Type	Description
	OcpT16PTOC2	PTOC_NEU	Overcurrent Protection - T16 - Stage 2
	OcpT17PTOC1	PTOC_NEU	Overcurrent Protection - T17 - Stage 1
	OcpT17PTOC2	PTOC_NEU	Overcurrent Protection - T17 - Stage 2
	OcpT18PTOC1	PTOC_NEU	Overcurrent Protection - T18 - Stage 1
	OcpT18PTOC2	PTOC_NEU	Overcurrent Protection - T18 - Stage 2
	OcpT19PTOC1	PTOC_NEU	Overcurrent Protection - T19 - Stage 1
	OcpT19PTOC2	PTOC_NEU	Overcurrent Protection - T19 - Stage 2
	OcpT20PTOC1	PTOC_NEU	Overcurrent Protection - T20 - Stage 1
	OcpT20PTOC2	PTOC_NEU	Overcurrent Protection - T20 - Stage 2
	OcpT21PTOC1	PTOC_NEU	Overcurrent Protection - T21 - Stage 1
	OcpT21PTOC2	PTOC_NEU	Overcurrent Protection - T21 - Stage 2
	PTRC1	PTRC_NO_SEG	Trip Conditioning
Records			
	LLN0	LLN0_STANDARD	Records Logical Device
	LPHD1	LPHD_STANDARD	Physical Device Information
	RDRE1	RDRE_BASIC	Disturbance Recorder
	RFLO1	RFLO_PRIV_P747	Fault record
System			
	AlmGGIO1	GGIO_ALM_96	Alarms
	AlmGGIO2	GGIO_ALM_32	User Alarm Status
	FnkGGIO1	GGIO_IND_10	Function Key Indications
	GosGGIO1	GGIO_IND_64	GOOSE Input Signals
	GosGGIO2	GGIO_IND_32	GOOSE Output Signals
	LedGGIO1	GGIO_IND_18	Red LED Signals
	LedGGIO2	GGIO_IND_18	Green LED Signals
	LLN0	LLN0_SYSTEM	System Logical Device
	LPHD1	LPHD_STANDARD	Physical Device Information
	OptGGIO1	GGIO_IND_40	Opto Inputs
	OrdRunGGIO1	GGIO_IND_64	Uniqueness of control "Order Running" indications for Control operations
	PloGGIO1	GGIO_IND_32_CTRL	PSL Control Inputs
	RlyGGIO1	GGIO_IND_32	Relay outputs

4 LOGICAL NODE DEFINITIONS

The definition tables for each of the Logical Nodes in the top-level data model are presented in the following sub-sections.

The following table presents a summary of the Logical Node templates used across the Logical Devices within the overall IEC61850 product data model:

LN Type	(LN)	Description	Name Space
GGIO_ALM_96	(GGIO)	Generic Process I/O (w.r.t 96 Alarm Elements)	IEC 61850-7-4:2003
GGIO_IND_10	(GGIO)	Generic process I/O	IEC 61850-7-4:2003
GGIO_IND_18	(GGIO)	Generic Process I/O (w.r.t 18 Indication Elements)	IEC 61850-7-4:2003
GGIO_IND_32	(GGIO)	Generic Process I/O (w.r.t 32 Indication Elements)	IEC 61850-7-4:2003
GGIO_IND_32_CTRL	(GGIO)	Generic Process I/O (w.r.t 32 Indication Elements)	IEC 61850-7-4:2003
GGIO_IND_40	(GGIO)	Generic Process I/O (w.r.t 40 Indication Elements)	IEC 61850-7-4:2003
GGIO_IND_64	(GGIO)	Generic Process I/O (w.r.t 64 Indication Elements)	IEC 61850-7-4:2003
GGIO_ALM_32	(GGIO)	Generic process I/O(with 32 Alarm Elements)	IEC 61850-7-4:2003
LLN0_PROT	(LLN0)	Protection Domain Logical Node 0	IEC 61850-7-4:2003
LLN0_STANDARD	(LLN0)	General Logical Node 0	IEC 61850-7-4:2003
LLN0_SYSTEM	(LLN0)	System Domain Logical Node 0	IEC 61850-7-4:2003
LPHD_STANDARD	(LPHD)	Px40 Physical Device Information	IEC 61850-7-4:2003
MDIF_CZ	(MDIF)	Differential measurements for checkzone	IEC 61850-7-4:2003
MDIF_BBP	(MDIF)	Differential measurements for buspar	IEC 61850-7-4:2003
MMXU_A_21	(MMXU)	Standard measurements for P747 three-box mode	IEC 61850-7-4:2003
MMXU_A_7	(MMXU)	Standard measurements for P747 one box mode	IEC 61850-7-4:2003
MMXU_DERIVED_A_7	(MMXU)	Standard measurements for P747	IEC 61850-7-4:2003
MMXU_FOURIER_7	(MMXU)	Fourier standard measurements for P747	IEC 61850-7-4:2003
MSQI_SEQ_7	(MSQI)	Sequence and imbalance For P747	IEC 61850-7-4:2003
PDIF_NEU	(PDIF)	Differential (w.r.t Neutral)	IEC 61850-7-4:2003
PTOC_NEU	(PTOC)	Timed Overcurrent (w.r.t Neutral)	IEC 61850-7-4:2003
PTRC_NO_SEG	(PTRC)	Protection trip conditioning (w.r.t No Phase Segregation)	IEC 61850-7-4:2003

LN Type	(LN)	Description	Name Space
RBRF_STANDARD	(RBRF)	Breaker Failure	IEC 61850-7-4:2003
RDRE_BASIC	(RDRE)	Disturbance Recorder function (w.r.t Mandatory Attributes only)	IEC 61850-7-4:2003
RFLO_PRIV_P747	(RFLO)	Fault locator	IEC 61850-7-4:2003

4.1

Logical Node: GGIO_ALM_32

Description: Generic process I/O(with 32 Alarm Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Alm1	SPS_D	General single alarm		
Alm2	SPS_D	General single alarm		
Alm3	SPS_D	General single alarm		
Alm4	SPS_D	General single alarm		
Alm5	SPS_D	General single alarm		
Alm6	SPS_D	General single alarm		
Alm7	SPS_D	General single alarm		
Alm8	SPS_D	General single alarm		
Alm9	SPS_D	General single alarm		
Alm10	SPS_D	General single alarm		
Alm11	SPS_D	General single alarm		
Alm12	SPS_D	General single alarm		
Alm13	SPS_D	General single alarm		
Alm14	SPS_D	General single alarm		
Alm15	SPS_D	General single alarm		
Alm16	SPS_D	General single alarm		
Alm17	SPS_D	General single alarm		
Alm18	SPS_D	General single alarm		
Alm19	SPS_D	General single alarm		
Alm20	SPS_D	General single alarm		
Alm21	SPS_D	General single alarm		
Alm22	SPS_D	General single alarm		
Alm23	SPS_D	General single alarm		
Alm24	SPS_D	General single alarm		
Alm25	SPS_D	General single alarm		
Alm26	SPS_D	General single alarm		
Alm27	SPS_D	General single alarm		
Alm28	SPS_D	General single alarm		
Alm29	SPS_D	General single alarm		

Attribute	Attr. Type	Explanation	T	X
Alm30	SPS_D	General single alarm		
Alm31	SPS_D	General single alarm		
Alm32	SPS_D	General single alarm		

4.2 Logical Node: GGIO_ALM_96

Description: Generic Process I/O (w.r.t 96 Alarm Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Alm1	SPS_D	General single alarm		
Alm2	SPS_D	General single alarm		
Alm3	SPS_D	General single alarm		
Alm4	SPS_D	General single alarm		
Alm5	SPS_D	General single alarm		
Alm6	SPS_D	General single alarm		
Alm7	SPS_D	General single alarm		
Alm8	SPS_D	General single alarm		
Alm9	SPS_D	General single alarm		
Alm10	SPS_D	General single alarm		
Alm11	SPS_D	General single alarm		
Alm12	SPS_D	General single alarm		
Alm13	SPS_D	General single alarm		
Alm14	SPS_D	General single alarm		
Alm15	SPS_D	General single alarm		
Alm16	SPS_D	General single alarm		
Alm17	SPS_D	General single alarm		
Alm18	SPS_D	General single alarm		
Alm19	SPS_D	General single alarm		
Alm20	SPS_D	General single alarm		
Alm21	SPS_D	General single alarm		
Alm22	SPS_D	General single alarm		
Alm23	SPS_D	General single alarm		
Alm24	SPS_D	General single alarm		
Alm25	SPS_D	General single alarm		
Alm26	SPS_D	General single alarm		
Alm27	SPS_D	General single alarm		
Alm28	SPS_D	General single alarm		
Alm29	SPS_D	General single alarm		
Alm30	SPS_D	General single alarm		
Alm31	SPS_D	General single alarm		
Alm32	SPS_D	General single alarm		

Attribute	Attr. Type	Explanation	T	X
Alm33	SPS_D	General single alarm		
Alm34	SPS_D	General single alarm		
Alm35	SPS_D	General single alarm		
Alm36	SPS_D	General single alarm		
Alm37	SPS_D	General single alarm		
Alm38	SPS_D	General single alarm		
Alm39	SPS_D	General single alarm		
Alm40	SPS_D	General single alarm		
Alm41	SPS_D	General single alarm		
Alm42	SPS_D	General single alarm		
Alm43	SPS_D	General single alarm		
Alm44	SPS_D	General single alarm		
Alm45	SPS_D	General single alarm		
Alm46	SPS_D	General single alarm		
Alm47	SPS_D	General single alarm		
Alm48	SPS_D	General single alarm		
Alm49	SPS_D	General single alarm		
Alm50	SPS_D	General single alarm		
Alm51	SPS_D	General single alarm		
Alm52	SPS_D	General single alarm		
Alm53	SPS_D	General single alarm		
Alm54	SPS_D	General single alarm		
Alm55	SPS_D	General single alarm		
Alm56	SPS_D	General single alarm		
Alm57	SPS_D	General single alarm		
Alm58	SPS_D	General single alarm		
Alm59	SPS_D	General single alarm		
Alm60	SPS_D	General single alarm		
Alm61	SPS_D	General single alarm		
Alm62	SPS_D	General single alarm		
Alm63	SPS_D	General single alarm		
Alm64	SPS_D	General single alarm		
Alm65	SPS_D	General single alarm		
Alm66	SPS_D	General single alarm		
Alm67	SPS_D	General single alarm		
Alm68	SPS_D	General single alarm		
Alm69	SPS_D	General single alarm		
Alm70	SPS_D	General single alarm		
Alm71	SPS_D	General single alarm		
Alm72	SPS_D	General single alarm		
Alm73	SPS_D	General single alarm		
Alm74	SPS_D	General single alarm		
Alm75	SPS_D	General single alarm		
Alm76	SPS_D	General single alarm		

Attribute	Attr. Type	Explanation	T	X
Alm77	SPS_D	General single alarm		
Alm78	SPS_D	General single alarm		
Alm79	SPS_D	General single alarm		
Alm80	SPS_D	General single alarm		
Alm81	SPS_D	General single alarm		
Alm82	SPS_D	General single alarm		
Alm83	SPS_D	General single alarm		
Alm84	SPS_D	General single alarm		
Alm85	SPS_D	General single alarm		
Alm86	SPS_D	General single alarm		
Alm87	SPS_D	General single alarm		
Alm88	SPS_D	General single alarm		
Alm89	SPS_D	General single alarm		
Alm90	SPS_D	General single alarm		
Alm91	SPS_D	General single alarm		
Alm92	SPS_D	General single alarm		
Alm93	SPS_D	General single alarm		
Alm94	SPS_D	General single alarm		
Alm95	SPS_D	General single alarm		
Alm96	SPS_D	General single alarm		

4.3 Logical Node: GGIO_IND_10

Description: Generic process I/O

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ind1	SPS_D	General indication (binary input)		
Ind2	SPS_D	General indication (binary input)		
Ind3	SPS_D	General indication (binary input)		
Ind4	SPS_D	General indication (binary input)		
Ind5	SPS_D	General indication (binary input)		
Ind6	SPS_D	General indication (binary input)		
Ind7	SPS_D	General indication (binary input)		
Ind8	SPS_D	General indication (binary input)		
Ind9	SPS_D	General indication (binary input)		
Ind10	SPS_D	General indication (binary input)		

4.4 Logical Node: GGIO_IND_18

Description: Generic Process I/O (w.r.t 18 Indication Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ind1	SPS_D	General indication (binary input)		
Ind2	SPS_D	General indication (binary input)		
Ind3	SPS_D	General indication (binary input)		
Ind4	SPS_D	General indication (binary input)		
Ind5	SPS_D	General indication (binary input)		
Ind6	SPS_D	General indication (binary input)		
Ind7	SPS_D	General indication (binary input)		
Ind8	SPS_D	General indication (binary input)		
Ind9	SPS_D	General indication (binary input)		
Ind10	SPS_D	General indication (binary input)		
Ind11	SPS_D	General indication (binary input)		
Ind12	SPS_D	General indication (binary input)		
Ind13	SPS_D	General indication (binary input)		
Ind14	SPS_D	General indication (binary input)		
Ind15	SPS_D	General indication (binary input)		
Ind16	SPS_D	General indication (binary input)		
Ind17	SPS_D	General indication (binary input)		
Ind18	SPS_D	General indication (binary input)		

4.5

Logical Node: GGIO_IND_32

Description: Generic Process I/O (w.r.t 32 Indication Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ind1	SPS_D	General indication (binary input)		
Ind2	SPS_D	General indication (binary input)		
Ind3	SPS_D	General indication (binary input)		
Ind4	SPS_D	General indication (binary input)		
Ind5	SPS_D	General indication (binary input)		
Ind6	SPS_D	General indication (binary input)		
Ind7	SPS_D	General indication (binary input)		
Ind8	SPS_D	General indication (binary input)		
Ind9	SPS_D	General indication (binary input)		
Ind10	SPS_D	General indication (binary input)		
Ind11	SPS_D	General indication (binary input)		
Ind12	SPS_D	General indication (binary input)		
Ind13	SPS_D	General indication (binary input)		

Attribute	Attr. Type	Explanation	T	X
Ind14	SPS_D	General indication (binary input)		
Ind15	SPS_D	General indication (binary input)		
Ind16	SPS_D	General indication (binary input)		
Ind17	SPS_D	General indication (binary input)		
Ind18	SPS_D	General indication (binary input)		
Ind19	SPS_D	General indication (binary input)		
Ind20	SPS_D	General indication (binary input)		
Ind21	SPS_D	General indication (binary input)		
Ind22	SPS_D	General indication (binary input)		
Ind23	SPS_D	General indication (binary input)		
Ind24	SPS_D	General indication (binary input)		
Ind25	SPS_D	General indication (binary input)		
Ind26	SPS_D	General indication (binary input)		
Ind27	SPS_D	General indication (binary input)		
Ind28	SPS_D	General indication (binary input)		
Ind29	SPS_D	General indication (binary input)		
Ind30	SPS_D	General indication (binary input)		
Ind31	SPS_D	General indication (binary input)		
Ind32	SPS_D	General indication (binary input)		

4.6

Logical Node: GGIO_IND_32_CTRL

Description: Generic Process I/O (w.r.t 32 Indication Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
SPCSO1	SPC_CONTROL	Single point controllable status output		
SPCSO2	SPC_CONTROL	Single point controllable status output		
SPCSO3	SPC_CONTROL	Single point controllable status output		
SPCSO4	SPC_CONTROL	Single point controllable status output		
SPCSO5	SPC_CONTROL	Single point controllable status output		
SPCSO6	SPC_CONTROL	Single point controllable status output		
SPCSO7	SPC_CONTROL	Single point controllable status output		
SPCSO8	SPC_CONTROL	Single point controllable status output		
SPCSO9	SPC_CONTROL	Single point controllable status output		
SPCSO10	SPC_CONTROL	Single point controllable status output		
SPCSO11	SPC_CONTROL	Single point controllable status output		
SPCSO12	SPC_CONTROL	Single point controllable status output		
SPCSO13	SPC_CONTROL	Single point controllable status output		
SPCSO14	SPC_CONTROL	Single point controllable status output		
SPCSO15	SPC_CONTROL	Single point controllable status output		
SPCSO16	SPC_CONTROL	Single point controllable status output		

Attribute	Attr. Type	Explanation	T	X
SPCSO17	SPC_CONTROL	Single point controllable status output		
SPCSO18	SPC_CONTROL	Single point controllable status output		
SPCSO19	SPC_CONTROL	Single point controllable status output		
SPCSO20	SPC_CONTROL	Single point controllable status output		
SPCSO21	SPC_CONTROL	Single point controllable status output		
SPCSO22	SPC_CONTROL	Single point controllable status output		
SPCSO23	SPC_CONTROL	Single point controllable status output		
SPCSO24	SPC_CONTROL	Single point controllable status output		
SPCSO25	SPC_CONTROL	Single point controllable status output		
SPCSO26	SPC_CONTROL	Single point controllable status output		
SPCSO27	SPC_CONTROL	Single point controllable status output		
SPCSO28	SPC_CONTROL	Single point controllable status output		
SPCSO29	SPC_CONTROL	Single point controllable status output		
SPCSO30	SPC_CONTROL	Single point controllable status output		
SPCSO31	SPC_CONTROL	Single point controllable status output		
SPCSO32	SPC_CONTROL	Single point controllable status output		

4.7

Logical Node: GGIO_IND_40

Description: Generic Process I/O (w.r.t 40 Indication Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ind1	SPS_D	General indication (binary input)		
Ind2	SPS_D	General indication (binary input)		
Ind3	SPS_D	General indication (binary input)		
Ind4	SPS_D	General indication (binary input)		
Ind5	SPS_D	General indication (binary input)		
Ind6	SPS_D	General indication (binary input)		
Ind7	SPS_D	General indication (binary input)		
Ind8	SPS_D	General indication (binary input)		
Ind9	SPS_D	General indication (binary input)		
Ind10	SPS_D	General indication (binary input)		
Ind11	SPS_D	General indication (binary input)		
Ind12	SPS_D	General indication (binary input)		
Ind13	SPS_D	General indication (binary input)		
Ind14	SPS_D	General indication (binary input)		
Ind15	SPS_D	General indication (binary input)		
Ind16	SPS_D	General indication (binary input)		
Ind17	SPS_D	General indication (binary input)		
Ind18	SPS_D	General indication (binary input)		
Ind19	SPS_D	General indication (binary input)		

Attribute	Attr. Type	Explanation	T	X
Ind20	SPS_D	General indication (binary input)		
Ind21	SPS_D	General indication (binary input)		
Ind22	SPS_D	General indication (binary input)		
Ind23	SPS_D	General indication (binary input)		
Ind24	SPS_D	General indication (binary input)		
Ind25	SPS_D	General indication (binary input)		
Ind26	SPS_D	General indication (binary input)		
Ind27	SPS_D	General indication (binary input)		
Ind28	SPS_D	General indication (binary input)		
Ind29	SPS_D	General indication (binary input)		
Ind30	SPS_D	General indication (binary input)		
Ind31	SPS_D	General indication (binary input)		
Ind32	SPS_D	General indication (binary input)		
Ind33	SPS_D	General indication (binary input)		
Ind34	SPS_D	General indication (binary input)		
Ind35	SPS_D	General indication (binary input)		
Ind36	SPS_D	General indication (binary input)		
Ind37	SPS_D	General indication (binary input)		
Ind38	SPS_D	General indication (binary input)		
Ind39	SPS_D	General indication (binary input)		
Ind40	SPS_D	General indication (binary input)		

4.8

Logical Node: GGIO_IND_64

Description: Generic Process I/O (w.r.t 64 Indication Elements)

LN Class: GGIO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ind1	SPS_D	General indication (binary input)		
Ind2	SPS_D	General indication (binary input)		
Ind3	SPS_D	General indication (binary input)		
Ind4	SPS_D	General indication (binary input)		
Ind5	SPS_D	General indication (binary input)		
Ind6	SPS_D	General indication (binary input)		
Ind7	SPS_D	General indication (binary input)		
Ind8	SPS_D	General indication (binary input)		
Ind9	SPS_D	General indication (binary input)		
Ind10	SPS_D	General indication (binary input)		
Ind11	SPS_D	General indication (binary input)		
Ind12	SPS_D	General indication (binary input)		
Ind13	SPS_D	General indication (binary input)		
Ind14	SPS_D	General indication (binary input)		

Attribute	Attr. Type	Explanation	T	X
Ind15	SPS_D	General indication (binary input)		
Ind16	SPS_D	General indication (binary input)		
Ind17	SPS_D	General indication (binary input)		
Ind18	SPS_D	General indication (binary input)		
Ind19	SPS_D	General indication (binary input)		
Ind20	SPS_D	General indication (binary input)		
Ind21	SPS_D	General indication (binary input)		
Ind22	SPS_D	General indication (binary input)		
Ind23	SPS_D	General indication (binary input)		
Ind24	SPS_D	General indication (binary input)		
Ind25	SPS_D	General indication (binary input)		
Ind26	SPS_D	General indication (binary input)		
Ind27	SPS_D	General indication (binary input)		
Ind28	SPS_D	General indication (binary input)		
Ind29	SPS_D	General indication (binary input)		
Ind30	SPS_D	General indication (binary input)		
Ind31	SPS_D	General indication (binary input)		
Ind32	SPS_D	General indication (binary input)		
Ind33	SPS_D	General indication (binary input)		
Ind34	SPS_D	General indication (binary input)		
Ind35	SPS_D	General indication (binary input)		
Ind36	SPS_D	General indication (binary input)		
Ind37	SPS_D	General indication (binary input)		
Ind38	SPS_D	General indication (binary input)		
Ind39	SPS_D	General indication (binary input)		
Ind40	SPS_D	General indication (binary input)		
Ind41	SPS_D	General indication (binary input)		
Ind42	SPS_D	General indication (binary input)		
Ind43	SPS_D	General indication (binary input)		
Ind44	SPS_D	General indication (binary input)		
Ind45	SPS_D	General indication (binary input)		
Ind46	SPS_D	General indication (binary input)		
Ind47	SPS_D	General indication (binary input)		
Ind48	SPS_D	General indication (binary input)		
Ind49	SPS_D	General indication (binary input)		
Ind50	SPS_D	General indication (binary input)		
Ind51	SPS_D	General indication (binary input)		
Ind52	SPS_D	General indication (binary input)		
Ind53	SPS_D	General indication (binary input)		
Ind54	SPS_D	General indication (binary input)		
Ind55	SPS_D	General indication (binary input)		
Ind56	SPS_D	General indication (binary input)		
Ind57	SPS_D	General indication (binary input)		
Ind58	SPS_D	General indication (binary input)		

Attribute	Attr. Type	Explanation	T	X
Ind59	SPS_D	General indication (binary input)		
Ind60	SPS_D	General indication (binary input)		
Ind61	SPS_D	General indication (binary input)		
Ind62	SPS_D	General indication (binary input)		
Ind63	SPS_D	General indication (binary input)		
Ind64	SPS_D	General indication (binary input)		

4.9 Logical Node: LLN0_PROT

Description: Protection Domain Logical Node 0

LN Class: LLN0

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LLNO	Name Plate		
DifMod	INC_MOD_D_PRIV	Differential Mode		X
DifBeh	INS_BEH_D_PRIV	Differential Behaviour		X
DznMod	INC_MOD_D_PRIV	Deadzone Overcurrent Mode		X
DznBeh	INS_BEH_D_PRIV	Deadzone Overcurrent Behaviour		X
OcpMod	INC_MOD_D_PRIV	Overcurrent Mode		X
OcpBeh	INS_BEH_D_PRIV	Overcurrent Behaviour		X
EfmMod	INC_MOD_D_PRIV	Earth Fault 1 (Measured) Mode		X
EfmBeh	INS_BEH_D_PRIV	Earth Fault 1 (Measured) Behaviour		X
CbfMod	INC_MOD_D_PRIV	CB Fail Mode		X
CbfBeh	INS_BEH_D_PRIV	Circuit Breaker Fail Behaviour		X
SvnMod	INC_MOD_D_PRIV	System Backup Mode		X
SvnBeh	INS_BEH_D_PRIV	System backup Behaviour		X

4.10 Logical Node: LLN0_STANDARD

Description: General Logical Node 0

LN Class: LLN0

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LLNO	Name Plate		

4.11 Logical Node: LLN0_SYSTEM

Description: System Domain Logical Node 0

LN Class: LLN0

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		

Attribute	Attr. Type	Explanation	T	X
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LLNO	Name Plate		
LEDRs	SPC_CONTROL	LED Reset	T	
OrdRun	SPS_WD_NS	Order Running(IEC 61850 phase 2.0 and 2.1)		X
SyncSt	SPS_WD_NS	Time Synchronisation Indication(IEC 61850 phase 2.0 and 2.1)		X

4.12 Logical Node: LPHD_STANDARD

Description: Px40 Physical Device Information

LN Class: LPHD

Attribute	Attr. Type	Explanation	T	X
PhyNam	DPL_STANDARD	Physical device name plate		
PhyHealth	INS_HEALTH	Physical device health		
Proxy	SPS_D	Indicates if this LN is a proxy		
PwrUp	SPS_D	Power up detected		

4.13 Logical Node: MDIF_BBP

Description: Differential measurements for buspar

LN Class: MDIF

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
OpARem	WYE_SEG_D	Remote current measurement value		

4.14 Logical Node: MDIF_CZ

Description: Differential measurements for checkzone

LN Class: MDIF

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
OpARem	WYE_SEG_D	Remote current measurement value		

4.15 Logical Node: MMXU_A_21

Description: Standard measurements for P747 three-box mode

LN Class: MMXU

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ase1	WYE_SEG_ANONYMOU	Single anonymous phase terminal 1		X
Ase2	WYE_SEG_ANONYMOU	Single anonymous phase terminal 2		X
Ase3	WYE_SEG_ANONYMOU	Single anonymous phase terminal 3		X
Ase4	WYE_SEG_ANONYMOU	Single anonymous phase terminal 4		X
Ase5	WYE_SEG_ANONYMOU	Single anonymous phase terminal 5		X
Ase6	WYE_SEG_ANONYMOU	Single anonymous phase terminal 6		X
Ase7	WYE_SEG_ANONYMOU	Single anonymous phase terminal 7		X
Ase8	WYE_SEG_ANONYMOU	Single anonymous phase terminal 8		X
Ase9	WYE_SEG_ANONYMOU	Single anonymous phase terminal 9		X
Ase10	WYE_SEG_ANONYMOU	Single anonymous phase terminal 10		X
Ase11	WYE_SEG_ANONYMOU	Single anonymous phase terminal 11		X
Ase12	WYE_SEG_ANONYMOU	Single anonymous phase terminal 12		X
Ase13	WYE_SEG_ANONYMOU	Single anonymous phase terminal 13		X
Ase14	WYE_SEG_ANONYMOU	Single anonymous phase terminal 14		X
Ase15	WYE_SEG_ANONYMOU	Single anonymous phase terminal 15		X
Ase16	WYE_SEG_ANONYMOU	Single anonymous phase terminal 16		X
Ase17	WYE_SEG_ANONYMOU	Single anonymous phase terminal 17		X
Ase18	WYE_SEG_ANONYMOU	Single anonymous phase terminal 18		X
Ase19	WYE_SEG_ANONYMOU	Single anonymous phase terminal 19		X
Ase20	WYE_SEG_ANONYMOU	Single anonymous phase terminal 20		X
Ase21	WYE_SEG_ANONYMOU	Single anonymous phase terminal 21		X

4.16

Logical Node: MMXU_A_7

Description: Standard measurements for P747 one box mode

LN Class: MMXU

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
Ase1	WYE_SEG_ANONYMOU	Single anonymous phase terminal 1		X
NamPlt	LPL_LN	Name Plate		
Ase2	WYE_SEG_ANONYMOU	Single anonymous phase terminal 2		X
Ase3	WYE_SEG_ANONYMOU	Single anonymous phase terminal 3		X
Ase4	WYE_SEG_ANONYMOU	Single anonymous phase terminal 4		X
Ase5	WYE_SEG_ANONYMOU	Single anonymous phase terminal 5		X
Ase6	WYE_SEG_ANONYMOU	Single anonymous phase terminal 6		X
Ase7	WYE_SEG_ANONYMOU	Single anonymous phase terminal 7		X

4.17 Logical Node: MMXU_DERIVED_A_7

Description: Standard measurements for P747

LN Class: MMXU

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Ase1	WYE_SEG_ANG_NS	Phase currents, derived - T1		X
Ase2	WYE_SEG_ANG_NS	Phase currents, derived - T2		X
Ase3	WYE_SEG_ANG_NS	Phase currents, derived - T3		X
Ase4	WYE_SEG_ANG_NS	Phase currents, derived - T4		X
Ase5	WYE_SEG_ANG_NS	Phase currents, derived - T5		X
Ase6	WYE_SEG_ANG_NS	Phase currents, derived - T6		X
Ase7	WYE_SEG_ANG_NS	Phase currents, derived - T7		X

4.18 Logical Node: MMXU_FOURIER_7

Description: Fourier standard measurements for P747

LN Class: MMXU

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Hz	MV_FLOAT_D	Frequency		

4.19 Logical Node: MSQI_SEQ_7

Description: Sequence and imbalance For P747

LN Class: MSQI

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
SeqA	SEQ_MAG_ND	Positive, Negative and Zero sequence current for T1		
SeqAse1	SEQ_MAG	Positive, Negative and Zero sequence current for T2		X
SeqAse2	SEQ_MAG	Positive, Negative and Zero sequence current for T3		X
SeqAse3	SEQ_MAG	Positive, Negative and Zero sequence current for T4		X
SeqAse4	SEQ_MAG	Positive, Negative and Zero sequence current for T5		X

Attribute	Attr. Type	Explanation	T	X
SeqAse5	SEQ_MAG	Positive, Negative and Zero sequence current for T6		X
SeqAse6	SEQ_MAG	Positive, Negative and Zero sequence current for T7		X

4.20 Logical Node: PDIF_NEU

Description: Differential (w.r.t Neutral)

LN Class: PDIF

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Op	ACT_NO_SEG	Operate	T	

4.21 Logical Node: PTOC_NEU

Description: Timed Overcurrent (w.r.t Neutral)

LN Class: PTOC

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Str	ACD_NO_SEG	Start		
Op	ACT_NO_SEG	Operate	T	

4.22 Logical Node: PTRC_NO_SEG

Description: Protection trip conditioning (w.r.t No Phase Segregation)

LN Class: PTRC

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
Tr	ACT_NO_SEG	Trip		
Str	ACD_NO_SEG	Sum of all starts of all connected Logical Nodes		

4.23 Logical Node: RBRF_STANDARD

Description: Breaker Failure

LN Class: RBRF

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
OpEx	ACT_NO_SEG	Breaker failure trip ("External trip")	T	
OpIn	ACT_NO_SEG	Operate, retrip ("Internal trip")	T	

4.24 Logical Node: RDRE_BASIC

Description: Disturbance Recorder function (w.r.t Mandatory Attributes only)

LN Class: RDRE

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
RcdMade	SPS_WD	Recording made		
FltNum	INS_BASIC	Fault number		

4.25 Logical Node: RFLO_PRIV_P747

Description: Fault locator

LN Class: RFLO

Attribute	Attr. Type	Explanation	T	X
Mod	INC_MOD	Mode		
Beh	INS_BEH	Behaviour		
Health	INS_HEALTH	Health		
NamPlt	LPL_LN	Name Plate		
FltZ	CMV_MAG	Fault impedance		
FltDiskm	MV_FLOAT_ND	Fault distance in km		
FltPhs	INS_D_NS	Fault phase		X
FltSt1U	INS_D_NS	Fault start element 1 up		X
FltSt1L	INS_D_NS	Fault start element 1 low		X
FltSt2U	INS_D_NS	Fault start element 2 up		X
FltSt2L	INS_D_NS	Fault start element 2 low		X
FltSt3U	INS_D_NS	Fault start element 3 up		X
FltSt3L	INS_D_NS	Fault start element 3 low		X
FltSt4U	INS_D_NS	Fault start element 4 up		X
FltSt4L	INS_D_NS	Fault start element 4 low		X
FltOp1U	INS_D_NS	Fault trip element 1 up		X
FltOp1L	INS_D_NS	Fault trip element 1 low		X
FltOp2U	INS_D_NS	Fault trip element 2 up		X
FltOp2L	INS_D_NS	Fault trip element 2 low		X
FltOp3U	INS_D_NS	Fault trip element 3 up		X
FltOp3L	INS_D_NS	Fault trip element 3 low		X

Attribute	Attr. Type	Explanation	T	X
FltAlm1U	INS_D_NS	Fault alarm 1 up		X
FltAlm1L	INS_D_NS	Fault alarm 1 low		X
FltAlm2U	INS_D_NS	Fault alarm 2 up		X
FltAlm2L	INS_D_NS	Fault alarm 2 low		X
FltTU	INS_D_NS	Fault time up		X
FltTL	INS_D_NS	Fault time low		X
FltTms	INS_D_NS	Fault time ms		X
FltNum	INS_D	Fault record number		X
FltTye	INS_D_NS	Fault type		X
ActiveSG	INS_D_NS	Fault Record Active group		X
FltHz	MV_FLOAT_FAULT	Fault Record frequency		X
FltDur	MV_FLOAT_FAULT	Fault duration		X
CBOpTm	MV_FLOAT_FAULT	CB Operation time		X
RlyOpTm	MV_FLOAT_FAULT	Relay Operation time		X
TestMod	INS_D_NS	Test mode		X
FltA1	WYE_SEG_FAULT	Fault phase current--T1		X
FltA2	WYE_SEG_FAULT	Fault phase current--T2		X
FltA3	WYE_SEG_FAULT	Fault phase current--T3		X
FltA4	WYE_SEG_FAULT	Fault phase current--T4		X
FltA5	WYE_SEG_FAULT	Fault phase current--T5		X
FltA6	WYE_SEG_FAULT	Fault phase current--T6		X
FltA7	WYE_SEG_FAULT	Fault phase current--T7		X
AX1	MV_FLOAT_FAULT	Single anonymous phase terminal 1		X
AX2	MV_FLOAT_FAULT	Single anonymous phase terminal 2		X
AX3	MV_FLOAT_FAULT	Single anonymous phase terminal 3		X
AX4	MV_FLOAT_FAULT	Single anonymous phase terminal 4		X
AX5	MV_FLOAT_FAULT	Single anonymous phase terminal 5		X
AX6	MV_FLOAT_FAULT	Single anonymous phase terminal 6		X
AX7	MV_FLOAT_FAULT	Single anonymous phase terminal 7		X
AX8	MV_FLOAT_FAULT	Single anonymous phase terminal 8		X
AX9	MV_FLOAT_FAULT	Single anonymous phase terminal 9		X
AX10	MV_FLOAT_FAULT	Single anonymous phase terminal 10		X
AX11	MV_FLOAT_FAULT	Single anonymous phase terminal 11		X
AX12	MV_FLOAT_FAULT	Single anonymous phase terminal 12		X
AX13	MV_FLOAT_FAULT	Single anonymous phase terminal 13		X
AX14	MV_FLOAT_FAULT	Single anonymous phase terminal 14		X
AX15	MV_FLOAT_FAULT	Single anonymous phase terminal 15		X
AX16	MV_FLOAT_FAULT	Single anonymous phase terminal 16		X
AX17	MV_FLOAT_FAULT	Single anonymous phase terminal 17		X
AX18	MV_FLOAT_FAULT	Single anonymous phase terminal 18		X
AX19	MV_FLOAT_FAULT	Single anonymous phase terminal 19		X
AX20	MV_FLOAT_FAULT	Single anonymous phase terminal 20		X
AX21	MV_FLOAT_FAULT	Single anonymous phase terminal 21		X
Z1IDiff	WYE_SEG_FAULT	Fault differential current--Z1		X

Attribute	Attr. Type	Explanation	T	X
Z1Bias	WYE_SEG_FAULT	Fault bias current--Z1		X
Z2Diff	WYE_SEG_FAULT	Fault differential current--Z2		X
Z2Bias	WYE_SEG_FAULT	Fault bias current--Z2		X
Z3Diff	WYE_SEG_FAULT	Fault differential current--Z3		X
Z3Bias	WYE_SEG_FAULT	Fault bias current--Z3		X
Z4Diff	WYE_SEG_FAULT	Fault differential current--Z4		X
Z4Bias	WYE_SEG_FAULT	Fault bias current--Z4		X
CZIDiff	WYE_SEG_FAULT	Fault differential current--CZ		X
CZIBias	WYE_SEG_FAULT	Fault bias current--CZ		X

5 COMMON DATA CLASS DEFINITIONS

The definition tables for each of the Common Data Classes used in the Logical Node definitions are presented in the following sub-sections.

From an application point-of-view the data attributes of a Common Data Class are classified according to their specific use. The characterization of data attributes, and the services that they support/provide, will be through the use of 'Functional Constraints'. The Functional Constraints are specified by the table below:

FC Name	Semantic	Source Definition
BR	Buffered reports	IEC61850-7-2
CF	Configuration	IEC61850-7-2
CO	Control	IEC61850-7-2
DC	Description	IEC61850-7-2
EX	Extended Definition	IEC61850-7-2
GO	GOOSE Control	IEC61850-7-2
GS	GSSE Control (UCA2 GOOSE)	IEC61850-7-2
LG	Logging	IEC61850-7-2
MS	Multicast sampled value control	IEC61850-7-2
MX	Measurands (Analogue values)	IEC61850-7-2
RP	Unbuffered reports	IEC61850-7-2
SE	Setting Group Editable	IEC61850-7-2
SG	Setting Group	IEC61850-7-2
SP	Set Point	IEC61850-7-2
ST	Status Information	IEC61850-7-2
SV	Substitution Values	IEC61850-7-2
US	Unicast sampled value control	IEC61850-7-2
XX	Data attribute service parameters	IEC61850-7-2

5.1 Common Data Class: ACD_NO_SEG

Description: Directional Protection Activation Information (w,r,t No Phase Segregation)

CDC Class: ACD

Attribute	Type	FC	Enumeration	Comment	X
general	BOOLEAN	ST		Trip or start has happened	
dirGeneral	ENUMERATED8 (MMS Type: INT8)	ST	dir	General direction (unknown, forward, backward or both)	
q	Quality	ST		Quality of the protection activation information	
t	TimeStamp	ST		Timestamp of the last change in state of protection activation information	

5.2 Common Data Class: ACT_NO_SEG

Description: Protection Activation Information (w.r.t No Phase Segregation)

CDC Class: ACT

Attribute	Type	FC	Enumeration	Comment	X
general	BOOLEAN	ST		Trip or start has happened	
q	Quality	ST		Quality of the protection activation information	
t	TimeStamp	ST		Timestamp of the last change in state of protection activation information	

5.3**Common Data Class: CMV_MAG**

Description: Complex Measured value(without db and rangeC)

CDC Class: CMV

Attribute	Type	FC	Enumeration	Comment	X
cVal	Vector_Magnitude_Float	MX		Deadbanded complex measured vector. Updated to the current value of instCVal when the value has changed according to the configuration parameter db.	
q	Quality	MX		Quality of the measurement value	
t	TimeStamp	MX		Time deadbanded magnitude last exceeded its db configuration parameter	
units	Unit_Multiplier	CF		Unit of the attribute representing the data	

5.4**Common Data Class: CMV_MAG_ANG_FLOAT**

Description: Complex Measured value (w.r.t Floating Point Magnitude and Angle)

CDC Class: CMV

Attribute	Type	FC	Enumeration	Comment	X
cVal	Vector_MagnitudeAngle_Float	MX		Deadbanded complex measured vector. Updated to the current value of instCVal when the value has changed according to the configuration parameter db.	
q	Quality	MX		Quality of the measurement value	
t	TimeStamp	MX		Time deadbanded magnitude last exceeded its db configuration parameter	
units	Unit_Multiplier	CF		Unit of the attribute representing the data	
db	INT32U	CF		Measurement deadband	

Attribute	Type	FC	Enumeration	Comment	X
rangeC	RangeConfig_Deadband	CF		Measurement range configuration attributes	

5.5 Common Data Class: CMV_MAG_FLOAT

Description: Complex Measured value (w.r.t Floating Point Magnitude)

CDC Class: CMV

Attribute	Type	FC	Enumeration	Comment	X
cVal	Vector_Magnitude_Float	MX		Deadbanded complex measured vector. Updated to the current value of instCVal when the value has changed according to the configuration parameter db.	
q	Quality	MX		Quality of the measurement value	
t	TimeStamp	MX		Time deadbanded magnitude last exceeded its db configuration parameter	
units	Unit_Multiplier	CF		Unit of the attribute representing the data	
db	INT32U	CF		Measurement deadband	
rangeC	RangeConfig_Deadband	CF		Measurement range configuration attributes	

5.6 Common Data Class: DPL_STANDARD

Description: Standard Device Name Plate

CDC Class: DPL

Attribute	Type	FC	Enumeration	Comment	X
vendor	VISIBLE_STRING255	DC		Name of the vendor	
hwRev	VISIBLE_STRING255	DC		Hardware revision	
swRev	VISIBLE_STRING255	DC		Software revision	
serNum	VISIBLE_STRING255	DC		Serial Number	
model	VISIBLE_STRING255	DC		Model Number	
location	VISIBLE_STRING255	DC		Physical location of device	

5.7 Common Data Class: INC_MOD

Description: Controllable Integer Status (w.r.t Mode)

CDC Class: INC

Attribute	Type	FC	Enumeration	Comment	X
stVal	ENUMERATED8 (MMS Type: INT8)	ST	Mod	Status value of the data	
q	Quality	ST		Quality of the status value	

Attribute	Type	FC	Enumeration	Comment	X
t	TimeStamp	ST		Timestamp of the last change in state of status value	
ctlModel	ENUMERATED8 (MMS Type: INT8)	CF	ctlModel	Control model (Corresponding to the behaviour of the data)	

5.8**Common Data Class: INC_MOD_D_PRIV**

Description: Controllable Integer Status (w.r.t Mode, with description (Private DO))

CDC Class: INC

Attribute	Type	FC	Enumeration	Comment	X
ctlVal	INT32	CO		Control value	
stVal	ENUMERATED8 (MMS Type: INT8)	ST	Mod	Status value of the data	
q	Quality	ST		Quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state of status value	
ctlModel	ENUMERATED8 (MMS Type: INT8)	CF	ctlModel	Control model (Corresponding to the behaviour of the data)	
d	VISIBLE_STRING255	DC		Description of the status element	
cdcNs	VISIBLE_STRING255	EX		Common Data Class Name Space	
cdcName	VISIBLE_STRING255	EX		Name of the Common Data Class	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.9**Common Data Class: INS_BASIC**

Description: Integer Status (w.r.t Mandatory Options Only)

CDC Class: INS

Attribute	Type	FC	Enumeration	Comment	X
stVal	INT32	ST		The element status	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	

5.10**Common Data Class: INS_BEH**

Description: Integer Status (w.r.t Behaviour)

CDC Class: INS

Attribute	Type	FC	Enumeration	Comment	X
stVal	ENUMERATED8 (MMS Type: INT8)	ST	Beh	The element status	
q	Quality	ST		The quality of the status value	

Attribute	Type	FC	Enumeration	Comment	X
t	TimeStamp	ST		Timestamp of the last change in state	

5.11 Common Data Class: INS_BEH_D_PRIV

Description: Integer Status (w.r.t Behaviour, with Description (Private DO))

CDC Class: INS

Attribute	Type	FC	Enumeration	Comment	X
stVal	ENUMERATED8 (MMS Type: INT8)	ST	Beh	The element status	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	
d	VISIBLE_STRING255	DC		Description of the status element	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.12 Common Data Class: INS_D

Description: Integer Status

CDC Class: INS

Attribute	Type	FC	Enumeration	Comment	X
stVal	INT32	ST		The element status	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	
d	VISIBLE_STRING255	DC		Description of the status element	

5.13 Common Data Class: INS_D_NS

Description: Integer Status with description

CDC Class: INS

Attribute	Type	FC	Enumeration	Comment	X
stVal	INT32	ST		The element status	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	
d	VISIBLE_STRING255	DC		Description of the status element	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.14 Common Data Class: INS_HEALTH

Description: Integer Status (w.r.t health)

CDC Class: INS

Attribute	Type	FC	Enumeration	Comment	X
stVal	INT32 (MMS Type: INT8)	ST	Health	The element status	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	

5.15**Common Data Class: LPL_LLNO**

Description: Logical Node 0 Name Plate

CDC Class: LPL

Attribute	Type	FC	Enumeration	Comment	X
vendor	VISIBLE_STRING255	DC		Name of the vendor	
swRev	VISIBLE_STRING255	DC		Software revision	
d	VISIBLE_STRING255	DC		Description	
configRev	VISIBLE_STRING255	DC		Uniquely identifies the configuration of a local device instance	
ldNs	VISIBLE_STRING255	EX		Logical Device name space	

5.16**Common Data Class: LPL_LN**

Description: Standard Logical Node Name Plate

CDC Class: LPL

Attribute	Type	FC	Enumeration	Comment	X
vendor	VISIBLE_STRING255	DC		Name of the vendor	
swRev	VISIBLE_STRING255	DC		Software revision	
d	VISIBLE_STRING255	DC		Description	

5.17**Common Data Class: MV_FLOAT_D**

Description: Measured value (w.r.t Floating Point Value with Description)

CDC Class: MV

Attribute	Type	FC	Enumeration	Comment	X
mag	AnalogueValue_Float	MX		Deadbanded magnitude of the instantaneous value of a measured value or harmonic value. Updated to the current value of instMag when the value has changed according to the configuration parameter db.	
q	Quality	MX		Quality of the measurement value	
t	TimeStamp	MX		Time deadbanded magnitude last exceeded its db configuration parameter	

Attribute	Type	FC	Enumeration	Comment	X
units	Unit_Multiplier	CF		Unit of the attribute representing the data	
db	INT32U	CF		Measurement deadband	
rangeC	RangeConfig_Deadband	CF		Measurement range configuration attributes	
d	VISIBLE_STRING255	DC		Description of the status element	

5.18 Common Data Class: MV_FLOAT_FAULT

Description: Measured value(without db and rangC but NS)

CDC Class: MV

Attribute	Type	FC	Enumeration	Comment	X
mag	AnalogueValue_Float	MX		Deadbanded magnitude of the instantaneous value of a measured value or harmonic value. Updated to the current value of instMag when the value has changed according to the configuration parameter db.	
q	Quality	MX		Quality of the measurement value	
t	TimeStamp	MX		Time deadbanded magnitude last exceeded its db configuration parameter	
units	Unit	CF		Unit of the attribute representing the data	
d	VISIBLE_STRING255	DC		Description of the status element	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.19 Common Data Class: MV_FLOAT_ND

Description: Measured value (without d)

CDC Class: MV

Attribute	Type	FC	Enumeration	Comment	X
mag	AnalogueValue_Float	MX		Deadbanded magnitude of the instantaneous value of a measured value or harmonic value. Updated to the current value of instMag when the value has changed according to the configuration parameter db.	
q	Quality	MX		Quality of the measurement value	

Attribute	Type	FC	Enumeration	Comment	X
t	TimeStamp	MX		Time deadbanded magnitude last exceeded its db configuration parameter	
units	Unit	CF		Unit of the attribute representing the data	

5.20**Common Data Class: SEQ_MAG**

Description: Sequence components of a measurement value without dataNs

CDC Class: SEQ

Attribute	Type	FC	Enumeration	Comment	X
c1	CMV_MAG_FLOAT	--		Sequence component 1 (For semantic meaning see seqT)	
c2	CMV_MAG_FLOAT	--		Sequence component 2 (For semantic meaning see seqT)	
c3	CMV_MAG_FLOAT	--		Sequence component 3 (For semantic meaning see seqT)	
seqT	ENUMERATED8 (MMS Type: INT8)	MX	seqT	Sequence quantity measurement type (Pos-Neg-Zero or Dir-Quad-Zero)	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.21**Common Data Class: SEQ_MAG_ND**

Description: Sequence components of a measurement value

CDC Class: SEQ

Attribute	Type	FC	Enumeration	Comment	X
c1	CMV_MAG_FLOAT	--		Sequence component 1 (For semantic meaning see seqT)	
c2	CMV_MAG_FLOAT	--		Sequence component 2 (For semantic meaning see seqT)	
c3	CMV_MAG_FLOAT	--		Sequence component 3 (For semantic meaning see seqT)	
seqT	ENUMERATED8 (MMS Type: INT8)	MX	seqT	Sequence quantity measurement type (Pos-Neg-Zero or Dir-Quad-Zero)	

5.22**Common Data Class: SPC_CONTROL**

Description: Controllable Single Point

CDC Class: SPC

Attribute	Type	FC	Enumeration	Comment	X
ctlVal	BOOLEAN	CO		Control value (Off - FALSE, On - TRUE)	
origin	Originator	ST		Originator of the last change of the controllable data	
stVal	BOOLEAN	ST		Status value of the data	
q	Quality	ST		Quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state of status value	
ctlModel	ENUMERATED8 (MMS Type: INT8)	CF	ctlModel	Control model (Corresponding to the behaviour of the data)	
sboTimeout	INT32U	CF		Select Before Operate timeout period (in milliseconds)	
cdcNs	VISIBLE_STRING255	EX		Common Data Class Name Space	
cdcName	VISIBLE_STRING255	EX		Name of the Common Data Class	
d	VISIBLE_STRING255	DC		Description of the status element	

5.23 Common Data Class: SPS_D

Description: Standard Single Point Status (with Description)

CDC Class: SPS

Attribute	Type	FC	Enumeration	Comment	X
stVal	BOOLEAN	ST		The element status (TRUE or FALSE)	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	
d	VISIBLE_STRING255	DC		Description of the status element	

5.24 Common Data Class: SPS_WD

Description: Single Point Status (without Description)

CDC Class: SPS

Attribute	Type	FC	Enumeration	Comment	X
stVal	BOOLEAN	ST		The element status (TRUE or FALSE)	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	

5.25 Common Data Class: SPS_WD_NS

Description: Single Point Status (without Description, with namespace)

CDC Class: SPS

Attribute	Type	FC	Enumeration	Comment	X
stVal	BOOLEAN	ST		The element status (TRUE or FALSE)	
q	Quality	ST		The quality of the status value	
t	TimeStamp	ST		Timestamp of the last change in state	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.26 Common Data Class: WYE_SEG_ANG_NS

Description: Phase to ground measurements for a 3-Phase system with dataNs

CDC Class: WYE

Attribute	Type	FC	Enumeration	Comment	X
phsA	CMV_MAG_ANG_FLOAT	--		Measurement values for Phase A	
phsB	CMV_MAG_ANG_FLOAT	--		Measurement values for Phase B	
phsC	CMV_MAG_ANG_FLOAT	--		Measurement values for Phase C	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.27 Common Data Class: WYE_SEG_ANONYMOUS

Description: Phase to ground measurements for anonymous phase of a 3-Phase system

CDC Class: WYE

Attribute	Type	FC	Enumeration	Comment	X
neut	CMV_MAG_ANG_FLOAT	--		Measurement values for neutral input	
dataNs	VISIBLE_STRING255	EX		Data name space	

5.28 Common Data Class: WYE_SEG_D

Description: Phase to ground measurements for a 3-Phase system (w.r.t Phase Segregation + Description)

CDC Class: WYE

Attribute	Type	FC	Enumeration	Comment	X
phsA	CMV_MAG_FLOAT	--		Measurement values for Phase A	
phsB	CMV_MAG_FLOAT	--		Measurement values for Phase B	
phsC	CMV_MAG_FLOAT	--		Measurement values for Phase C	
d	VISIBLE_STRING255	DC		Description of the status element	

5.29

Common Data Class: WYE_SEG_FAULT

Description: Phase to ground measurements for a 3-Phase system

CDC Class: WYE

Attribute	Type	FC	Enumeration	Comment	X
phsA	CMV_MAG	--		Measurement values for Phase A	
phsB	CMV_MAG	--		Measurement values for Phase B	
phsC	CMV_MAG	--		Measurement values for Phase C	
d	VISIBLE_STRING255	DC		Description of the status element	
dataNs	VISIBLE_STRING255	EX		Data name space	

6 COMMON DATA ATTRIBUTE TYPE DEFINITIONS

Common data attribute types, known herein as components, are defined for use in the Common Data Classes defined in the sections above.

6.1 Component: AnalogueValue_Float

Comment: General analogue value (w.r.t Floating Point value)

Parent Type: AnalogueValue

Attribute	Type	Enumeration	Comment	X
f	FLOAT32		Floating point value	

6.2 Component: Originator

Comment: Originator of the last change of data attribute representing the value of a controllable data object

Parent Type:

Attribute	Type	Enumeration	Comment	X
orCat	ENUMERATED8 (MMS Type: INT8)	orCategory	Originator category (Not-supported, bay-control, station-control, remote-control, automatic-bay, automatic-station, automatic-remote, maintenance or process)	
orIdent	OCTET_STRING64		Originator identification (Null value indicates unknown or not reported)	

6.3 Component: RangeConfig_Deadband

Comment: Measurement range configuration

Parent Type: RangeConfig

Attribute	Type	Enumeration	Comment	X
min	AnalogueValue_Float		Minimum process measurement for which values of i and f are considered within limits	
hhLim	AnalogueValue_Float		High High range limit	
hLim	AnalogueValue_Float		High range limit	
lLim	AnalogueValue_Float		Low range limit	
max	AnalogueValue_Float		Maximum process measurement for which values of i and f are considered within limits	
llLim	AnalogueValue_Float		Low Low range limit	

6.4 Component: Unit

Comment: SI Unit definitions

Parent Type:

Attribute	Type	Enumeration	Comment	X
multiplier	ENUMERATED16 (MMS Type: INT8)	multiplier	Multiplier value, the default of which is 0 (i.e. multiplier = 1)	
SIUnit	ENUMERATED16 (MMS Type: INT8)	SIUnit	SI Unit	

6.5 Component: Unit_Multiplier

Comment: SI Unit definitions

Parent Type: Unit

Attribute	Type	Enumeration	Comment	X
multiplier	ENUMERATED16 (MMS Type: INT8)	multiplier	Multiplier value, the default of which is 0 (i.e. multiplier = 1)	
SIUnit	ENUMERATED16 (MMS Type: INT8)	SIUnit	SI Unit	

6.6 Component: Vector_Magnitude_Float

Comment: Complex vector (w.r.t Floating Point Magnitude value)

Parent Type: Vector

Attribute	Type	Enumeration	Comment	X
mag	AnalogueValue_Float		The magnitude of the complex value	

6.7 Component: Vector_MagnitudeAngle_Float

Comment: Complex vector (w.r.t Floating Point Magnitude and Angle values)

Parent Type: Vector

Attribute	Type	Enumeration	Comment	X
mag	AnalogueValue_Float		The magnitude of the complex value	
ang	AnalogueValue_Float		The angle of the complex value (the unit is degrees)	

7 ENUMERATED TYPE DEFINITIONS

The following sub-sections specify the enumerations that are associated to some Common Data Class attributes. The definition of the enumerations are according to IEC61850-7-3 and IEC61850-7-4 unless otherwise stated.

7.1 Enumerated Type: AddCause

Description: AddCause

Ordinal	Semantic
0	Unknown
1	Not-supported
2	Blocked-by-switching-hierarchy
3	Select-failed
4	Invalid-position
5	Position-reached
6	Parameter-change-in-execution
7	Step-limit
8	Blocked-by-Mode
9	Blocked-by-process
10	Blocked-by-interlocking
11	Blocked-by-synchrocheck
12	Command-already-in-execution
13	Blocked-by-health
14	1-of-n-control
15	Abortion-by-cancel
16	Time-limit-over
17	Abortion-by-trip
18	Object-not-selected

7.2 Enumerated Type: Beh

Description: Behaviour

Ordinal	Semantic
1	on
2	blocked
3	test
4	test/blocked
5	off

7.3 Enumerated Type: Bypass

Description: Bypass

Ordinal	Semantic
0	locking-bypass
1	mode-bypass
2	automation-bypass

Ordinal	Semantic
3	uniqueness-bypass
4	select-bypass
5	status-bypass

7.4 Enumerated Type: **ctlModel**

Description: Control Model

Ordinal	Semantic
0	status-only
1	direct-with-normal-security
2	sbo-with-normal-security
3	direct-with-enhanced-security
4	sbo-with-enhanced-security

7.5 Enumerated Type: **dir**

Description: Direction

Ordinal	Semantic
0	unknown
1	forward
2	backward
3	both

7.6 Enumerated Type: **Health**

Description: Health

Ordinal	Semantic
1	Ok
2	Warning
3	Alarm

7.7 Enumerated Type: **Mod**

Description: Mode

Ordinal	Semantic
1	on
2	blocked
3	test
4	test/blocked
5	off

7.8 Enumerated Type: **multiplier**

Description: Exponents of the multiplier value in base 10.

Ordinal	Semantic
-24	y
-21	z

Ordinal	Semantic
-18	a
-15	f
-12	p
-9	n
-6	μ
-3	m
-2	c
-1	d
0	
1	da
2	h
3	k
6	M
9	G
12	T
15	P
18	E
21	Z
24	Y

7.9 Enumerated Type: orCategory

Description: orCategory

Ordinal	Semantic
0	not-supported
1	bay-control
2	station-control
3	remote-control
4	automatic-bay
5	automatic-station
6	automatic-remote
7	maintenance
8	process

7.10 Enumerated Type: seqT

Description: Sequence Measurement Type

Ordinal	Semantic
0	pos-neg-zero
1	dir-quad-zero

7.11 Enumerated Type: SIUnit

Description: SI Units derived from ISO/IEC 1000

Ordinal	Semantic
-16	years

Ordinal	Semantic
-15	months
-14	weeks
-13	V/s
-12	mins
-11	hours
-10	days
-9	°F
-8	ratio
-7	miles
-6	inches
-5	feet
-4	df/dt
-3	Hz/s
-2	%
-1	pu
1	none
2	m
3	kg
4	s
5	A
6	K
7	mol
8	cd
9	deg
10	rad
11	sr
21	Gy
22	q
23	°C
24	Sv
25	F
26	C
27	S
28	H
29	V
30	ohm
31	J
32	N
33	Hz
34	lx
35	Lm
36	Wb
37	T
38	W

Ordinal	Semantic
39	Pa
41	m ²
42	m ³
43	m/s
44	m/s ²
45	m ³ /s
46	m/m ³
47	M
48	kg/m ³
49	m ² /s
50	W/m K
51	J/K
52	ppm
53	1/s
54	rad/s
61	VA
62	Watts
63	VAr
64	phi
65	cos(phi)
66	Vs
67	V ²
68	As
69	A ²
70	A ² t
71	VAh
72	Wh
73	VArh
74	V/Hz

8 MMS Data-Type Conversions

The following table shows the relationships between the Part 7 and Part 8-1 data types. The definitions presented above use Part 7 data types, however these are subject to 'translation' when exposed over an MMS (Part 8-1) interface:

Part 7 Type	MMS Type	Part 7 Description
BOOLEAN	Bool	Logical TRUE/FALSE value
BSTR16	Bstring16	Bit string 16
BVstring13	BVstring13	Variable bit string (upto 13 bits)
Check	BVstring2	Control Object check flags
CODED_ENUM	Byte	Coded enumeration
CODED_ENUM2	Byte	Coded enumeration (2)
Dbpos	Bstring2	Switch positions
EntryTime	Btime6	8.1 Section 8.1.3.7
ENUMERATED16	Short	16 bit enumerated value
ENUMERATED8	Byte	8 bit enumerated value
FLOAT32	Float	32 bit floating point value
FLOAT64	Double	64 bit floating point value
INT16	Short	16 bit signed integer value
INT16U	Ushort	16 bit unsigned integer value
INT24U	Ulong	24 bit unsigned integer value
INT32	Long	32 bit signed integer value
INT32U	Ulong	32 bit unsigned integer value
INT64	Int64	64 bit signed integer value
INT8	Byte	8 bit signed integer value
INT8U	Ubyte	8 bit unsigned integer value
OCTET_STRING6	Ostring6	6 character string (8 bits per character)
OCTET_STRING64	OVstring64	64 character string (8 bits per character)
OCTET_STRING8	OVstring8	8 character string (8 bits per character)
Quality	BVstring13	IEC61850 Quality
TimeStamp	Uttime	IEC61850 Time stamp
UNICODE_STRING255	UTF8Vstring255	255 character string (16 bits per unicode character)
UTC_TM	Uttime	UTC Timestamp
VISIBLE_STRING255	Vstring255	255 character string
VISIBLE_STRING64	Vstring64	64 character string
VISIBLE_STRING65	Vstring65	65 character string
VISIBLE_STRING97	Vstring97	97 character string



Customer Care Centre

<http://www.schneider-electric.com/cc>

Schneider Electric

35 rue Joseph Monier
92506 Rueil-Malmaison
FRANCE

Phone: +33 (0) 1 41 29 70 00

Fax: +33 (0) 1 41 29 71 00

www.schneider-electric.com

Publisher: Schneider Electric

Publication: Easergy MiCOM P746/EN MC/L72 Numerical Busbar Protection Relay Software Version: C3 Hardware Suffix: M IEC61850 Edition: 1

10/2016